





Fold-Down Handle For Compact Storage

Swivel Out Regulator For Easy Fuel Connection

Heats Up To 200 Square Feet For Up To 110 Hours.


- Single Control For Starting And Heat Adjustment
- "Low-Oxygen" Safety Shut-Off System
- Tip-Over Safety Shut-Off

## **Temporary Heat For:**

- Tents / Campers / RVs
- Hunting Blinds
- Workshops / Worksites
- Porches / Patios / Decks
- Cabins / Shelters
- Garages
- Picnics / Tailgate Parties
- Ice Fishing Shanties
- Truck & Horse Trailers
- Emergency Heat



Uses 1 lb. Or 20 lb. Propane Cylinder
With Ontional Hose Connection\*





America's Most Popular Brand Of Portable Heaters

> Provides 3 To 6 Hours Of Heat With 11b. Propage Cylinder; 48 To 110 Hours With 20 lb. Tank.

## Meet The Latest Generation Of Safe And Convenient Portable Heat!

Mr. Heater, the innovator of portable indoor-safe heating technology, now adds 21st Century design and improved convenience features to America's most popular indoor-safe radiant heater – the Portable Buddy.

With a larger heating surface, fold-down handle, swivel-out fuel connection, and an easy-start four-position control, Mr. Heater sets the new standard for today's portable propane heaters.

Plus, the Portable Buddy is certified by CSA International with low-oxygen (ODS) and tip-over safety shut-off systems to provide safe, reliable heat anytime, anywhere.

Whether you're tent camping, RV'ing or warming up chilly workspaces, you need a Buddy!



## Special Features

- Fold-Down Handle Reduces Storage Space
- Four Position Control With Built-In Piezo Igniter And Lo/Hi Heat Settings
- High Temperature Wire Guard
- Swivel-Out Connection For Easy LP Cylinder And Hose Installation
- Large Heating Surface Directs Radiant Heat Over Wider Area
- Durable Porcelain **Coated Reflector**
- Low-Oxygen Safety Shut-Off (ODS)
- Ceramic Burner Tile Mounted With Shock Absorbing Insulation For Durability And Easy Replacement
- Tip-Over Safety Shut-Off
  - CSA Certified For Indoor Use In The USA (Outdoor Use In Canada)
  - Limited 1-Year Warranty

## **Specifications**

Model No. MH9BX Stock No. F232000 4,000/9,000 BTU/HR Gas: Propane

Operating Position: Vertical Valve Positions: Off, Pilot, Lo, & Hi

Heating Time:

1lb. Cylinder: 3 to 6 hours 20lb. Cylinder: 48 to 110 hours Product Dimensions: 13.4"W X 15"H X 7.7"D

Folded Dimensions: 13.4"W X 13.3"H X 7.7"D Shipping Weight: 9.5lbs. UPC Code: 089301320000

UPC Code Canada: 089301320505 UPC Code California: 089301320253



**Optional Hoses And Fuel Filter** Fuel filter prevents contaminants from entering heater.

- F273701 5 ft. Hose Assembly
- F273702 12 ft. Hose Assembly
- F273699 Fuel Filter
- F273704 10 ft. Buddy Series Hose (No Fuel Filter Required)



**Key Shaped Mounting Holes For Easy Wall Mounting** 



Low-Oxygen Safety Shut-Off System

Not designed for permanent installation or for use above 7,000 feet.

When using a 20 lb. tank, place cylinder outdoors. Never bring a 20 lb. cylinder indoors. NOTE: Adequate ventilation must be provided, see operating instructions.

Patent Numbers: 6,340,298 6,648,635 6,884,065 Additional Patents Pending





★ CERTIFIED FOR INDOOR USE IN USA, OUTDOOR USE ONLY IN CANADA.



