

SAFETY DATA SHEET

Klean Strip Paint Thinner for CARB

Page: 1
 Printed: 04/13/2015
 Revision: 04/13/2015
 Supersedes Revision: 03/27/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Paint Thinner for CARB

Company Name: W. M. Barr
 2105 Channel Avenue
 Memphis, TN 38113

Phone Number: (901)775-0100

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Paint, stain, and varnish thinning.

Synonyms: GKPT94002CA, GKPT94002PCA, QKPT94003CA, GKPT94400CB, CKPT94402CA

Additional Information: This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 4
Aspiration Toxicity, Category 1



GHS Signal Word: **Danger**

GHS Hazard Phrases: H227: Combustible liquid.
 H304: May be fatal if swallowed and enters airways.


GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P331: Do NOT induce vomiting.
 P370+378: In case of fire, use dry chemical powder to extinguish.

GHS Storage and Disposal Phrases: P403+235: Store in cool/well-ventilated place.
 P405: Store locked up.
 P501: Dispose of contents/container according to local, state and federal regulations.

Hazard Rating System:

HEALTH	*	1
FLAMMABILITY	2	2
PHYSICAL	0	0
PPE	X	X



HMIS:

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

SAFETY DATA SHEET

Klean Strip Paint Thinner for CARB

Page: 2

Printed: 04/13/2015

Revision: 04/13/2015

Supersedes Revision: 03/27/2015

Potential Health Effects (Acute and Chronic):

INHALATION:

Vapor harmful. Danger of serious damage to health by prolonged exposure through inhalation.

SKIN CONTACT:

Prolonged skin contact may cause skin irritation and/or dermatitis.

EYE CONTACT:

Liquid contact may cause irritation.

INGESTION:

Harmful or fatal if swallowed. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage.

TARGET ORGANS: skin, central nervous system

PRIMARY ROUTES OF ENTRY: inhalation, skin contact

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
64742-47-8	Hydrotreated light distillate (petroleum)	99.0 -100.0 %	OA5504000

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Skin:

Wash the skin thoroughly with water and soap, if available, while removing contaminated clothing. Seek medical attention if irritation develops or persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure:

See Potential Health Effects.

SAFETY DATA SHEET
Klean Strip Paint Thinner for CARB

Page: 3
Printed: 04/13/2015
Revision: 04/13/2015
Supersedes Revision: 03/27/2015

5. FIRE FIGHTING MEASURES

Flammability Classification: NFPA Class IIIA

Flash Pt: 190.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, foam, or water spray / fog.

Unsuitable Extinguishing Media: Do not use straight water streams, as this may spread the fire.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Material float on water. Do not use straight water streams, as this may spread the fire.

Flammable Properties and Hazards: Material will float on water.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Isolate the immediate area. Prevent unauthorized entry. Eliminate all sources of ignition in area and downwind of the spill area. Stay upwind, out of low areas, and ventilate closed spaces before entering. All equipment used when handling this product must be grounded or non-sparking. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill for possible collection and reuse or disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Ensure all equipment is electrically grounded before beginning transfer operations.

Avoid prolonged skin contact.

Precautions To Be Taken in Storing: Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.

Klean Strip Paint Thinner for CARB

Printed: 04/13/2015

Revision: 04/13/2015

Supersedes Revision: 03/27/2015

Respiratory Equipment (Specify Type):	<p>For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.</p> <p>For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.</p> <p>A dust mask does not provide protection against vapors.</p>
Eye Protection:	Chemical splash goggles should be worn to prevent eye contact.
Protective Gloves:	Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.
Other Protective Clothing:	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.
Engineering Controls (Ventilation etc.):	<p>Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.</p> <p>Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.</p>
Work/Hygienic/Maintenance Practices:	<p>Wash hands thoroughly after use and before eating, drinking, or smoking.</p> <p>Do not eat, drink, or smoke in the work area.</p> <p>Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.</p>

SAFETY DATA SHEET
Klean Strip Paint Thinner for CARB

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Aromatic hydrocarbon-like odor. Free and clear, water-white liquid.

Melting Point: No data.

Boiling Point: No data.

Autoignition Pt: No data.

Flash Pt: 190.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: No data. UEL: No data.

Specific Gravity (Water = 1): 0.7693 - 0.8093

Density: 6.567 LB/GL

Vapor Pressure (vs. Air or mm Hg): 0.17 MM HG at 68.0 F

Vapor Density (vs. Air = 1): > 1

Evaporation Rate: < 1

Solubility in Water: Not Soluble

Viscosity: water thin

Percent Volatile: 100.0 % by weight.

VOC / Volume: 2.8800 G/L

Additional Physical Information Product category, Paint Thinner, LVP solvent and is not a VOC as defined by the California Air Resources Board (CARB).

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability: No data available.

Incompatibility - Materials To Avoid: Incompatible with oxidizing agents.

Hazardous Decomposition Or Byproducts: Thermal decomposition may produce carbon monoxide and carbon dioxide.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions: No data available.

SAFETY DATA SHEET
Klean Strip Paint Thinner for CARB

Page: 6
Printed: 04/13/2015
Revision: 04/13/2015
Supersedes Revision: 03/27/2015

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Refer to section 2 for acute and chronic effects.

Chronic Toxicological Effects:

Carcinogenicity/Other Information: ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material, Not Regulated

DOT Hazard Class:

UN/NA Number:

Additional Transport Information: The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No

This material meets the EPA Yes No Acute (immediate) Health Hazard

'Hazard Categories' defined Yes No Chronic (delayed) Health Hazard

for SARA Title III Sections Yes No Fire Hazard

311/312 as indicated: Yes No Sudden Release of Pressure Hazard

Yes No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

SAFETY DATA SHEET
Klean Strip Paint Thinner for CARB

Regulatory Information Statement: All components of this material are listed on the TSCA Inventory or are exempt.

16. OTHER INFORMATION

Revision Date: 04/13/2015

Preparer Name: W.M. Barr EHS Department (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.