



8900 Series

- 8900C – 24 GPM Pump/ Cast Iron
- 8900C R– 24 GPM Pump/ Cast Iron Reverse Rotation/Clockwise
- DKP-8900C – 24 GPM Pump/ Cast Iron #90300 Coupler and Torque Arm Kit
- 8900DSS – 24 GPM Pump/ Diamond Stainless Steel
- 8900DSSR – 24 GPM Pump/ Diamond Stainless Steel Reverse Rotation / Clockwise
- DPK-8900DSS - 24 GPM Pump/ Diamond Stainless Steel #90300 Coupler and Torque Arm Kit

Pump:

- Type: 8-roller design
- Max Pressure: 300 PSI
- Max Recommended Temperature: 140°F
- Port Size: 1" FNPT
- Mounting:
- Base Mounted: 3/8"– 18UNC-2B (2 holes)
- PTO: Use Torque Bar and Chain
- Shaft: 15/16" Solid Shaft
- Weight: 14 lbs

Materials of Construction:

- Pump Housing: Cast Iron or Stainless Steel
- Rollers: 3/4" Ultra Rollers
- Shaft Seals: Viton cartridge type lip seals
- Shaft & Rotor:
- C: Extra-fine finish 404 SST
- DSS: Extra-fine finish 416 SST
- Bearings: Permanently-lubricated, heavy-duty sealed bearings

8900 Series Performance

PSI	540 RPM	850 RPM	1000 RPM
0	13.0	20.2	24.0
20	12.4	19.8	23.2
40	11.6	19.1	22.4
100	10.6	18.6	21.8
200	8.9	15.7	18.0
300	7.0	14.0	17.1