

# EFSUB10-253

## 4" Submersible Pump, 3-Wire

### 1 HP - 25 GPM

**APPLICATIONS**

- Provides Smooth Water Passages for Maximum Efficiency

**FEATURES**

- 1-1/4" FNPT Discharge Cast Iron Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing REsin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

**SPECIFICATIONS**

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x W x H)	PALLET QUANTITY
856594003787	1 Year	27.56 Lbs.	25.8" x 3.5"	108



**PERFORMANCE CHART**

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER										
				20	40	60	80	100	150	200	250	300	350	400
EFSUB10-253	1	25	230	-	-	22.7	20	19	-	-	-	-	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE