

# EFSUB5-122-1

## 4" Submersible Pump, 2-Wire

### 1/2 HP - 12 GPM



**APPLICATIONS**

- Provides Smooth Water Passages for Maximum Efficiency

**FEATURES**

- 1-1/4" FNPT Discharge Cast Iron Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing REsin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

**SPECIFICATIONS**

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x D)	PALLET QUANTITY
856594003701	1 Year	23.8 Lbs.	23.4" x 3.5"	108

**PERFORMANCE CHART**

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER										
				20	40	60	80	100	150	200	250	300	350	400
EFSUB5-122-1	1/2	10	115	-	-	11	9.8	8.7	-	-	-	-	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE