

WATER WELL PUMPS - 4" Submersible Pumps



EFSUB10-122

4" Submersible Pump, 2-Wire

1 HP - 12 GPM

APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

FEATURES

- 1-1/4" FNPT Discharge Cast Iron Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing RESin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

SPECIFICATIONS

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x W x H)	PALLET QUANTITY
856594003756	1 Year	32.12 Lbs.	30.6" x 3.5"	108



PERFORMANCE CHART

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER										
				20	40	60	80	100	150	175	200	250	300	350
EFSUB10-122	1	10	230	-	-	-	-	-	-	11.1	10.5	9.7	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE

ECO-FLO PRODUCTS INCORPORATED

1899 Cottage Street, Ashland, Ohio 44805 • Customer Service: 1-877 326-3561 • Fax: 1-877 326-1994 • www.ecofloproducts.com