

EFSUB15-123

4" Submersible Pump, 3-Wire

1-1/2 HP - 14 GPM

APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

FEATURES

- 1-1/4" FNPT Discharge Cast Iron Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing REsin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

SPECIFICATIONS

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x W x H)	PALLET QUANTITY
856594003770	1 Year	30.91 Lbs.	33.6" x 3.5"	48



PERFORMANCE CHART

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER											
				20	40	60	80	100	150	200	250	300	350	400	
EFSUB15-123	1-1/2	10	230	-	-	-	-	-	-	-	11.5	10.8	8.1	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE