

Refractory Cement

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Refractory Cement

SDS Number: 33

Product Code: 610, 611, 612 **Revision Date:** 9/24/2019

Version:

Product Description: Pre-mixed cement

Product Use: For masonry to masonry repairs; Use to set, coat, or repair brick in fire boxes.

Supplier Details: Rutland Products

7 Crabtree Road Jacksonville, IL 62650

Contact: Faith Nergenah, Brian Miller

Phone: 217-245-7810 **Fax:** 217-245-1194

Email: faith@rutland.com bmiller@rutland.com

Web: www.rutland.com

Emergency: CHEMTREC (800) 424-9300

SDS Number: 33 Page: 1/5 Revision Date: 9/24/2019



Refractory Cement

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Corrosive to Metals, 1

Health, Acute toxicity, 5 Oral

Health, Skin corrosion/irritation, 1 A

Health, Serious Eye Damage/Eye Irritation, 1

Environmental, Hazards to the aquatic environment - Acute, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H290 - May be corrosive to metals

H303 - May be harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H402 - Harmful to aquatic life

GHS Precautionary Statements:

P234 - Keep only in original container.

P260 - Do not breathe dust or mist.

P264 - Wash skin thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician.

P321 - Specific treatment (see supplemental first aid instructions on this label).

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant stainless steel container with a resistant inner liner.

P501 - Dispose of contents/ container to an approved waste disposal plant.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Ingestion; Skin;

Skin Contact: May cause irritation.

Eye Contact: May cause irritation.

Ingestion: Ingestion is not an applicable route of entry for intended use. May be harmful if swallowed.



Refractory Cement

3 COMPOSITION/INFORMATION OF INGREDIENTS

	Chemical Ingredients:
CAS#	% Chemical Name:
1332-58-7 1310-73-2 1344-09-8 13983-17-0 14808-60-7	Kaolin Sodium hydroxide (NaOH) Silicic acid, sodium salt Calcium Metasilicate (Wollastonite) Silica, crystalline

Percentages withheld, Trade Secret

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Seek medical attention if cough or other symptoms develop or persist.

Skin Contact: Wash with plenty of water. Get medical attention if irritation develops or persists.

Eye Contact: Immediately flush eyes with plenty of water. After initial flushing, remove contact lenses and continue flushing for at

least 15 minutes. If effects occur, consult a physician, preferably an ophthalmologist. May cause injury due to

mechanical action.

Ingestion: If Swallowed, DO NOT INDUCE VOMITING. Give one cup (8 ounces or 240 ml) of water or milk if available and

transport to a medical facility. Never give anything by mouth to an unconscious or convulsive person.

5 FIRE FIGHTING MEASURES

Flammability: Non-Flammable

Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Absorb spilled material and place in appropriate container for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes and skin. Use in a well-ventilated area. Avoid inhalation of vapors and mists.

Storage Requirements: Keep container closed to prevent drying out.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: A system of local and/or general exhaust is recommended to keep employee exposures as low as

possible.

Personal Protective EYES AND FACE: Wear safety glasses with side shields. Chemical splash goggles and face shield **Equipment:** (ANSI Z87.1 or approved equivalent) are recommended.

SKIN: Wear protective clothing, including long sleeves and gloves, to prevent skin contact. Thoroughly

wash clothing before reuse. RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory

equipment.

SDS Number: 33 Page: 3 / 5 Revision Date: 9/24/2019



Refractory Cement

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Buff

Physical State: Paste Odor: Mild

Odor Threshold:Not AvailableMolecular Formula:Not AvailableParticle Size:Not AvailableSolubility:Soluble in waterSpec Grav./Density:1.8Softening Point:Not Available

 Viscosity:
 Not Available
 Percent Volatile:
 Not Available

 Saturated Vapor
 Not Available
 Heat Value:
 Not Available

Saturated Vapor Not Available F
Concentration:

Not Available **Boiling Point:** Not Available Freezing/Melting Pt.: Not Available **Flash Point:** Flammability: Not Available **Partition Coefficient:** Not Available Octanol: Not Available Vapor Pressure: Not Available Vapor Density: Not Available 12.5 VOC: Not Available pH:

Evap. Rate: Not Available **Bulk Density:** Not Available

Molecular weight: Not Available Auto-Ignition Temp: Not Available

Decomp Temp: Not Available UFL/LFL: Not Available

10 STABILITY AND REACTIVITY

Reactivity: This product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Product is stable under normal conditions.

Conditions to Avoid: None Known

Materials to Avoid: Strong Acids; Strong Oxidizing Agents;

Hazardous Decomposition: None Known
Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

No data available.

12 ECOLOGICAL INFORMATION

No information available

13 DISPOSAL CONSIDERATIONS

Dispose of this product in accordance with all applicable local, state and federal regulations.

14 TRANSPORT INFORMATION

Not Regulated

SDS Number: 33 Page: 4 / 5 Revision Date: 9/24/2019



Refractory Cement

15

REGULATORY INFORMATION

RQ (CAS#) Substance - Reg Codes

Kaolin (1332-58-7) CAPROP65, OSHAWAC, PA, TSCA, TXAIR

RQ(1000LBS), Sodium hydroxide (NaOH) (1310-73-2) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

Silicic acid, sodium salt (1344-09-8) TSCA

Calcium Metasilicate (Wollastonite) (13983-17-0)

Silica, crystalline (14808-60-7) GADSL, MASS, NRC, OSHAWAC, PA, PROP65, TSCA, TXAIR



This product can expose you to chemicals including Silica, Crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity

CAPROP65 = California Prop 65

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

MASS = MA Massachusetts Hazardous Substances List

GADSL = Global Automotive Declarable Substance List (GADSL)

NRC = Nationally Recognized Carcinogens

16

OTHER INFORMATION

PREPARED BY: Brian Miller

MANUFACTURER DISCLAIMER: The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to their circumstances.

Revision Date: 9/24/2019

SDS Number: 33 Page: 5 / 5 Revision Date: 9/24/2019