

## "QUICK DRAW" POLARIS MOUNTING PLATE MODEL: QD800PMP

## **▲ WARNING**

READ ALL INSTRUCTIONS BEFORE INSTALLING POLARIS PLATE. NOTE: Failure to read instructions before use could result in injury or death.

## Instructions for Installation and Use:



Fig. 1

## **CONTENTS: SEE FIG. 1**

- 1- Quick Draw Polaris Plate (QD800PMP)
- **4** 1/4" Knob Screws
- **4** 1/4" Flat Washers
- $4 \frac{1}{4} 20 \times \frac{1}{2}$ " Floor Screws
- 4 M6-1.00 x 40mm Cap Screws

With the Quick Draw Gun Rack facing towards you, attach gun rack to plate using 4- 1/4" knob screws. (See Figs. 2 & 3.) Tighten thoroughly.




Fig. 2




Fig. 3

Position Gun Rack / Plate assembly onto floorboard of Ranger to locate the 4 floorboard screws that will need to be removed for installation. (See Fig. 4). Using the torx wrench provided in the Ranger tool kit, Remove the 4 screws from floorboard. (See Fig. 5)





Fig. 4 Fig. 5

\*\*NOTE\*\*TO MINIMIZE POTENTIAL INSTALLATION PROBLEMS, PLEASE FOLLOW THESE STEPS EXPLICITLY. Position assembly back over holes and replace 2 original screws on driver's side. Turn screws to engage threads but do not tighten. There will be a gap between plate & floorboard. (See Fig. 6) While pressing down on passenger side of plate, start remaining 2 original screws. Once all 4 screws are engaged, tighten completely. (See Fig. 6A & 6B)
\*\*NOTE\*\*IF LONGER SCREWS ARE NEEDED, REPLACE ORIGINAL SCREWS WITH 4- 1/4-20 x 1 ½" FLOOR SCREWS



Fig. 6



Fig. 6A



Fig. 6B

WARNING: PLEASE READ AND FOLLOW ALL INSTRUCTIONS AND WARNINGS FURNISHED WITH QD800 QUICK DRAW GUN RACK.

For more information about this or other products, contact us at:

Great Day, Inc.