

PLEASE READ AND FOLLOW ALL INSTRUCTIONS AND WARNINGS INCLUDED WITH THIS PRODUCT.

****  WARNING ****

- NEVER PLACE A LOADED GUN(S) INTO GUN RACK.
- NEVER HAVE AMMUNITION READILY AVAILABLE OR ACCESSIBLE TO CHILDREN OR OTHER PASSENGERS.
 - NEVER ALLOW CHILDREN TO INSTALL OR REMOVE GUN(S) FROM GUN RACK WITHOUT ADULT SUPERVISION.
- NEVER USE GUN RACK OR FIREARMS IN ANY MANNER THAT IS IN VIOLATION OF APPLICABLE STATE OR FEDERAL LAWS.
- DO NOT MOUNT GUN RACK INTO VEHICLE WHERE IT MAY IMPAIR DRIVER'S VISION.
 - DO NOT INSTALL GUN RACK IN VEHICLE WHERE IT COULD CAUSE AIRBAG INTERFERENCE.
- MAKE SURE THE MUZZLE(S) OF THE GUN(S) IS POINTED UP AND AWAY FROM ANY VEHICLE OCCUPANTS.
- DO NOT MOUNT THE GUN RACK INTO VEHICLE WHERE IT WILL INTERFERE IN ANY WAY WITH THE OPERATION OF THE VEHICLE. I.E. STEERING WHEEL, BRAKE PEDAL OR GAS PEDAL.
- NEVER USE GUN RACK TO CARRY ANYTHING OTHER THAN AN UNLOADED GUN(S) I.E. AXES, KAISER BLADES, SHOVELS.....
- MAKE SURE GUN(S) ARE PROPERLY SECURED INTO CRADLES WITH VELCRO STRAPS BEFORE OPERATING VEHICLE.
 - NEVER TRY TO INSTALL OR REMOVE GUN(S) FROM THE GUN RACK WHILE OPERATING THE VEHICLE OR WHILE THE VEHICLE IS MOVING.

****  WARNING ****

PLEASE READ AND FOLLOW ALL INSTRUCTIONS AND WARNINGS INCLUDED WITH THIS PRODUCT.



“CENTER-LOK” Overhead Gun Rack

**Model: CL1500-OGR/CL1501-OGR FOR ALL FULL SIZE 4 DOOR CREW CAB PICKUP TRUCKS
PLEASE READ ALL INSTRUCTIONS AND WARNINGS BEFORE USING THE “CENTER-LOK”
OVERHEAD GUN RACK FOR FULL SIZE 4DOOR CREW PICKUP TRUCKS.**

NOTE: FAILURE TO READ INSTRUCTIONS & WARNINGS COULD RESULT IN INJURY OR DEATH.

INSTRUCTIONS FOR INSTALLATION AND USE:



CONTENTS

CONTENTS:

- 2 – GUN CLIP ASSEMBLIES
 - 2 – MOUNTING BAR ASSEMBLIES
 - 2 – 1/4" X 1 3/4" BOLTS
 - 2 – 1/4" LOCKNUTS
 - 4 – FLAT WASHERS
 - 2 – 3/4" FLAT WASHERS
 - 1 - CENTER-LOK TENSION ROD W/4 JAM NUTS
- **NOTE**THE FLAT WASHER IS TO BE INSTALLED BETWEEN THE JAM NUTS & THE GUN RACK BODY.**



FIG. 1

CL-1500 mounting bars have 3 sets of holes. Choose holes that best accommodate gun(s) to be placed in rack. Attach gun clips to mounting bars using 1/4" x 1-3/4" bolts, flat washers, and locknuts (**FIG.1**) ****NOTE****Gun clip assemblies are designed with a 1" offset to allow for optimum separation of guns. The barrel sticker on gun clips indicates the longer side of gun clip assemblies. The arrows on stickers should be pointing in opposite directions.



FIG. 2

Slide Center-Lok rod assembly into open ends of mounting bars. (FIG. 2) Center-Lok overhead gun rack is now fully assembled and ready for installation.



FIG. 3

While seated on backseat, slide 1 side of assembled gun rack between headliner and center pillar until plate is resting against metal frame of truck between doors. Repeat process with other side of gun rack. FIG. 3



FIG. 4

With gun rack mounting bars spread between the center pillars of truck, turn the 2 outside jam nuts in opposite directions until they are hand tightened against the mounting bars. FIG. 4



FIG. 5

Using 2 adjustable wrenches, completely tighten the 2 outside jam nuts against mounting bars. FIG. 5



FIG. 6

Turn the 2 inside jam nuts by hand until they are against the 2 outside jam nuts. Using 2 adjustable wrenches lock the 2 jam nuts tight against each other. **FIG. 6** This will prevent the gun rack from becoming loose.

****NOTE** ONCE GUN RACK IS INSTALLED IN PICKUP TRUCK PLACE GUN(S) INTO GUN RACK AND CHECK POSITION FOR HEAD CLEARANCE. ****

****NOTE** GUN CLIPS ARE BENDABLE AND CAN BE MOLDED BY HAND FOR THE BEST FIT OF GUN(S) BEING PLACED INTO RACK. ****

For more information about this or other products, contact us at:

Great Day, Inc.

604 Kimbrough Dr. * Tallulah, LA 71282 * (866) 649-1918 * www.greatdayinc.com