

# JLite LED Equipment Lights

## Versatile Lighting For A Variety Of Applications

Durable housings, sealed construction and easy-mount brackets make Jameson JLite ideal for a wide variety of general-purpose lighting applications: Construction vehicles, utility trucks, forklifts, ATV's, golf carts, boats and more!

- IP65 – Protected against dust, dirt and low-pressure water jets
- Durable powder-coated die-cast aluminum housing
- Corrosion resistant stainless steel mounting bracket
- Impact resistant polycarbonate lens
- Various beam patterns
- 30,000 hours rated life
- CE and RoHS certifications
- One (1) year warranty



JL33C5W

500 Lumens



JL2C7S  
JL2C7W

650 Lumens



JL11800-FL

1800 Lumens



JL16C28M  
JL16C28W

2520 Lumens



JL13C48W

2700 Lumens



JL13C65S  
JL13C65W

5460 Lumens



JL9C90S  
JL9C90W

6750 Lumens



# JLite LED Equipment Lights



	JL33C5W	JL2C7W	JL11800-FL	JL16C28W	JL13C48W	JL13C65S	JL13C65W	JL9C90S	JL9C90W
Effective Lumens	500	650	1800	2520	2700	5460		6750	
Number of LEDs	33	2	8	16	13	13		9	
Beam Patterns	Wide	Wide	Flood	Wide	Wide	Spot	Wide	Spot	Wide
Ingress Protection	IP65								
Power	5 Watts	7 Watts	18 Watts	28 Watts	30 Watts	65 Watts		90 Watts	
Current	0.4 A @ 12 VDC 0.2 A @ 24 VDC	0.6 A @ 12 VDC 0.3 A @ 24 VDC	1.4A @ 12VDC 0.7A @ 24VDC	2.3 A @ 12 VDC 1.2 A @ 24 VDC	2.5 A @ 12 VDC 1.3 A @ 24 VDC	5.4 A @ 12 VDC 2.7 A @ 24 VDC		6.3 A @ 12 VDC 3.2 A @ 24 VDC	
Voltage	10-30VDC		12-24 VDC	10-30VDC					
Operating Temp	-4°F to 122°F (-20°C to 50°C)								
Color Temp (CCT)	6000K Cool White								
Weight	0.22 lbs (0.1 kg)	0.25 lbs (0.1 kg)	1.43 lbs (0.6 kg)	0.71 lbs (0.3 kg)	1.1 lbs (0.5 kg)	2.69 lbs (1.2 kg)		6.39 lbs (2.9 kg)	
Dimensions	3.7" x 3.0" x .91"	3.7" x 2.4" x 1.8"	5.6" x 4" x 2.3"	5.5" x 4.3" x 1.9"	5.7" x 4.9" x 2.8"	6.5" x 5.6" x 3.7"		6.3" x 5.3" x 4.7"	
Termination	6" Wire Lead with Deutsch Connector (Mating Connector Included)								



## JLITE WIRING HARNESSSES

Sold Separately

Wiring	
JLWH-DT1	14' Wiring Harness With On/Off Switch & One Deutsch Connector, Battery Ring Terminals
JLWH-DT2	14' Wiring Harness With On/Off Switch & Two Deutsch Connectors, Battery Ring Terminals
JLWH-DT1-CIG	12' Wiring Harness, One Deutsch Connector & 12V Auto Plug Adapter, 10A Fuse

Visit Our Website To See Our Full Line Of Lighting Products

[www.SpartacoGroup.com](http://www.SpartacoGroup.com)

800.346.1956

PD-1010  
REV. 09/2018