

Full Frame Vented Temple Safety Glasses

Ironside®

ANSI



Rubber Nosepiece



Anti-Fog



Ultraviolet Protection



Scratch Resistant

FEATURES

Rubber nosepiece

Straight-back vented co-injected temples

CAPTURE CLAM

MODEL NO. STYLE NO.

EN678 CHB618DTCC ● Sandstone Bronze Anti-fog

EN672 CHB620DTCC ● Gray Anti-fog

EN679 CHB690DTCC ● Antique Mirror Anti-fog

POLYBAG

MODEL NO. STYLE NO.

EN618 CHB618DT ● Sandstone Bronze Anti-fog

EN620 CHB620DT ● Gray Anti-fog

EN690 CHB690DT ● Antique Mirror Anti-fog

Available in a Carhartt capture clam or polybag
Carhartt packaging design subject to change



Model No: EN690
Style No: CHB690DT



GENERAL SPECIFICATIONS

Weight: 30.6 gm

Bridge: 13 mm

Lens base: 8 curve

Lens size diagonal: 64 mm

Lens size vertical: 38 mm

Lens thickness: 2 mm

Overall length (lens - tip): 130 mm

Overall width (hinge - hinge): 134+1 mm

Closest point between temple tips: 98+5 mm

Closest point between lens: 15 mm

MATERIALS

Lens: polycarbonate (PC)

Frame: polycarbonate (PC)

Temple: polycarbonate (PC)

Temple tips: thermoplastic rubbers (TPR)

Screw: stainless steel

Nose pad: thermoplastic rubbers (TPR)

LENS + FRAME MARKING SYMBOLS

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special purpose

MODEL NO.	STYLE NO.	LENS MARKINGS	FRAME MARKING
EN678	CHB618DTCC	P+S	P Z87+
EN618	CHB618DT	P+S	P Z87+
EN672	CHB620DTCC	P+S	P Z87+
EN620	CHB620DT	P+S	P Z87+
EN679	CHB690DTCC	P+S	P Z87+
EN690	CHB690DT	P+S	P Z87+