



6438 Speed-Fill™ Elastic Crack Filler

SPEED-FILL

- Lasts 2-3 Times Longer than Basic Filler
- Non-Shrink Formula
- Flexes & Seals Cracks Up to 3/4"

DESCRIPTION: SPEED-FILL™ ELASTIC CRACK FILLER is a fast drying, rubberized compound for use on the repair of asphalt roads, driveways, pavements, expansion joints and walkways. Speeds up sealcoating jobs with quick drying. Provides a long term flexible repair on cracks and joints up to 3/4" wide. Also seals foundation walls and other pavement surfaces. Dries to dark black finish.

PREPARATION: Surfaces should be cleaned. Spray on cleaner & degreaser and free any loose materials, grease, oil and dirt, before filling cracks. Rinse out area thoroughly with a high pressure hose and allow to dry.

APPLICATION: Make sure top is secured and shake thoroughly. Unscrew top and flip over spout. Cut tip on a 45° angle to desired opening. Pour into crack filling slightly higher to allow for settling, deeper cracks will require an additional application. For larger holes and cracks use **Speed-Patch Blacktop Crack & Hole Repair**. Allow 1 hour at good drying conditions (ie: above 65 °F and under 50% relative humidity) prior to coating with a premium driveway sealer. Note: humidity and cool air/surface temperatures may lengthen cure time. Do not apply if rain is expected within 24 hours. DO NOT HEAT.

FOR BEST RESULTS: Apply when weather temperature is at least 65 °F and rising.

CLEAN-UP: Clean tools with soap and water when wet. Dried crack filler may be removed with a citrus based cleaner.

COVERAGE RATE: 3.6 qt. will fill approximately 75 linear feet of 1/4" cracks.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that cap is tight and jug is secure and upright. Do not allow jug to tumble as this may cause cap to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers. Dispose of properly. Do not use in drinking water or food systems. KEEP FROM FREEZING.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6438-9-34	1 gal.	6.25" x 6.25" x 11.5"	3.6 qt. / 3.4 L	9.6 lbs.	6/case	027134643811

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101