

TIMEMASTER®**21199****21200**

ENGINE*	10.00 ft-lb Gross Torque Briggs & Stratton® 223cc OHV	10.00 ft-lb Gross Torque Briggs & Stratton 223cc OHV
STARTER	Recoil	» Electric
SELF-PROPEL	Personal Pace® Rear Wheel Drive	Personal Pace Rear Wheel Drive
FUEL CAPACITY	1.2 Qt. / 1.1 L (Up to one hour run time)	1.2 Qt. / 1.1 L (Up to one hour run time)
PERFORMANCE		
CUTTING WIDTH	30" / 76 cm	30" / 76 cm
DECK MATERIAL	Steel Deck, Cast-Aluminum Frame	Steel Deck, Cast-Aluminum Frame
HEIGHT OF CUT	1.25" - 4.25" / 3.2 - 10. cm 2-point	1.25" - 4.25" / 3.2 - 10. cm 2-point
MULCH, REAR BAG, SIDE DISCHARGE 3-IN-1	Standard	Standard
USER FRIENDLY FEATURES		
WHEEL HEIGHT	8" / 20.3 cm Front 10" / 25.4 cm Rear	8" / 20.3 cm Front 10" / 25.4 cm Rear
WASHOUT PORT	Standard	Standard
QUICK STOW STORAGE HANDLE	Standard	Standard
WEIGHT	140 lbs. / 63.5 kg	145 lbs. / 65.8 kg
TORO PERFORMANCE WARRANTY**	3-Year GTS / 3-Year Full	3-Year GTS / 3-Year Full

» = Enhanced or Step-up feature

**POWERFUL ENGINE**

Briggs & Stratton 10.00 ft-lb Gross Torque Professional Series™ 223cc OHV Engine.

**PERSONAL PACE® WITH TRACTION ASSIST**

Senses and smoothly adjusts to your preferred walking pace. For more challenging areas with uneven terrain, the Traction Assist Handle can help you monitor your speed, and keep you mowing at a comfortable pace.

**ELECTRIC START**

No need to pull the cord, just turn the key and you're ready to mow.
21200 only

**QUICK STOW STORAGE HANDLE**

Two storage positions for easy compact storage.

**SPIN-STOP™ BLADE STOP SYSTEM**

Stops the blade and allows you to briefly step away from the mower, without having to restart the engine.

**2 POINT HEIGHT-OF-CUT**

Allows you to quickly adjust cutting heights from one side of the mower.

**DUAL-FORCE™ CUTTING SYSTEM**

The Dual-Force cutting system and Toro Atomic blades cut grass into a fine mulch for a superior quality of cut and a healthy, lush lawn.



490-9919 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross torque of this engine was laboratory rated at 2600 RPM per SAE J1940 by the engine manufacturer. As configured to meet safety, emission and operating requirements, the actual engine torque on these mowers may be significantly lower. **See retailer for warranty details.