D)2 TRAILERS



4.5FT x 7.5FT SINGLE **AXLE MULTI-UTILITY GALVANIZED TRAILER**

ITEM NUMBER

MMT5X7G

UPC

826518003391

DESCRIPTION

This single axle multi-utility trailer from DK2 is one of the most versatile trailers on the market. Sitting on a solid square tube cambered axle with 12-inch, 6-ply bias tires and a load capacity of 1,639 pounds. When the front and back load-bearing gates are down, the trailer bed extends to nearly 12 feet in length, and the tilt/dump capability that makes it easy to load or unload heavy items. Fabricated from 100% steel, all of the components are reinforced, adjustable, removable and/or interchangeable.

SPECIFICATION

PAYLOAD CAPACITY	1,639lb (743.4kg)
GVWR	2,090lb (948kg)
WHEELS & TIRES	D.O.T. 5.30-12 6-ply radial tire with 5 x 4.5" (11.4cm) bolt pattern
MATERIAL	Fully welded heavy-duty UV powder coated tubular steel
SIDE PANELS	Corrugated reinforced steel
DROP GATES	24" (61cm) load-bearing corrugated reinforced steel
FLOORING	Corrugated reinforced steel panel
DUMP BED	2-position, axle-mounted with quick-release lock pin
LIGHTING	Pre-wired, quick-connect D.O.T LED
BED DIMENSIONS	88" (L) x 52" (W) 223.5cm (L) x 132.1cm (W)
FLOOR HEIGHT	20" (50.8cm)
HITCH HEIGHT	16" (40.6cm)
DIMENSIONS	177" (L) x 65" (W) x 36" (H) 449.6cm (L) x 165.1cm (W) x 91.4cm (H)
WEIGHT	451lb (204.6kg)
SHIPPING DIMENSIONS	88" (L) x 55" (W) x 9" (H) 223.5cm (L) x 139.7cm (W) x 22.9cm (H)
SHIPPING WEIGHT	460lb (208.7kg)
WARRANTY	1-year limited











FEATURES

- · Constructed with fully welded heavyduty hot-dipped galvanized tubular steel
- Corrugated reinforced steel floor panel 1
- · Corrugated reinforced steel side panels 2
- 24" (61cm) load-bearing corrugated steel drop gates, extending the length of the trailer to 11.3ft (3.4m)
- · Solid square tube cambered axle
- 2-position axle-mounted dump bed with quick release lock pin
- D.O.T. 5.30-12 radial tires with 5 x 4.5" (11.4cm) bolt pattern 5
- · Heavy-duty tail light protectors
- · Quick-connect D.O.T. LED lighting with side markers
- · Ships in a single package
- 2" (5.08cm) coupler on an A-frame tongue for added stability
- Includes all necessary paperwork for registration



