

Warrior Spartan 9,500 lb. Synthetic Rope – Part No. 9500

<p>Description</p>	<p>In the winching industry, you usually get what you pay for. The lower the price, the poorer the quality. Very rarely is a new product brought to the market that is the exception to this rule, giving you far more features & value than the price would imply.</p> <p>Warrior Winches are delighted to announce the arrival of the Spartan Series, Tough, Strong and ready for a Battle, these Winches really will challenge all before them. We have reluctantly termed them as ‘entry level’, however this describes the price point, not the performance. We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.</p> <p>Available in 8000lb, 9500lb, & 12000lb capacity there is a model for every leisure application. With great performance, outstanding features included as standard, & backed by the Warrior Winches un-rivalled limited Lifetime Warranty, this should make a Spartan the first choice for all serious enthusiasts.</p>																																																																		
<p>Features / Benefits</p>	<ul style="list-style-type: none"> • Weather Sealed High Performance Motor • Heavy Duty 3 Stage Gearbox • Heavy Duty Drum Supports • Weather Sealed Solenoids • Full Steel Planetary Gearing • Full Load Holding Brake • Every winch is 100% Load Tested • Chip Resistant Gloss Paint Finish 																																																																		
<p>Technical Specs</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">Rated Line Pull</td> <td colspan="2">9500 lbs (4309 kg)</td> </tr> <tr> <td>Motor</td> <td colspan="2">12v : 4.6hp / 3.5kw</td> </tr> <tr> <td>Gearing</td> <td colspan="2">230:1</td> </tr> <tr> <td>Braking Action</td> <td colspan="2">Auto in the drum</td> </tr> <tr> <td>Drum Size Dia x L</td> <td colspan="2">63 x 224mm</td> </tr> <tr> <td>Cable Dia x L</td> <td colspan="2">9.2mm x 25m</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">545 x 160 x 248mm</td> </tr> <tr> <td>Mounting Pattern</td> <td colspan="2">254 x 114.3mm</td> </tr> <tr> <td>Layer of Wire Rope</td> <td>Line Pull</td> <td></td> </tr> <tr> <td></td> <td>lbs (kgs)</td> <td></td> </tr> <tr> <td>1</td> <td>9500 (4309)</td> <td></td> </tr> <tr> <td>2</td> <td>7600 (3447)</td> <td></td> </tr> <tr> <td>3</td> <td>6200 (2812)</td> <td></td> </tr> <tr> <td>4</td> <td>5400 (2449)</td> <td></td> </tr> <tr> <td>Line Pull lbs (kgs)</td> <td>Line Speed</td> <td>Amp Draw 12v</td> </tr> <tr> <td></td> <td>ft/min (m/min)</td> <td></td> </tr> <tr> <td>0</td> <td>25 (7.8)</td> <td>65</td> </tr> <tr> <td>2000 (907)</td> <td>11.67 (3.6)</td> <td>179</td> </tr> <tr> <td>3000 (1361)</td> <td>10.05 (3.1)</td> <td>203</td> </tr> <tr> <td>6000 (2721)</td> <td>9.08 (2.8)</td> <td>286</td> </tr> <tr> <td>8000 (3629)</td> <td>7.13 (2.2)</td> <td>330</td> </tr> <tr> <td>9500 (4309)</td> <td>6.16 (1.9)</td> <td>365</td> </tr> </table>	Rated Line Pull	9500 lbs (4309 kg)		Motor	12v : 4.6hp / 3.5kw		Gearing	230:1		Braking Action	Auto in the drum		Drum Size Dia x L	63 x 224mm		Cable Dia x L	9.2mm x 25m		Dimensions	545 x 160 x 248mm		Mounting Pattern	254 x 114.3mm		Layer of Wire Rope	Line Pull			lbs (kgs)		1	9500 (4309)		2	7600 (3447)		3	6200 (2812)		4	5400 (2449)		Line Pull lbs (kgs)	Line Speed	Amp Draw 12v		ft/min (m/min)		0	25 (7.8)	65	2000 (907)	11.67 (3.6)	179	3000 (1361)	10.05 (3.1)	203	6000 (2721)	9.08 (2.8)	286	8000 (3629)	7.13 (2.2)	330	9500 (4309)	6.16 (1.9)	365
Rated Line Pull	9500 lbs (4309 kg)																																																																		
Motor	12v : 4.6hp / 3.5kw																																																																		
Gearing	230:1																																																																		
Braking Action	Auto in the drum																																																																		
Drum Size Dia x L	63 x 224mm																																																																		
Cable Dia x L	9.2mm x 25m																																																																		
Dimensions	545 x 160 x 248mm																																																																		
Mounting Pattern	254 x 114.3mm																																																																		
Layer of Wire Rope	Line Pull																																																																		
	lbs (kgs)																																																																		
1	9500 (4309)																																																																		
2	7600 (3447)																																																																		
3	6200 (2812)																																																																		
4	5400 (2449)																																																																		
Line Pull lbs (kgs)	Line Speed	Amp Draw 12v																																																																	
	ft/min (m/min)																																																																		
0	25 (7.8)	65																																																																	
2000 (907)	11.67 (3.6)	179																																																																	
3000 (1361)	10.05 (3.1)	203																																																																	
6000 (2721)	9.08 (2.8)	286																																																																	
8000 (3629)	7.13 (2.2)	330																																																																	
9500 (4309)	6.16 (1.9)	365																																																																	