

Warrior Spartan 12,000 lb. Synthetic Rope – Part No. 12000

<p>Description</p>	<p>In the winching industry, you usually get what you pay for. The lower the price, the poorer the quality. Very rarely is a new product brought to the market that is the exception to this rule, giving you far more features &amp; value than the price would imply.</p> <p>Warrior Winches are delighted to announce the arrival of the Spartan Series, Tough, Strong and ready for a Battle, these Winches really will challenge all before them. We have reluctantly termed them as ‘entry level’, however this describes the price point, not the performance. We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.</p> <p>Available in 8000lb, 9500lb, &amp; 12000lb capacity there is a model for every leisure application. With great performance, outstanding features included as standard, &amp; backed by the Warrior Winches un-rivalled limited Lifetime Warranty, this should make a Spartan the first choice for all serious enthusiasts.</p>																																												
<p>Features / Benefits</p>	<ul style="list-style-type: none"> <li>• Weather Sealed High Performance Motor</li> <li>• Heavy Duty 3 Stage Gearbox</li> <li>• Heavy Duty Drum Supports</li> <li>• Weather Sealed Solenoids</li> <li>• Full Steel Planetary Gearing</li> <li>• Full Load Holding Brake</li> <li>• Every winch is 100% Load Tested</li> <li>• Chip Resistant Gloss Paint Finish</li> </ul>																																												
<p>Technical Specs</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td><b>Rated Line Pull</b></td> <td>12000 lbs (5443 kg)</td> </tr> <tr> <td><b>Motor</b></td> <td>12v : 6.0hp / 4.6kw</td> </tr> <tr> <td><b>Gearing</b></td> <td>230:1</td> </tr> <tr> <td><b>Braking Action</b></td> <td>Auto in the drum</td> </tr> <tr> <td><b>Drum Size Dia x L</b></td> <td>63 x 224mm</td> </tr> <tr> <td><b>Cable Dia x L</b></td> <td>10.2mm x 25m</td> </tr> <tr> <td><b>Dimensions</b></td> <td>579 x 160 x 248mm</td> </tr> <tr> <td><b>Mounting Pattern</b></td> <td>254 x 114.3mm</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Layer of Wire Rope</th> <th>Line Pull lbs (kgs)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>12000 (5443)</td> </tr> <tr> <td>2</td> <td>9533 (4324)</td> </tr> <tr> <td>3</td> <td>7907 (3586)</td> </tr> <tr> <td>4</td> <td>6755 (3064)</td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Line Pull lbs (kgs)</th> <th>Line Speed ft/min (m/min)</th> <th>Amp Draw 12v</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>22 (6.6)</td> <td>65</td> </tr> <tr> <td>6000 (2721)</td> <td>11.15 (3.4)</td> <td>120</td> </tr> <tr> <td>8000 (3629)</td> <td>7.22 (2.2)</td> <td>230</td> </tr> <tr> <td>10000 (4536)</td> <td>4.92 (1.5)</td> <td>310</td> </tr> <tr> <td>12000 (5443)</td> <td>3.28 (1.0)</td> <td>380</td> </tr> </tbody> </table>	<b>Rated Line Pull</b>	12000 lbs (5443 kg)	<b>Motor</b>	12v : 6.0hp / 4.6kw	<b>Gearing</b>	230:1	<b>Braking Action</b>	Auto in the drum	<b>Drum Size Dia x L</b>	63 x 224mm	<b>Cable Dia x L</b>	10.2mm x 25m	<b>Dimensions</b>	579 x 160 x 248mm	<b>Mounting Pattern</b>	254 x 114.3mm	Layer of Wire Rope	Line Pull lbs (kgs)	1	12000 (5443)	2	9533 (4324)	3	7907 (3586)	4	6755 (3064)	Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Amp Draw 12v	0	22 (6.6)	65	6000 (2721)	11.15 (3.4)	120	8000 (3629)	7.22 (2.2)	230	10000 (4536)	4.92 (1.5)	310	12000 (5443)	3.28 (1.0)	380
<b>Rated Line Pull</b>	12000 lbs (5443 kg)																																												
<b>Motor</b>	12v : 6.0hp / 4.6kw																																												
<b>Gearing</b>	230:1																																												
<b>Braking Action</b>	Auto in the drum																																												
<b>Drum Size Dia x L</b>	63 x 224mm																																												
<b>Cable Dia x L</b>	10.2mm x 25m																																												
<b>Dimensions</b>	579 x 160 x 248mm																																												
<b>Mounting Pattern</b>	254 x 114.3mm																																												
Layer of Wire Rope	Line Pull lbs (kgs)																																												
1	12000 (5443)																																												
2	9533 (4324)																																												
3	7907 (3586)																																												
4	6755 (3064)																																												
Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Amp Draw 12v																																											
0	22 (6.6)	65																																											
6000 (2721)	11.15 (3.4)	120																																											
8000 (3629)	7.22 (2.2)	230																																											
10000 (4536)	4.92 (1.5)	310																																											
12000 (5443)	3.28 (1.0)	380																																											