

Warrior Samurai 12,000 lb. Steel Cable & Synthetic Rope – Part No. S12000 & S12000 SR

<p>Description</p>	<p>Superb high specification winch. Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing. Comes with stainless steel roller fairlead and fittings as standard. The 12V version comes complete with Heavy Duty integrated wireless remote.</p>																																																																								
<p>Features / Benefits</p>	<ul style="list-style-type: none"> • All Brass (no corrosion) Series Wound Motor • Double Sealed Motor • Sealed Waterproof Contactor • Steel Contactor Cover for Added Protection • Double Sealed Drum (Gearbox/Motor) • Sealed 3 Stage Planetary Gears • Stainless Steel 4 Way Fairleads • Integrated Wireless Remote (12V only) 																																																																								
<p>Technical Specs</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Rated Line Pull</td> <td colspan="3">12000 lbs (5400 kg)</td> </tr> <tr> <td>Motor</td> <td colspan="3">12v : 6.5hp / 4.6kw</td> </tr> <tr> <td>Gearing</td> <td colspan="3">230:1</td> </tr> <tr> <td>Braking Action</td> <td colspan="3">Auto in the drum</td> </tr> <tr> <td>Drum Size Dia x L</td> <td colspan="3">63 x 223mm</td> </tr> <tr> <td>Cable Dia x L</td> <td colspan="3">10.2mm x 26m</td> </tr> <tr> <td>Dimensions</td> <td colspan="3">580 x 160 x 219mm</td> </tr> <tr> <td>Mounting Pattern</td> <td colspan="3">254 x 114mm</td> </tr> <tr> <td>Layer of Wire Rope</td> <td>Line Pull lbs (kgs)</td> <td colspan="2"></td> </tr> <tr> <td>1</td> <td>12000 (5443)</td> <td colspan="2"></td> </tr> <tr> <td>2</td> <td>9563 (4338)</td> <td colspan="2"></td> </tr> <tr> <td>3</td> <td>7948 (3606)</td> <td colspan="2"></td> </tr> <tr> <td>4</td> <td>6800 (3085)</td> <td colspan="2"></td> </tr> <tr> <td>Line Pull lbs (kgs)</td> <td>Line Speed ft/min (m/min)</td> <td>Amp Draw 12v</td> <td>Amp Draw 24v</td> </tr> <tr> <td>0</td> <td>22.3 (6.8)</td> <td>100</td> <td>60</td> </tr> <tr> <td>4000 (1814)</td> <td>13.1 (4.0)</td> <td>220</td> <td>130</td> </tr> <tr> <td>8000 (3629)</td> <td>9.8 (3.0)</td> <td>330</td> <td>170</td> </tr> <tr> <td>12000 (5443)</td> <td>5.8 (1.8)</td> <td>450</td> <td>220</td> </tr> </table>	Rated Line Pull	12000 lbs (5400 kg)			Motor	12v : 6.5hp / 4.6kw			Gearing	230:1			Braking Action	Auto in the drum			Drum Size Dia x L	63 x 223mm			Cable Dia x L	10.2mm x 26m			Dimensions	580 x 160 x 219mm			Mounting Pattern	254 x 114mm			Layer of Wire Rope	Line Pull lbs (kgs)			1	12000 (5443)			2	9563 (4338)			3	7948 (3606)			4	6800 (3085)			Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Amp Draw 12v	Amp Draw 24v	0	22.3 (6.8)	100	60	4000 (1814)	13.1 (4.0)	220	130	8000 (3629)	9.8 (3.0)	330	170	12000 (5443)	5.8 (1.8)	450	220
Rated Line Pull	12000 lbs (5400 kg)																																																																								
Motor	12v : 6.5hp / 4.6kw																																																																								
Gearing	230:1																																																																								
Braking Action	Auto in the drum																																																																								
Drum Size Dia x L	63 x 223mm																																																																								
Cable Dia x L	10.2mm x 26m																																																																								
Dimensions	580 x 160 x 219mm																																																																								
Mounting Pattern	254 x 114mm																																																																								
Layer of Wire Rope	Line Pull lbs (kgs)																																																																								
1	12000 (5443)																																																																								
2	9563 (4338)																																																																								
3	7948 (3606)																																																																								
4	6800 (3085)																																																																								
Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Amp Draw 12v	Amp Draw 24v																																																																						
0	22.3 (6.8)	100	60																																																																						
4000 (1814)	13.1 (4.0)	220	130																																																																						
8000 (3629)	9.8 (3.0)	330	170																																																																						
12000 (5443)	5.8 (1.8)	450	220																																																																						