

Warrior Samurai 17,500 lb. Steel Cable – Part No. S17500

<p>Description</p>	<p>The best \$ for lb winch on the market. Outstanding features includes Huge 7.0 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing. Stainless steel roller fairleads and fittings as standard.</p>																																																																																										
<p>Features / Benefits</p>	<ul style="list-style-type: none"> • All Brass (no corrosion) Series Wound Motor • Double Sealed Motor • Sealed Waterproof Contactor • Steel Contactor Cover for Added Protection • Double Sealed Drum (Gearbox/Motor) • Sealed 3 Stage Planetary Gears • Stainless Steel 4 Way Fairleads 																																																																																										
<p>Technical Specs</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">Rated Line Pull</td> <td colspan="3">17500 lbs (7938 kg)</td> </tr> <tr> <td>Motor</td> <td colspan="3">12v : 7.0hp / 4.9kw</td> </tr> <tr> <td>Gearing</td> <td colspan="3">430:1</td> </tr> <tr> <td>Braking Action</td> <td colspan="3">Auto in the drum</td> </tr> <tr> <td>Drum Size Dia x L</td> <td colspan="3">89 x 219mm</td> </tr> <tr> <td>Cable Dia x L</td> <td colspan="3">12mm x 26m</td> </tr> <tr> <td>Dimensions</td> <td colspan="3">610 x 216 x 254mm</td> </tr> <tr> <td>Mounting Pattern</td> <td colspan="3">254 x 114mm</td> </tr> <tr> <td>Layer of Wire Rope</td> <td>Line Pull</td> <td colspan="2"></td> </tr> <tr> <td></td> <td>lbs (kgs)</td> <td colspan="2"></td> </tr> <tr> <td>1</td> <td>17500 (7938)</td> <td colspan="2"></td> </tr> <tr> <td>2</td> <td>14000 (6364)</td> <td colspan="2"></td> </tr> <tr> <td>3</td> <td>12500 (5682)</td> <td colspan="2"></td> </tr> <tr> <td>4</td> <td>10000 (4545)</td> <td colspan="2"></td> </tr> <tr> <td>5</td> <td>6000 (2728)</td> <td colspan="2"></td> </tr> <tr> <td>Line Pull lbs (kgs)</td> <td>Line Speed</td> <td>Amp Draw 12v</td> <td>Amp Draw 24v</td> </tr> <tr> <td></td> <td>ft/min (m/min)</td> <td></td> <td></td> </tr> <tr> <td>0</td> <td>22.3 (6.8)</td> <td>100</td> <td>60</td> </tr> <tr> <td>6000 (2728)</td> <td>9.84 (3.0)</td> <td>220</td> <td>130</td> </tr> <tr> <td>10000 (4545)</td> <td>9.8 (2.0)</td> <td>320</td> <td>170</td> </tr> <tr> <td>12500 (5682)</td> <td>5.8 (1.7)</td> <td>350</td> <td>220</td> </tr> <tr> <td>17500 (7938)</td> <td>3.9 (1.2)</td> <td>450</td> <td>290</td> </tr> </table>			Rated Line Pull	17500 lbs (7938 kg)			Motor	12v : 7.0hp / 4.9kw			Gearing	430:1			Braking Action	Auto in the drum			Drum Size Dia x L	89 x 219mm			Cable Dia x L	12mm x 26m			Dimensions	610 x 216 x 254mm			Mounting Pattern	254 x 114mm			Layer of Wire Rope	Line Pull				lbs (kgs)			1	17500 (7938)			2	14000 (6364)			3	12500 (5682)			4	10000 (4545)			5	6000 (2728)			Line Pull lbs (kgs)	Line Speed	Amp Draw 12v	Amp Draw 24v		ft/min (m/min)			0	22.3 (6.8)	100	60	6000 (2728)	9.84 (3.0)	220	130	10000 (4545)	9.8 (2.0)	320	170	12500 (5682)	5.8 (1.7)	350	220	17500 (7938)	3.9 (1.2)	450	290
Rated Line Pull	17500 lbs (7938 kg)																																																																																										
Motor	12v : 7.0hp / 4.9kw																																																																																										
Gearing	430:1																																																																																										
Braking Action	Auto in the drum																																																																																										
Drum Size Dia x L	89 x 219mm																																																																																										
Cable Dia x L	12mm x 26m																																																																																										
Dimensions	610 x 216 x 254mm																																																																																										
Mounting Pattern	254 x 114mm																																																																																										
Layer of Wire Rope	Line Pull																																																																																										
	lbs (kgs)																																																																																										
1	17500 (7938)																																																																																										
2	14000 (6364)																																																																																										
3	12500 (5682)																																																																																										
4	10000 (4545)																																																																																										
5	6000 (2728)																																																																																										
Line Pull lbs (kgs)	Line Speed	Amp Draw 12v	Amp Draw 24v																																																																																								
	ft/min (m/min)																																																																																										
0	22.3 (6.8)	100	60																																																																																								
6000 (2728)	9.84 (3.0)	220	130																																																																																								
10000 (4545)	9.8 (2.0)	320	170																																																																																								
12500 (5682)	5.8 (1.7)	350	220																																																																																								
17500 (7938)	3.9 (1.2)	450	290																																																																																								