

Warrior Samurai 20,000 lb. Steel Cable – Part No. S20000

<p>Description</p>	<p>Warrior Winches are excited to announce the arrival of the colossal Samurai 20000lb Winch. Designed for the toughest of applications & tested in the most extreme environments imaginable, this great piece of kit boasts a massive 7.5 hp Series wound motor, which is housed in full steel supports, ensuring this immense Warrior is ready for any battle.</p> <p>Available in 12v or 24v this Beast comes packed with all the features you would expect from the Samurai Range, the motor and gearbox are fully double sealed, the high spec motor boasts brass internals, all the external fittings including the roller fairleads are stainless steel & the smooth planetary gearing is full steel. All this is backed up by the unrivalled Warrior Lifetime Warranty.</p>																																																																																																						
<p>Features / Benefits</p>	<ul style="list-style-type: none"> • All Brass (no corrosion) Series Wound Motor • Double Sealed Motor • Sealed Waterproof Contactor • Steel Contactor Cover for Added Protection • Double Sealed Drum (Gearbox/Motor) • Sealed 3 Stage Planetary Gears • Stainless Steel 4 Way Fairleads 																																																																																																						
<p>Technical Specs</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Rated Line Pull</td> <td colspan="4">20000 lbs (9072 kg)</td> </tr> <tr> <td rowspan="2">Motor</td> <td>12v :</td> <td colspan="3">7.5hp / 5.4kw</td> </tr> <tr> <td>24v :</td> <td colspan="3">7.9hp / 6.0kw</td> </tr> <tr> <td>Gearing</td> <td colspan="4">430:1</td> </tr> <tr> <td>Drum Size Dia x L</td> <td colspan="4">89 x 219mm</td> </tr> <tr> <td>Cable Dia x L</td> <td colspan="4">12mm x 26.5m</td> </tr> <tr> <td>Dimensions</td> <td colspan="4">610 x 216 x 254mm</td> </tr> <tr> <td>Weight</td> <td colspan="4">67 kg</td> </tr> <tr> <td>Mounting Pattern</td> <td colspan="4">254 x 114mm</td> </tr> <tr> <td rowspan="5">Layer of Wire Rope</td> <td>Line Pull lbs (kgs)</td> <td colspan="3"></td> </tr> <tr> <td>1</td> <td colspan="3">20000 (9072)</td> </tr> <tr> <td>2</td> <td colspan="3">16160 (7330)</td> </tr> <tr> <td>3</td> <td colspan="3">13557 (6149)</td> </tr> <tr> <td>4</td> <td colspan="3">11677 (5297)</td> </tr> <tr> <td rowspan="8">Line Pull lbs (kgs)</td> <td>Line Speed ft/min (m/min)</td> <td>Line Speed 24v ft/min (m/min)</td> <td>Amp Draw 12v</td> <td>Amp Draw 24v</td> </tr> <tr> <td>0</td> <td>19.7 (6.0)</td> <td>13.8 (4.4)</td> <td>100</td> </tr> <tr> <td>6000 (2728)</td> <td>7.2 (2.2)</td> <td>6.9 (2.1)</td> <td>220</td> </tr> <tr> <td>10000 (4545)</td> <td>5.6 (1.7)</td> <td>5.9 (1.8)</td> <td>320</td> </tr> <tr> <td>12500 (5682)</td> <td>4.9 (1.5)</td> <td>5.2 (1.6)</td> <td>350</td> </tr> <tr> <td>14000 (6350)</td> <td>4.6 (1.4)</td> <td>4.6 (1.4)</td> <td>380</td> </tr> <tr> <td>17500 (7938)</td> <td>3.0 (0.9)</td> <td>3.9 (1.2)</td> <td>450</td> </tr> <tr> <td>20000 (9072)</td> <td>3.6 (0.9)</td> <td>3.3 (1.0)</td> <td>480</td> </tr> </table>					Rated Line Pull	20000 lbs (9072 kg)				Motor	12v :	7.5hp / 5.4kw			24v :	7.9hp / 6.0kw			Gearing	430:1				Drum Size Dia x L	89 x 219mm				Cable Dia x L	12mm x 26.5m				Dimensions	610 x 216 x 254mm				Weight	67 kg				Mounting Pattern	254 x 114mm				Layer of Wire Rope	Line Pull lbs (kgs)				1	20000 (9072)			2	16160 (7330)			3	13557 (6149)			4	11677 (5297)			Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Line Speed 24v ft/min (m/min)	Amp Draw 12v	Amp Draw 24v	0	19.7 (6.0)	13.8 (4.4)	100	6000 (2728)	7.2 (2.2)	6.9 (2.1)	220	10000 (4545)	5.6 (1.7)	5.9 (1.8)	320	12500 (5682)	4.9 (1.5)	5.2 (1.6)	350	14000 (6350)	4.6 (1.4)	4.6 (1.4)	380	17500 (7938)	3.0 (0.9)	3.9 (1.2)	450	20000 (9072)	3.6 (0.9)	3.3 (1.0)	480
Rated Line Pull	20000 lbs (9072 kg)																																																																																																						
Motor	12v :	7.5hp / 5.4kw																																																																																																					
	24v :	7.9hp / 6.0kw																																																																																																					
Gearing	430:1																																																																																																						
Drum Size Dia x L	89 x 219mm																																																																																																						
Cable Dia x L	12mm x 26.5m																																																																																																						
Dimensions	610 x 216 x 254mm																																																																																																						
Weight	67 kg																																																																																																						
Mounting Pattern	254 x 114mm																																																																																																						
Layer of Wire Rope	Line Pull lbs (kgs)																																																																																																						
	1	20000 (9072)																																																																																																					
	2	16160 (7330)																																																																																																					
	3	13557 (6149)																																																																																																					
	4	11677 (5297)																																																																																																					
Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Line Speed 24v ft/min (m/min)	Amp Draw 12v	Amp Draw 24v																																																																																																			
	0	19.7 (6.0)	13.8 (4.4)	100																																																																																																			
	6000 (2728)	7.2 (2.2)	6.9 (2.1)	220																																																																																																			
	10000 (4545)	5.6 (1.7)	5.9 (1.8)	320																																																																																																			
	12500 (5682)	4.9 (1.5)	5.2 (1.6)	350																																																																																																			
	14000 (6350)	4.6 (1.4)	4.6 (1.4)	380																																																																																																			
	17500 (7938)	3.0 (0.9)	3.9 (1.2)	450																																																																																																			
	20000 (9072)	3.6 (0.9)	3.3 (1.0)	480																																																																																																			