



E350

FEATURES / SPECS

PUMP: 100% CAST IRON CONSTRUCTION



FEATURES

- PATENTED PRESSURE LUBRICATED PUMP**
 Rated 70,000 Hr. Life Expectancy.
- PREMIUM INDUSTRIAL MOTORS**
 Low 1750 RPM's.
- POWDER COATED ASME CERTIFIED TANKS**
 200 PSI rating
- MANUAL BALL VALVE TANK DRAIN**
 Easy access to drain tank moisture.
- QUALITY COMPONENTS**
 We use B-style belts to ensure smooth operation. Top quality pressure switches, 100% brass valves, ASME certified tank, powder coated 13G Steel with premium grade expanded metal belt guards.
- ETL CERTIFIED**
 Tested to all safety standards and certified.
- EXTENDED WARRANTY PLANS**



TECH SPECS

	EI05V08011	EI07V080V1	EI10V080V1
RUNNING HP	5	7.5	10
CFM 100PSI	19	31	38
MAX PSI	175	175	175
PUMP RPM	800	640	800
MOTOR RPM	1750	1750	1750
MOTOR PHASE OPTIONS	single	single	single
PRODUCT DIMS	31 x 33 x 75	27 x 42 x 72	27 x 42 x 72
PRODUCT WEIGHT	576	735	795
TANK GALLONS	80	80	80
TANK ORIENTATION	vertical	vertical	vertical

