



- Low RPM 1750, low AMP draw motors with solid copper windings for longer life
- Silent air low RPM, 2 cylinder commercial grade pumps plus heavy gauge steel cylinders, cylinder heads and valves
- Commercial Grade engineered components; pressure switch, stainless steel transfer tubes, brass quick couplers, gate valve tank drains combined with heavy steel construction for maximum durability and reliability!

Hulk Power by EMAX Silent Portable Air Compressors!



2 YEAR WARRANTY



2 YEAR WARRANTY



2 YEAR WARRANTY



2 YEAR WARRANTY

36 dBA SILENT AIR 90% QUIETER	OIL FREE	2.5 CFM @90 PSI
--	----------	---------------------------

41 dBA SILENT AIR 80% QUIETER	OIL FREE	2.7 CFM @90 PSI
--	----------	---------------------------

37 dBA SILENT AIR 80% QUIETER	OIL FREE	3.2 CFM @90 PSI
--	----------	---------------------------

45 dBA SILENT AIR 80% QUIETER	OIL FREE	3.1 CFM @90 PSI
--	----------	---------------------------

HP01P002SS	
Motor HP	1
Description	Oil Free Silent Side Stack
CFM @ 90 PSI	2.54
CFM @ 40 PSI	3.72
Max PSI	120
Tank Size	2 Gal
Noise DBA	36 DB @ 3FT

HP15P004SS	
Motor HP	1
Description	Oil Free Silent Twin Stack
CFM @ 90 PSI	2.69
CFM @ 40 PSI	3.92
Max PSI	120
Tank Size	4 Gal
Noise DBA	41 DB @ 3FT

HP15P005SS	
Motor HP	1.5
Description	Oil Free Silent Side Stack-w/ Dual Regulators
CFM @ 90 PSI	3.24
CFM @ 40 PSI	5.29
Max PSI	120
Tank Size	5 Gal
Noise DBA	37 DB @ 3FT

HP01P006SS	
Motor HP	1
Description	Oil Free Silent Side Stack w/Wheels
CFM @ 90 PSI	3.14
CFM @ 40 PSI	4.87
Max PSI	120
Tank Size	6 Gal
Noise DBA	45 DB @ 3FT

HULK POWER™

Hulk Power by EMAX Silent Portable Air Compressors!



 **41** dBA
SILENT AIR
 80% QUIETER

 **OIL FREE**

5.8
CFM
 @90 PSI

2 YEAR WARRANTY



 **41** dBA
SILENT AIR
 80% QUIETER

 **OIL FREE**

5.8
CFM
 @90 PSI

2 YEAR WARRANTY

	HP02P010SS
Motor HP	2
Description	Oil Free Silent Vertical
CFM @ 90 PSI	5.77
CFM @ 40 PSI	8.37
Max PSI	125
Tank Size	10 Gal
Noise DBA	41 DB @ 3FT

	HP01P002SS
Motor HP	2
Description	Oil Free Silent Vertical
CFM @ 90 PSI	5.77
CFM @ 40 PSI	8.37
Max PSI	125
Tank Size	20 Gal
Noise DBA	41 DB @ 3FT

- Low RPM 1750, low AMP draw motors with solid copper windings for longer life
- Silent air low RPM, 2 cylinder commercial grade pumps plus heavy gauge steel cylinders, cylinder heads and valves
- Commercial Grade engineered components; pressure switch, stainless steel transfer tubes, brass quick couplers, gate valve tank drains combined with heavy steel construction for maximum durability and reliability!
- ASME certified tanks on 20 Gallon
- Two quick disconnect couplers
- Drain Valve
- Non-flat tires

www.hulkcompressors.com