



**HULK**  
POWER<sup>™</sup>  
By EMAX



## Hulk 5HP & 7.5HP 3 Cylinder Industrial Air Compressor with 80 Gallon Tank

HULK air compressors deliver overwhelming performance to ensure that they meet the needs of even the most demanding environments. All products are designed with exacting tolerance and specifications to deliver all the power that's needed at the job site, garage or shop, for extreme performance.

HULK commercial air compressors are designed to deliver high air power output with lower operating noise. These commercial-grade pumps are designed with heavy gauge steel cylinders, cylinder head and valves for maximum durability and reliability.

- Tank Drain Extended Valve
- Magnetic Starter
- 1750 Low RPM Industrial ODP Electric Motor
- 80 Gallon ASME Certified Tank
- Solid Cast Iron, 2-Stage, 3 Cylinder, low RPM pump with Industrial Disc Valves
- Oil Drain Valve
- 2-V Style Belts—B Groove
- 13 Gauge Steel Belt Guard
- 4 Year Full Warranty

Ask about our extended **5 year warranty**



|                | HI05V080Y1  | HI07V080Y1  |
|----------------|-------------|-------------|
| Running HP     | 5           | 7.5         |
| CFM @ 100 PSI  | 18          | 26          |
| Max PSI        | 175         | 175         |
| Pump Model     | APP3Y0722T  | APP3Y0722T  |
| Pump RPM       | 680         | 800         |
| Motor RPM      | 1750        | 1750        |
| DBA Avg Rating | 57          | 67          |
| Outlet Size    | 3/4"        | 3/4"        |
| Motor Phase    | Single 230V | Single 230V |





## Hulk 5HP & 7.5HP 3 Cylinder Industrial Air Compressor with 80 Gallon Tank

HULK air compressors deliver overwhelming performance to ensure that they meet the needs of even the most demanding environments. All products are designed with exacting tolerance and specifications to deliver all the power that's needed at the job site, garage or shop, for extreme performance.

HULK silent air compressors are designed to deliver high air power output with little noise. These commercial-grade pumps are designed with heavy gauge steel cylinders, cylinder head and valves for maximum durability and reliability.

- Whisper 100 Silent Air Noise Suppression System with 5-Stage Intake Filtration
- Tank Drain Extended Valve
- Magnetic Starter
- 1750 Low RPM Industrial ODP Electric Motor
- 80 Gallon ASME Certified Tank
- Solid Cast Iron, 2-Stage, 3 Cylinder, low RPM pump with Industrial Disc Valves
- Oil Drain Valve
- 2-V Style Belts—B Groove
- 13 Gauge Steel Belt Guard
- 4 Year Full Warranty

Ask about our extended **5 year warranty**



|                | HI05V080Y 1S | HI07V080Y 1S |
|----------------|--------------|--------------|
| Running HP     | 5            | 7.5          |
| CFM @ 100 PSI  | 18           | 26           |
| Max PSI        | 175          | 175          |
| Pump Model     | APP3Y0722T   | APP3Y0722T   |
| Pump RPM       | 680          | 800          |
| Motor RPM      | 1750         | 1750         |
| DBA Avg Rating | 57           | 67           |
| Outlet Size    | 3/4"         | 3/4"         |
| Motor Phase    | Single 230V  | Single 230V  |

**Model HP01P002SS**

**1HP 2 Gallon**  
Oil-Free, Silent

**Model HP15P004SS**

**1HP 4 Gallon**  
Oil-Free, Silent, Twin Stack

**Model HP01P005SS**

**1HP 5 Gallon**  
Oil-Free, Silent

**Model HP15P005SS**

**1.5HP 5 Gallon**  
Oil-Free, Silent

**Model HP01P006SS**

**1HP 6 Gallon**  
Oil-Free, Silent, Portable

**Model HP02P010SS**

**2HP 10 Gallon**  
Oil-Free, Silent, Portable

**Model HP02P020SS**

**2HP 20 Gallon**  
Oil-Free, Silent, Portable

| Model      | CFM 40 PSI | CFM 90 PSI | Max PSI | Sound DBA  |
|------------|------------|------------|---------|------------|
| HP01P002SS | 3.72       | 2.54       | 120     | 36 DB@3 Ft |
| HP15P004SS | 3.92       | 2.69       | 120     | 41 DB@3 Ft |
| HP01P005SS | 3.91       | 2.59       | 125     | 37 DB@3 Ft |
| HP15P005SS | 5.29       | 3.24       | 125     | 37 DB@3 Ft |
| HP01P006SS | 4.87       | 3.14       | 120     | 45 DB@3 Ft |
| HP02P010SS | 8.39       | 5.77       | 125     | 41 DB@3 Ft |
| HP02P020SS | 8.39       | 5.77       | 125     | 41 DB@3 Ft |

- Low RPM, low AMP draw motors with solid copper windings for longer life
- Silent Air low RPM, 2 cylinder commercial grade pumps plus heavy gauge steel cylinders, cylinder heads and valves.
- Commercial Grade Engineered components - pressure switches, stainless steel transfer tubes, brass quick couplers, gate valve tank drains, combined with heavy gauge steel construction for maximum durability & reliability.



## Our Customers Say It Best



*I absolutely love it. I wanted something to run my air tools and this unit performs. I did a ton of research before choosing this and I couldn't find anything that puts out equal cfm anywhere close to this price point. The fact that it's SUPER quiet is just the cherry on top.*



## About HULK by EMAX

HULK Air Compressors & Air Tools deliver overwhelming performance to ensure that they meet the needs of even the most demanding environments. All products are designed with exacting tolerance and specifications to deliver all the power that's needed at the job site, garage or shop, for extreme performance.

HULK silent air compressors are designed to deliver high air power output with little noise. These commercial-grade pumps are designed with heavy gauge steel cylinders, cylinder head and valves for maximum durability and reliability.

Available from online retailers, nationwide.

### **EMAX Compressor**

1000 Cass Drive  
Clayton, OH 45315



866-294-4153



[sales@hulkcompressors.com](mailto:sales@hulkcompressors.com)



[www.hulkcompressors.com](http://www.hulkcompressors.com)