

# JX

## Comparison Chart



FEATURE	JX 5K CENTER	JX 2K CENTER	JX 5K SIDE	JX 2K SIDE
<b>Weight Capacity</b>	5,000 lb weight capacity	2,000 lb weight capacity	5,000 lb weight capacity	2,000 lb weight capacity
<b>Mount Type</b>	Mounts through center of A-frame coupler	Mounts through center of A-frame coupler	Mounts to side of trailer frame	Mounts to side of trailer frame
<b>Bracket Type</b>	N/A	N/A	Pipe mount bracket system with stow pin	Pull-pin swivel mount for easy stow
<b>Finish</b>	Signature Wrinkle-Black Powder Coating	Signature Wrinkle-Black Powder Coating	Signature Wrinkle-Black Powder Coating	Signature Wrinkle-Black Powder Coating
<b>Gear System Ratio</b>	3:4	1:1	3:4	3:4
<b>Smooth-Glide Protective Sleeve</b>	N/A	N/A	✓	✓

SPECIFICATIONS	JX 5K CENTER	JX 2K CENTER	JX 5K SIDE	JX 2K SIDE
<b>Plating</b>	Zinc nickel plating	Zinc nickel plating	Zinc nickel plating	Zinc nickel plating
<b>Misc</b>	Includes installation bolts	Includes installation bolts	Needs 8" of clearance to install	Needs 6" of clearance to install
<b>Retracted Height</b>	23 in	23 in	23 in	23 in
<b>Extended Height</b>	37 in	37 in	37 in	37 in
<b>Total Extension</b>	14 in	14 in	14 in	14 in
<b>Trailer Lift</b>	9.5 in to 23.5 in	9.5 in to 23.5 in	11.5 in to 25.5 in	7.5 in to 21.5 in
<b>Outer/Inner Tube Diameter</b>	57 mm / 51 mm	57 mm / 51 mm	57 mm / 51 mm	57 mm / 51 mm
<b>Clearance (bottom of bracket to top)</b>	N/A	N/A	14 in	14 in
<b>Clearance (mount point to top of Jack)</b>	13.5 in	13.5 in	11.5 in	11.5 in
<b>Max Frame Size Fit</b>	N/A	N/A	4.75 in high, 3.75 in deep	4.75 in high, 3.75 in deep