



WARNING: THE ATTACHMENT OF THIS PRODUCT IS CRITICAL AND BEYOND THE CONTROL OF HORIZON GLOBAL. HORIZON GLOBAL IS NOT RESPONSIBLE FOR ITS ATTACHMENT OR ITS INSTALLATION. IT NEITHER GUARANTEES, NOR WILL IT BE LIABLE FOR ANY DAMAGE RESULTING FROM ITS ATTACHMENT, INSTALLATION OR IMPROPER USE. THE LIABILITY OF THIS PRODUCT IS LIMITED TO ITS PURCHASE PRICE IF IT PROVES TO BE DEFECTIVE IN MATERIAL AND/OR WORKMANSHIP. WARRANTY INFORMATION AVAILABLE UPON REQUEST. WARRANTY VOID IF HARDWARE IS DAMAGED OR WORN.



WARNINGS FOR HITCH BALL USE:

- 1.** MOUNTING HOLE MUST NOT EXCEED SHANK DIAMETER BY MORE THAN .060 INCH (1/16 INCH).
- 2.** ALWAYS INCLUDE LOCKWASHER TO INSTALL HITCH BALL.
- 3.** TORQUE NUT TO: 160 FT•LB FOR 3/4" SHANK, 250 FT•LB FOR 1" SHANK & 450 FT•LB FOR 1-1/4" SHANK. IMPROPER TIGHTENING MAY CAUSE BALL TO LOOSEN OR FAIL.
- 4.** BALL SHANK MUST EXTEND AT LEAST ONE THREAD BEYOND NUT.
- 5.** USE ONLY WITH COUPLERS MARKED WITH THE SAME HITCH BALL SIZE.
- 6.** DO NOT EXCEED THE LOWER LOAD RATING OF BALL OR HITCH.
- 7.** DO NOT FASTEN SAFETY CHAIN TO HITCH BALL. DO NOT ATTACH TOW CHAIN, CABLE, ROPE, ELASTIC STRAP, NOR ELASTIC ROPE TO HITCH BALL.
- 8.** CHECK HITCH BALL TIGHTNESS BEFORE EACH USE.
- 9.** PLACE A SMALL AMOUNT OF HEAVY OIL OR GREASE ON BALL BEFORE EACH USE. DO NOT ALLOW OIL OR GREASE TO ACCUMULATE UNDER FLANGE OR ON NUT AND THREADS. THIS PRODUCT COMPLIES WITH SAFETY SPECIFICATIONS AND REQUIREMENTS FOR THE STATE OF NEW YORK, VESC REGULATION V-5, AND CSA STANDARD D-264 FOR CONNECTING DEVICES AND TOWING ITEMS. FAILURE TO FOLLOW WARNINGS EXACTLY CAN CAUSE BALL FAILURE OR LOSS OF ATTACHMENT RESULTING IN VEHICLE CRASH AND/OR SERIOUS PERSONAL INJURY.