



2018 WINCH CATALOGUE

DK2 CANADA
1080 Clay Avenue,
Unit 2, Burlington, Ontario,
L7L 0A1, Canada

DK2 USA
6245 Industrial Parkway
Whitehouse, Ohio,
43571, United States

TEL: 1-888-277-6960 WWW.DETAILK2.COM

D_K WARRIOR WINCHES



Detail K2 Warrior Winches are the #1 selling brand of winches in Europe and are now proudly available in North America. In partnership with our distributors we supply the North American market with a complete range of electric, worm drive, and hydraulic winches.

DK2 WARRIOR WINCHES

Features



In the most extreme conditions, when lesser products might be found wanting, DK2 Warrior Winches will deliver what your customer demands and our service levels will raise the bar in the process.

Whatever the requirement and whatever the vehicle we can supply a DK2 Warrior Winch that will provide exceptional performance and be backed by only the highest level of customer service and after sales support thus our motto" Value Without Compromise".

Value for money specification



At Detail K2 Inc. we recognize that our customers want an all-inclusive price and do not want the bother of searching through a long, expensive extras list. It's for this reason that each one of our Winches is supplied as standard, with a specification that translates into exceptional value for your hard earned money.

Highest quality motors are the powerhouse, 3 stage Planetary Gears provide the right ratios for any task. Our water resistant solenoids and fully sealed housings deliver reliability in the field regardless of what Mother Nature throws your way.

Limited Lifetime Warranty



It shouldn't come as a surprise that every DK2 Warrior Winch is backed by a no quibble Limited Lifetime Warranty. We are so confident in our product that in the unlikely event something should go wrong there will be a simple and direct commitment to rectifying the problem. It's this integrity that translates into knowing our service and reputation will deliver when called on.

A 1 year warranty is offered for commercial and industrial applications. For more warranty information please visit our website at www.detailk2.com

NINJA SERIES ATV WINCHES

Item Numbers:
C2500N, C2500N-SR
C3500N, C3500N-SR

FEATURES

- Sealed High Power Motor
- Heavy Duty Watertight Contactors
- Full Steel Planetary Gearing
- Strengthened Steel Drum (suitable for Synthetic rope)
- Watertight Controller Socket
- Gloss Chip Resistant Paint

INCLUDED

- Steel Cable
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- 3 Tonne Pulley Block
- Mounting plate & Hardware
- 1/4 hook



DESCRIPTION

Ideal for large ATV's and small trailers. A huge high power motor, heavy duty clutch, heavy duty steel gearing and heavy duty waterproof contactors ensure the ultimate in performance and reliability. Strengthened Steel drum makes it ideal to use with Synthetic Rope.

Watertight 4 Pin connection allows the use of 'Plug and Play' Wireless.



**Synthetic version
available**

SPECIFICATION

C2500N

RATED LINE PULL: 2500lbs(1134kg)
MOTOR: 12v : 1.35hp / 0.95kw
GEARING: 170:1
BRAKING ACTION: Dynamic
DRUM SIZE Dia x L: 1.5 x 3.1"
CABLE Dia x L: 0.2" x 46 ft
MOUNT PATTERN: 3.1"
DIMENSIONS: 13.2 x 4.4 x 6.5"

C3500N

RATED LINE PULL: 3500lbs (1588kg)
MOTOR: 12v : 1.95hp / 1.37kw
GEARING: 170:1
BRAKING ACTION: Dynamic
DRUM SIZE Dia x L: 1.5 x 3.1"
CABLE Dia x L: 0.2" x 42 ft
MOUNT PATTERN: 3.1"
DIMENSIONS: 13.7 x 4.6 x 6.5"



NINJA SERIES TRAILER WINCHES

Item Numbers:
C4500N
C4500N-SR

DESCRIPTION

High quality three stage planetary gearing ensure this is one of the quietest and smoothest winches on the market.

The silky smooth performance and the full load holding brake make it the perfect solution for high spec applications.



Synthetic version available

FEATURES

- Power in and Power out
- High Torque 1.95hp Motor
- HD Waterproof Contactors
- Full Steel Planetary Gearing
- Mount Plate as Standard
- Full Load Holding Break
- Can fit tow ball mount

SPECIFICATION

RATED LINE PULL: 4500lbs (2041kg)
MOTOR: 12v : 1.95hp / 1.37kw
GEARING: 172:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 1.7 x 3.8"
CABLE Dia x L: 0.25" x 47.5ft
MOUNT PATTERN: 5 x 3.7"
DIMENSIONS: 14.4 x 4.9 x 6.4"
WEIGHT: 28.6 lbs



INCLUDED

- 0.25" x 47.5ft Steel Cable
- 3m Remote Handset
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- Mounting plate
- Mounting hardware
- 3/8 hook
- *ATV remote available

Layer of wire rope	Line pull lbs (kg)
1	4500 (2401)
2	3642 (1652)
3	3060 (1388)
4	2638 (1196)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	11.6	3.6	20	15
1500 (680)	9.2	2.8	70	40
2500 (1134)	7.8	2.4	100	65
3500 (1587)	6.6	2.0	140	80
4500 (2041)	4.9	1.5	200	130

SPARTAN 6000 ELECTRIC WINCH

Item Numbers:
6000
6000-SR



DESCRIPTION

Warrior Winches are delighted to announce the arrival of the new member of Spartan Series, Tough, Strong and ready for Battle. The Spartan 6000 Lb short drum model is ideal where space and payload are limited. The winch has a short drum and is less than 66Lbs, however the extended drum supports allow it to carrier up to 131ft of 0.28" cable. The Synthetic rope version comes fitted with 0.27" x 98ft.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

With great performance, outstanding features included as standard, & backed by the Warrior Winches un-rivalled limited Lifetime Warranty, this should make a Spartan the first choice for all serious enthusiasts.

SPECIFICATION

RATED LINE PULL: 6000 lbs (2727kg)
MOTOR: 12V: 4.5hp / 3.4kW
GEARING: 230:1
DRUM SIZE Dia x L: 2.48 x 4.2"
CABLE Dia x L: 0.28" x 131'
DIMENSIONS: 17.4 x 7.7 x 10.8"
WEIGHT: 66 lbs



FEATURES

- Weather Sealed High Performance Motor
- Heavy Duty 3 Stage Gearbox
- Heavy Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch is 100% Load Tested
- Chip Resistant Gloss Paint Finish

INCLUDED

- 10ft Remote Handset
- 5/16 Hook
- Aluminium or Roller Fairlead (Synthetic rope or steel cable)
- Heavy Duty Battery Leads
- Stainless Steel Mounting Hardware
- 0.27" x 98ft Synthetic Rope or 0.28" x 131ft Steel Cable

Layer of wire rope	Line Pull lbs (kg)	Cable Cap ft (m)
1	6000 (2727)	9.8 (3.0)
2	4979 (2258)	22.0 (6.7)
3	4255 (1930)	36.1 (11.0)
4	3714 (1685)	52.2 (15.9)
5	3296 (1495)	70.5 (21.5)
6	2962 (1344)	90.9 (27.7)
7	2690 (1220)	113.2 (34.5)
8	2463 (1117)	131.2 (40.0)

Line pull lbs (kg)	Line speed		Amps 12v
	ft/min	m/min	
0	19.4	5.9	80
2000 (907)	13.1	1.0	140
4000 (1814)	9.2	2.8	210
6000 (2727)	7.2	2.2	285



SPARTAN SERIES ELECTRIC WINCH

Item Numbers:
8000, 8000-SR
9500, 9500-SR
12000, 12000-SR

DESCRIPTION

We are delighted to announce the arrival of the Spartan Series, Tough, Strong and ready for a Battle, these Winches really will challenge all before them. We have reluctantly termed them as 'entry level', however this describes the price point, not the performance.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

SPECIFICATION

8000

RATED LINE PULL: 8000lbs(3629kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 233:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.3" x 85 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 21.3 x 6.3 x 8.6"

9500

RATED LINE PULL: 9500lbs(4500kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.36" x 82 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 21.3 x 6.3 x 8.6"

12000

RATED LINE PULL: 12000lbs (5400kg)
MOTOR: 12v : 6.0hp / 4.6kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.4" x 82 ft
MOUNT PATTERN: 10 x 4.5" 22.8 x 6.3 x 8.6"



FEATURES

- Weather Sealed High Performance motor
- Heavy-Duty 3 Stage Gearbox
- Heavy-Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch 100 % load tested
- Chip Resistant Gloss Paint Finish

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Steel Roller Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- Clevis hook

SAMURAI SERIES ELECTRIC WINCH

Item Numbers:
S8000, S8000-SR
S9500, S9500-SR,
S12000, S12000-SR



DESCRIPTION

Superb high specification winch. Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing.

Comes with stainless steel roller fairlead and fittings as standard. Complete with Heavy Duty integrated wireless remote. Available with Armortek Synthetic Rope and Aluminum Fairlead.



Synthetic version available

SPECIFICATION

	S8000	S9500
RATED LINE PULL:	8000lbs(3629kg)	9500lbs(4500kg)
MOTOR: 12v :	4.6hp / 3.2kw	4.6hp / 3.2kw
GEARING:	210:1	230:1
BRAKING ACTION:	Auto in the drum	Auto in the drum
DRUM SIZE Dia x L:	2.5 x 8.8"	2.5 x 8.8"
CABLE Dia x L:	0.3" x 95 ft	0.4" x 85 ft
MOUN PATTERN:	10 x 4.5"	10 x 4.5"
DIMENSIONS:	21.3 x 6.3 x 8.6"	21.3 x 6.3 x 8.6"

S12000

RATED LINE PULL:	12000lbs(5400kg)
MOTOR: 12v :	6.5hp / 4.6kw
GEARING:	230:1
BRAKING ACTION:	Auto in the drum
DRUM SIZE Dia x L:	2.5 x 8.8"
CABLE Dia x L:	0.4" x 85 ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	22.8 x 6.3 x 8.6"

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook

SAMURAI 9,500 LB HIGH SPEED PERFORMANCE WINCH

Item Numbers:
S9500HS
S9500HS-SR



DESCRIPTION

The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing.

Complete with heavy duty integrated wireless remote. Available with Steel Rope or Armortek Synthetic Rope and Aluminum Fairlead.



**Steel Cable
version available**

SPECIFICATION

RATED LINE PULL: 9500lbs(4500kg)
MOTOR: 12v : 6.5hp / 4.5kw
GEARING: 110:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.4" x 98 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 22.7 x 6.3 x 8.5"

Layer of wire rope	Line pull lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5400 (2400)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	65	19.8	80	45
4000 (1818)	12.5	3.8	300	175
6000 (2722)	11.81	3.6	400	230
9500 (4309)	8.86	1.9	530	335

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Integrated Wireless Remote

INCLUDED

- Wire rope 0.4" x 98ft
- 10ft Remote Handset
- Roller Fairlead (does not attach to winch)
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



SAMURAI 9,500 LB SHORT DRUM WINCH

Item Numbers:
S9500SD
S9500SD-SR

DESCRIPTION

The narrow drum version of the best selling 9500. A total width of 17.2 inches ensures this is the perfect product for limited space. The 5.0hp motor delivers 9500lb of pulling power in space normally designed for Winches with half the power.

The Short Drum winch is the preferred choice of the British Military on specialist vehicles currently serving in action. Available with synthetic rope and aluminium fairlead, to give a total weight of 44 lbs.



Steel Cable version available

SPECIFICATION

- RATED LINE PULL:** 9500lbs(4500kg)
- MOTOR: 12v :** 5.0hp / 3.5kw
- GEARING:** 230:1
- BRAKING ACTION:** Auto in the drum
- DRUM SIZE Dia x L:** 2.5 x 4.7"
- CABLE Dia x L:** 0.4" x 46 ft
- MOUNT PATTERN:** 5.9 x 4.5"
- DIMENSIONS:** 17.2 x 6.3 x 10.7"

Layer of wire rope	Line pull lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5593 (2537)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	23	7	80	70
3000 (1361)	12.5	3.8	170	140
6000 (2722)	9.8	3	260	210
9500 (4309)	6.4	1.9	380	270

FEATURES

- Power in and Power out
- High Quality 5.0hp Series Wound Motor
- Heavy Duty Waterproof Contactors
- Full Steel Planetary Gearing
- Double sealed motor and drum
- Full Load Holding Brake
- Integrated Wireless remote

INCLUDED

- 0.4" x 46ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



SAMURAI 17500 & 20000 LBS WINCHES

Item Numbers:
S17500
S20000

DESCRIPTION

Warrior Winches are excited to announce the arrival of the colossal Samurai 17500 & 20000lb Winches. Designed for the toughest of applications & tested in the most extreme environments imaginable, these Winches boasts a massive 7.0 & 7.5 hp Series wound motors respectively.

Double sealed drum on maintenance free bearings and quiet, fully sealed efficient full steel planetary gearing ensures these immense Warriors are ready for any battle.

SPECIFICATION

S17500 Winch

RATED LINE PULL:	17 500lbs (7938kg)
MOTOR: 12v :	7.0hp / 4.9kw
GEARING:	430:1
BRAKING ACTION:	Auto in the drum
DRUM SIZE Dia x L:	3.5 x 8.6"
CABLE Dia x L:	0.5" x 85 ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	24 x 8.5 x 10"
WEIGHT:	147.7 lbs

S20000 Winch

RATED LINE PULL:	20 000lbs (9072kg)
MOTOR: 12v :	7.5hp / 5.4kw
GEARING:	430:1
BRAKING ACTION:	Automatic in the drum
DRUM SIZE Dia x L:	3.5 x 8.6"
CABLE Dia x L:	0.47" x 87 ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	24 x 8.6 x 10.7"
WEIGHT:	158.7 lbs

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Reinforced Plastic Contactor Cover
- Double Sealed Drum (G-box/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- High Quality Steel Drum Supports

INCLUDED

- 0.5" x 85ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Wireless Remote



PREDATOR 10,000 LB DUAL MOTOR PERFORMANCE WINCH

**Item Number:
P1000D-SR**

DESCRIPTION

The Predator is designed for hard-core competition. Two powerful 7.2HP sealed motors provide a performance that is truly out of this World, coupling this with a 108:1 ratio 3 stage planetary gearbox enables this performance winch to handle even the most extreme off-road punishment.

With a surprisingly low draw of only 140 amps (at no load), the Predator also contains an innovative “multi stop” 10% ratchet brake design, which provides zero drag when returning the “cable in”, and is situated away from the drum to prevent any damaging heat transferring to your Armortek or Synthetic rope.

The steel drum flanges are precision machined to 0.39” on either side to resist the unique loading characteristics of synthetic rope, while the Alloy Carbon gears are heat treated and tempered to 62HRc rating for extra strength. This Warrior from another dimension will mercilessly prey on its weaker rivals, hunting the opposition down. At 10kg lighter than any of its nearest competitors, with off-load line speeds from 65ft per minute & available with or without synthetic rope, there’s a Predator out there, ready & waiting, for everyone!

SPECIFICATION

RATED LINE PULL: 10 000lbs (4536kg)
MOTOR: 12v : 7.2hp / 5.4kw
GEARING: 108:1
DRUM SIZE Dia x L: 2.8 x 8.42”
CABLE Dia x L: 0.35” x 124ft
MOUNT PATTERN: 10 x 4.5”
DIMENSIONS: 18.8 x 10.3 x 13.9”
WEIGHT: 99lbs

Layer of wire rope	Line pull lbs (kg)	Total Rope on drum ft(m)	Line pull	Line speed	Amp draw
			lbs (kg)	ft(m)/min 12v	12v
1	10000 (4536)	18.4 (5.6)	0	66 (20)	140
2	8153 (3698)	41.0 (12.5)	4000 (1816)	19.7 (6.0)	400
3	6881 (3131)	68.9 (21)	6000 (2722)	16.7 (5.1)	560
4	5953 (2700)	101 (30.8)	8000 (3629)	13.1 (4.0)	690
5	5245 (2379)	131.2 (40)	10000 (4536)	10.5 (3.2)	790

FEATURES

- Dual 7.2HP (5.4KW) Sealed Motors
- Sealed Motor conforms to IP67
- Sealed Waterproof Contactor
- “Multi Stop” 10% Ratchet Brake Design
- Sealed 3 Stage Planetary Gears
- Alloy Carbon Gears hardened to 62HRc Rating
- No load speed of 65ft/min

INCLUDED

- 0.35” x 124ft Synthetic Armortek Rope
- Wireless remote with LCD Display
- Heavy Duty Remote Control
- Silver Warrior Aluminum Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- 12 Ton Competition Hook



NH SERIES HYDRAULIC WINCHES

Item Numbers:
10000NH
15000NH

DESCRIPTION

Compact, tough. A hydraulic winch for industrial and commercial applications. The unique patented steel gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding. Stainless steel roller fairleads and fittings are standard.

SPECIFICATION

10 000 NH HYDRAULIC Winch

RATED LINE PULL:	10 000lbs (4536kg)
MAX LINE PULL:	12 500lbs (5670kg)
MOTOR:	Hydraulic Dis 50 ml/r
GEARING:	33:1
DRUM SIZE Dia x L:	2.8 x 8.8"
CABLE Dia x L:	0.4" x 87ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	20 x 7.3 x 8.8"

15 000 NH HYDRAULIC Winch

RATED LINE PULL:	15 000lbs (6804kg)
MAX LINE PULL:	17 000lbs (7711kg)
MOTOR:	Hydraulic Dis 80 ml/r
GEARING:	37:1
DRUM SIZE Dia x L:	3.5 x 8.8"
CABLE Dia x L:	0.5 x 87ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	20.9 x 8.1 x 9.7"

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Stainless Steel fairlead and Fittings
- Rugged and compact for Long Life

INCLUDED

- Steel cable (see below)
- Heavy Duty Roller Fairlead (10000/15000NH)
- 5/16 or 3/8 Hook

NW SERIES HYDRAULIC WINCHES

Item Numbers:
10000NW
15000NW



DESCRIPTION

Compact, tough. A hydraulic winch for industrial and commercial applications. The special heat treated planetary gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding.

SPECIFICATION

10 000 NW Winch

RATED LINE PULL:	10 000lbs (4536kg)
MAX LINE PULL:	12 500lbs (5670kg)
MOTOR:	Hydraulic Dis 100.8 ml/r
GEARING:	16:1
DRUM SIZE Dia x L:	3.9 x 9.9"
CABLE Dia x L:	1/2" x 86 ft
MOUNTING:	14.6 x 4.5" (11.34 x 4.5")
DIMENSIONS:	25 x 10.33 x 9.39"

15 000 NW Winch

RATED LINE PULL:	15000lbs(6810kg)
MAX LINE PULL:	17 500lbs (7954kg)
MOTOR:	Hydraulic Dis 160 ml/r
GEARING:	17.2:1
DRUM SIZE Dia x L:	5 x 10.6"
CABLE Dia x L:	0.6" x 92 ft
MOUNTING:	11.9 x 4.5" (14.5 x 4.6")
DIMENSIONS:	28.2 x 11.1 x 12"

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Rugged and Compact for Long Life
- Meets the requirements of SAE J706

INCLUDED

- 86 ft x 1/2" steel cable
- 5/16 Hook
- Tensioner included



JP SERIES HYDRAULIC WINCHES

**Item Numbers:
10TJP, 13.5TJP, 15TJP
20TJP, 30TJP, 40TJP**

DESCRIPTION

Tough and compact, the JP series are heavy duty hydraulic winches designed and tested for toughest applications.

Minimum rope to drum ratio of 10:1, multi disc frictional brake, balance valve and rope tensioner as standard.

Available from 10 tonne to 40 tonne. Manufactured to meet GJB82-86 National Military Standard.



FEATURES

- Full Float Heavy Duty Planetary Gearing
- Multi Disc Friction Brake
- Minimum 10:1 Rope/Drum Ratio
- High Torque Industrial Motor
- Air and Manual Clutch Operation

SPECIFICATION

	10TJP	13.5TJP	15TJP
RATED LINE PULL (btm layer):	10 000 kg 22046 lbs	13 500 kg 29762 lbs	15 000 kg 33069 lbs
WORKING SPEED (btm layer):	21.6ft/min*	24.6ft/min	20ft/min
ARRESTER RESP PRESS:	5 Mpa	<2.5 Mpa	<2.5 Mpa
WORKING PRESSURE:	20 Mpa	17 Mpa	17 Mpa
OIL FLOW:	15-75 L/min	110 L/min	110 L/min
DRUM SIZE:	5.4x12.4"	15.7x8.3x13.4"	15.7x8.3x13.4"
REC ROPE SIZE:	157ft x 0.6"	131ft x 0.7"	230ft x 0.9"
WEIGHT:	363 lbs	578 lbs	628 lbs
	20TJP	30TJP	40TJP
RATED LINE PULL (btm layer):	20 000 kg 44092 lbs	30 000 kg 66138 lbs	40 000 kg 88184 lbs
WORKING SPEED (btm layer):	20ft/min	18ft/min	10ft/min
ARRESTER RESP PRESS:	<2.5 Mpa	<2.5 Mpa	<2.5 Mpa
WORKING PRESSURE:	17 Mpa	17 Mpa	17 Mpa
OIL FLOW:	120 L/min	120 L/min	120 L/min
DRUM SIZE:	20.9x8.3x13.4"	20.9x11x14.2"	23.7x11x18.9"
REC ROPE SIZE:	197ft x 1"	197ft x 1.3"	213ft x 1.4"
WEIGHT:	650 lbs	1257 lbs	1763 lbs

*when oil flow 60L/min

INCLUDED

- Heavy Duty Rope Tensioner as Standard
- Balance Valve as Standard

AMORTEK WINCH ROPE

CENTURION WIRELESS REMOTE

ARMORTEK WINCH ROPES

Armortek synthetic rope is 70% stronger than wire!

- Armortek weighs 6 times less than wire.
- Unlike wire, Armortek will not whiplash if broken.
- Armortek is rated at 70% stronger than wire.
- Armortek floats, wire doesn't.
- Armortek is coated to prevent abrasion.
- You don't have to worry about wire splinters.

Diameter	6mm (3/16")	9.5mm (3/8")
Breaking Load	3200 kg (7040 Lb)	7500 kg (16500 Lb)



Part no: HW0884-CAD: 6mm x 16m (1/4" X 50') Synthetic Rope
 Part no: HW0932/45-CAD: 10mm x 14m (3/8" x 45') Synthetic Rope
 Part no: HW0932/85-CAD: 10mm x 26m (3/8" x 85') Synthetic Rope

CENTURION

The ultimate remote for the professional user.

- Two-way Closeslink wireless communication.
- Distinct source code so no interference from other remotes in the vicinity.
- Centurion devices are perfectly watertight.
- Output protection from short circuits & surges.
- Manufactured in highly resistant moulded plastic with a rubber shell for protection.
- The absence of mechanical elements enables functioning in unfavourable environments, with a temperature range from -20°C to +55°C.



Part no: CENT12/242FCT - Centurion Remote

ROLLER FAIRLEAD

ROLLER FAIRLEAD

ALUMINIUM FAIRLEADS

ALUMINIUM FAIRLEADS



Part No: RFF400-CAD
 Chrome 4 Way Roller Fairlead For Winches Up to 4500 lb.



Part No: RFS150-CAD
 Stainless Fairlead With Hole Centres 255mm.



ALI450-CAD - 2500/3500 Winch.
 ALXT450-CAD - 4500 XT Winch.



ALI950-CAD - 9500SD Winch.
 ALI015-CAD - 8000/9500/12000 Winch.

HOOK & RELEASE PIN

2T PULLY BLOCK

4T PULLY BLOCK

8T PULLY BLOCK



CHK014-CAD - 1/4 Steel Hook
 CHK038-CAD - 3/8 Steel Hook
 CHK516-CAD - 5/16 Steel Hook



Part No: PBK300-CAD
 2 Tonne Pully Block Hook Type.



Part No: PBK900-CAD
 4 Tonne Swingway Pully Block.



Part No: PBK150-CAD
 8 Tonne Swingway Pully Block.

WINCH KIT

WINCH KIT PRO

WINCH COVER SMALL

WINCH COVER



Part No: AWK001-CAD
 Warrior Bag, 1m Strop, 1/4 Shackle, 4T Pully Block.



Part No: LWK001-CAD
 Warrior bag, 2m Strop, Gloves, 4.75 Shackle, 8T Pully Block.



Part No: SWC001-CAD
 ATV Small Winch Cover.



Part No: LWC003-CAD
 Winch Cover For Heavy Duty Winches up to 13000lbs.

SHACKLES

SHK325-CAD - 3.25 Tonne Shackle.
SHK475-CAD - 4.75 Tonne Shackle.

TREE STROP

Part No: STP002-CAD
2m x 60mm - 14 Tonne tree strop.

WINCH STOPPER

Part No: RWS001-CAD
Rubber removable winch stopper.

PORTABLE BUMPER

Part No: PWM001-CAD
Portable bumper.

INSTALLATION PLATE

Part No: IST900-CAD
Winch installation plate for
Winches up to 9 000lb.

INSTALLATION PLATE

Part No: IST500-CAD
Winch installation plate for 9500
SD Winches.

INSTALLATION PLATE

Part No: IST600-CAD
Winch installation plate for
Winches up to 15 000lb.

INSTALLATION PLATE

Part No: IST200-CAD
Winch installation plate for
Winches up to 20 000lb.

WIRED REMOTE

Part No: HRO001-CAD
Toggle (WARN Type) Hand Held
Wired Remote.

WIRED REMOTE

Part No: HRO002-CAD
Hand held remote for XT and A
Series (air socket).

ATV HANDLEBAR REMOTE

Part No: ATR001-CAD
ATV / Quad Handlebar Remote.

WIRELESS REMOTE

Part No: CPW001-CAD
Wireless Remote Control With Key
Fob Handset / Air Socket.

WIRELESS REMOTE

Part No: EWX001-CAD
Heavy Duty Wireless Remote
Control / NO Socket.

WIRELESS REMOTE

Part No: EWX002-CAD
Heavy Duty Wireless Remote
Control with Socket.

WIRELESS REMOTE

Part No: EWX003-CAD
Wireless Remote Control for XT
and A series (Air Socket).

ATV CONNECTOR

Part No: AIRS01-CAD
ATV to Standard Socket
Connector.

Y CABLE

Part No: AIRS02-CAD
Y Cable For Dual Connection.

SOLENOID SET

Part No: ATC012-CAD
Solenoid Set For Up to 4500lbs
Winch.

ISOLATION SWITCH

Part No: BAT001-CAD
Battery Isolation Switch.

EXTENSION SOCKET

Part No: EXT001-CAD
Solenoid Box Extension Socket.

HD CONTACTOR

Part No: CON012-CAD
12v Heavy Duty Contactor.

WINCH UPGRADE KIT

Part No: AUK001-CAD
Universal 12v Winch Upgrade Kit &
Mini Thumbswitch.

SNAP CONNECTOR

Part No: QCC400-CAD
400 amp Snap Connector.

6.5 HP 12V MOTOR

Part No: EPW012-CAD
6.5 HP 12v Motor.



DK2 CANADA
1080 Clay Avenue,
Unit 2, Burlington, Ontario,
L7L 0A1, Canada

DK2 USA
6245 Industrial Parkway
Whitehouse, Ohio,
43571, United States

TEL: 1-888-277-6960 WWW.DETAILK2.COM