

16553



Call Us First!
DO NOT RETURN TO STORE.

For questions on assembly or for general inquiries, you may contact us in the following ways:

Call customer service: **1-877-743-3400**

AVOID THE WAIT!

visit us online at
help.backyardproducts.com

- Submit a help request
- Answers to frequently asked questions
- Live chat with an agent



Did you enjoy building your shed?

JOIN OUR TEAM
AND MAKE UP TO \$1,500/WEEK*

Call a Recruiter Today! 734-365-7000




Flexible schedule



No selling,
just building



Bonus incentives
available



*based on number of completed installations




Win \$500

A new winner is selected every 2 months.

Review your product for the chance to win a **\$500 Visa Gift Card**.



How to Enter:



Open camera.
Aim. Tap.



1

Scan
QR code above.

2

Click
'write a review'

3

Find your product.
Tell us what you think.

4

Submit your review.
You'll be notified by e-mail if
you've won the \$500 gift card.

Write a Backyard Products, LLC. product review at backyardreviews.net for a chance to win a \$500 Visa gift card. No purchase necessary to enter. Must be legal U.S. resident (including DC & Puerto Rico), 18 or older to participate. Taxes on prize are responsibility of winner. Odds of winning depend on the number of eligible reviews received. Void where prohibited. For complete details and official rules, visit <https://backyardreviews.net/sweepstakes-rules>.




ASSEMBLY MANUAL

HOMESTEAD 10' x 8' (304,8 x 243,8 cm)

ACTUAL FLOOR SIZE IS 120" x 92-5/8" (304,8 x 235,3 cm)

KEEP THIS MANUAL FOR FUTURE REFERENCE



Building
10' x 8'
(304,9 x 243,8 cm)

⚠ **IMPORTANT!** ⚠

READ INSTRUCTIONS THOROUGHLY PRIOR TO BEGINNING ASSEMBLY.

BEFORE YOU BEGIN

• **BUILDING RESTRICTIONS AND APPROVALS**

Be sure to check local building department and homeowners association for specific restrictions and/ or requirements before building.

• **ENGINEERED DRAWINGS**

Contact our Customer Service Team if engineered drawings are needed to pull local permits.

• **SURFACE PREPARATION**

To ensure proper assembly you must build your shed on a level surface.

Recommended methods and materials to level your shed are listed on page 7.

• **CHECK ALL PARTS**

Inventory all parts listed on pages 4-6.

• **ADDITIONAL MATERIALS**

You will need additional materials to complete your shed. See page 3 for required and optional materials and quantities.



*****CONTACT OUR CUSTOMER SERVICE TEAM
IF ANY PARTS ARE MISSING OR DAMAGED*****
















- Order form and warranty at back of manual -

Call: 1-877-743-3400 email: customerservice@backyardproductsllc.com






TOOLS

Required

- ☐ Phillips Screwdriver 
- ☐ Drill / Driver
 - ☐ 1/8" Drill Bit
 - ☐ 1/4" Drill Bit
 - ☐ 5/16" Drill Bit
 - ☐ 1/2" Drill Bit
 - ☐ #2 Phillips Drive Bit
- ☐ Hammer 
- ☐ Level 
- ☐ Pencil 
- ☐ Tape Measure 
- ☐ Square 

- ☐ Utility Knife 
- ☐ Shingle Blades 
- ☐ Caulk Gun 
- ☐ Paint Tools 
- ☐ Safety Glasses 
- ☐ Hand Saw 
- ☐ Ladder 

Optional

- ☐ Tool Belt/ Nail Pouch 
- ☐ Tin Snips (for drip edge) 
- ☐ Chalk Line 
- ☐ Nail Gun
 - gun nails
- ☐ Gloves 

Safety! Always use approved safety glasses during assembly.

HELPFUL REMINDER SYMBOLS

Look for these symbols for helpful reminders throughout this manual.



= Assistance Required; two or more people.



= Ensure squareness.



= Important required step or operation.



= Helpful assembly hint.



= Mark part with pencil.



= Beginning of steps for assembly or installation.



= You have finished the assembly or installation.






= Level

ORIENT LUMBER AND TRIM FOR BEST APPEARANCE

Framing lumber is graded for structural strength and not appearance. Exterior trim is graded for one good side.

Always install the material leaving the best edge and best surface visible. Please remember that these blemishes in no way negatively affect the strength or integrity of our product. (See Fig. A, B, C.)



ADDITIONAL MATERIALS

FOUNDATION OR FLOOR MATERIALS


- This shed includes a floor.
- See the FLOOR LEVELING section on page 7 for recommended methods and suggested materials to properly level your floor, as this will vary depending on your specific site.

REINFORCED WOOD FLOOR FRAME (OPTIONAL)

IMPORTANT! This floor has been designed for general use. Depending on your specific use you may want to construct a heavy duty floor frame by adding additional floor joists (shown below as shaded).

Below is a list of additional materials (not included):

- ☐ **x1** 2 x 4 x 8' (5 x 10 x 243,8 cm) Treated Lumber
Cut to (2) 2 x 4 x 89-5/8" (5 x 10 x 227,6 cm)
- ☐ **x8** ea. 3" (7,6 cm) Hot Dipped Galvanized Nails



COMPLETING YOUR SHED


You will need these additional materials:

- | | |
|---|---|
| <input type="checkbox"/> PAINT FOR SIDING 2 Gallons
Use 100% acrylic latex exterior paint. (2) coats recommended. | <input type="checkbox"/> PAINT FOR TRIM 1 Quart
Use 100% acrylic latex exterior paint. |
| <input type="checkbox"/> CAULK 2 Tubes
Use acrylic latex exterior caulk that is paintable.  | |



TO VALIDATE YOUR WARRANTY YOU MUST USE THE FOLLOWING:



- ☐ **CAULK** **1 Tube** 
For windows use acrylic latex exterior caulk that is paintable.

PARTS IDENTIFICATION AND SIZES

Part identification letters are stamped on some parts.



Check these locations for part stamp.

WOOD SIZE CONVERSION CHART

Nominal Board Size

Actual Size

2 x 41-1/2" x 3-1/2"	(3,8 x 8,9 cm)
1 x 43/4" x 3-1/2"	(1,9 x 8,9 cm)
2 x 31-1/2" x 2-1/2"	(3,8 x 6,3 cm)
1 x 33/4" x 2-1/2"	(3,8 x 6,3 cm)

PARTS LIST




INVENTORY YOUR PARTS before you begin.

We suggest sorting parts by the category they are listed in.

WALLS

- ☐ x1 **GAA** 1 x 3 x 5" (2,5 x 7,6 x 12,7 cm) Gauge Block for 3/4" (1,9 cm) measurement
- ☐ x2 **JBD** 2 x 4 x 20-3/8" (5,1 x 10,2 x 51,8 cm)
- ☐ x1 **GSB** 2 x 4 x 23-3/4" (5,1 x 10,2 x 60,3 cm)
- ☐ x2 **KHA** 2 x 4 x 24-1/2" (5,1 x 10,2 x 62,2 cm)
- ☐ x2 **CKB** 2 x 3 x 25-1/2" (5,1 x 7,6 x 64,8 cm)
- ☐ x2 **BNC** 2 x 3 x 26-1/4" (5,1 x 7,6 x 66,7 cm)
- ☐ x22 **UM** 2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)
- ☐ x1 **HJ** 1 x 3 x 72" (2,5 x 7,6 x 182,9 cm)
- ☐ x1 **GBD** 2 x 4 x 89-1/4" (5,1 x 10,2 x 226,7 cm)



ROOF

- ☐ x4 **DHB** 2 x 3 x 71-1/4" (5,1 x 7,6 x 181 cm)
- ☐ x6 **TJ** 2 x 4 x 92-5/8" (5,1 x 10,2 x 235,3 cm)
- ☐ x6 **FYA** 2 x 4 x 93-3/8" (5,1 x 10,2 x 237,2 cm)

TRIM

- ☐ x2 3/8 x 2-5/8 x 25-1/8" (1 x 6,7 x 63,8 cm)
- ☐ x10 3/8" x 1-3/4" x 69" (1 x 4,4 x 175,3 cm)
- ☐ x6 3/8" x 1-3/4" x 70-1/2" (1 x 4,4 x 179,1 cm)
- ☐ x2 **JGR** 19/32" x 3-1/2" x 71-7/8" (1,5 x 8,9 x 182,6 cm)
- ☐ x2 **JGL** 19/32" x 3-1/2" x 71-7/8" (1,5 x 8,9 x 182,6 cm)
- ☐ x2 3/8 x 2-5/8 x 72" (1 x 6,7 x 182,9 cm)
- ☐ x2 **EEB** 2 x 3 x 94-1/8" (5,1 x 7,6 x 239,1 cm)

DOORS

- ☐ x4 **AH** 19/32" x 2-1/2" x 26-5/8" (1,5 x 6,3 x 67,6 cm) 19/32" x 2-1/2" x 72" (1,5 x 6,3 x 182,9 cm)
- ☐ x2 **OO** 69" (175,3 cm) Door Stiffener
- ☐ x1 **ZJ** 19/32" x 2-1/2" x 72" (1,5 x 6,3 x 182,9 cm)

FLOOR

- ☐ x1 **TREATED** 2 x 4 x 24" (5,1 x 10,2 x 61 cm)
- ☐ x1 **TREATED** 2 x 4 x 48" (5,1 x 10,2 x 121,9 cm)
- ☐ x1 **TREATED** 2 x 4 x 72" (5,1 x 10,2 x 182,9 cm)
- ☐ x9 **TREATED** 2 x 4 x 89-5/8" (5,1 x 10,2 x 227,6 cm)
- ☐ x1 **TREATED** 2 x 4 x 96" (5,1 x 10,2 x 243,8 cm)

Treated lumber is stamped:




TREATED

PANEL PARTS LIST

WALL PANELS & DOORS

Wall panels are 3/8" (1,1 cm) thick.


NOTE: Panel parts are not stamped.



FLOOR PANELS





Floor panels are 5/8" (1,6 cm) thick.

NOTE: Panel parts are not stamped.





PARTS LIST continued...



METAL ROOFING



NAIL BOXES





FASTENERS / HARDWARE BAG








NOTE:

If you are using a nail gun, nails may be used where screws are shown for quicker assembly. Length of nail must match screw length.




VENTS / DOOR HARDWARE / WINDOW



FLOOR LEVELING OPTIONS

There are multiple ways to level your floor frame. Our recommended leveling method is shown below.
Leveling materials are not included in this kit.

PREFERRED METHOD - 4x4 TREATED RUNNERS




MATERIAL REQUIRED

☐ x2 4 x 4 x 10' (10,1 x 10,1 x 304,8 cm) Treated Lumber

☐ Fasteners for Frame to 4x4.
(3" Screws shown as one option.) Minimum (36) 3" screws / exterior grade.

! Use only wood treated for ground contact and fasteners approved for use with treated wood.

! Always support frame seams.



LEVELING METHODS

- Level under 4x4 runners only.
- Locate leveling material 12" from ends of runners and no more than 48" apart.
- Asphalt shingles should be used between 4x4 runners and blocks or treated lumber. Never use shingles in direct contact with ground.
- For best results and aiding in water drainage use gravel under each concrete block.

LEVELING MATERIALS

- ☐ Gravel
- ☐ Solid Masonry Blocks in 1", 2", 4" or 8" thickness
- ☐ 2x4 Treated Lumber
- ☐ Asphalt Shingles


! Leveling higher than 16" not recommended.

CONCRETE

- If you are building your shed on a concrete foundation see the following page.

CONCRETE FOUNDATION

If you choose to install your kit on a concrete slab, refer to the diagram below.



Building Size	Actual Size	A	B	C
10' x 8' (304,8 x 243,8 cm)	120" x 92-5/8" (182,9 x 235,3 cm)	92-5/8" (235,3 cm)	85-5/8" (227,6 cm)	120" (304,8 cm)

Use treated lumber supplied in kit.

- ☐ **x2** 2 x 4 x 10' (5 x 10 x 304,8 cm) **MUST be treated lumber.**
- ☐ **x2** 2 x 4 x 8' (5 x 10 x 243,8 cm) Cut to (2) 85-5/8" (227,6 cm) **MUST be treated lumber.**
- ☐ **x1** Caulk

Allow new concrete slabs to cure for at least seven (7) days.


- A treated 2 x 4 (5,1 x 10,2 cm) sill plate is required when installing your shed on concrete.
- Use a high quality exterior grade caulk beneath all sill plates.
- Fasten 2 x 4 (5,1 x 10,2 cm) sill plates to slab using approved concrete anchors (**fasteners not included**).
- Check local code for concrete foundation requirements.

NOTES

FLOOR FRAME

PARTS REQUIRED:

x1 **TREATED** 2 x 4 x 24" (5,1 x 10,2 x 61 cm)


x40  3" (7,6 cm)

x1 **TREATED** 2 x 4 x 48" (5,1 x 10,2 x 121,9 cm)

NOTE: Look for **TREATED** Stamp.

x1 **TREATED** 2 x 4 x 72" (5,1 x 10,2 x 182,9 cm)

x9 **TREATED** 2 x 4 x 89-5/8" (5,1 x 10,2 x 227,6 cm)



x1 **TREATED** 2 x 4 x 96" (5,1 x 10,2 x 243,8 cm)

BEGIN



1 Orient parts as shown on flat surface.

Measure and mark each dimension from end of boards.

Secure with (2) 3" nails at each mark and (4) 3" nails at seams.



HINT:
For easier nailing
stand on frame.



FINISH

Your floor frame is now assembled.


STOP!**LEVEL AND SQUARE FLOOR FRAME****STOP!**

Before attaching floor decking, it is important to level and square the floor frame.
A level and square floor frame is required to correctly construct your shed.

✓ BEGIN

- 1 See page 7 for the preferred floor leveling method.
- 2 Use level and check the frame is level before applying floor panels.
- 3 Check for frame squareness by measuring diagonally across corners.
If the measurements are the same, the frame is square.
The diagonal measurement will be approximately 151-9/16" (385 cm).
- 4 When the frame is level and square secure one side of frame to the 4x4 runners using one fastener at ends of each runner.
Move to the opposite end of the frame.
Secure the frame to 4x4 runners with one fastener at ends of each runner making sure the frame remains square (**Fig. A**).

First, secure at ends with one fastener.



Once the floor frame is level and square, fasten the frame to the 4x4 runners wherever the frame contacts the 4x4 runners.

FLOOR PANELS

PARTS REQUIRED:


GAA
3/4" GAUGE
BLOCK

x1



5/8 x 48 x 96"
(1,6 x 121,9 x 243,8 cm)

x53




Install panels with rough side up (painted grid lines).

✓ **BEGIN**

1 Install the **48" x 96"** panel with the edges and corner flush to the outside of the floor frame.

Use **GAA** as a spacer for consistent 3/4" measurement.

Secure panel with 2" nails spaced 6" apart on edges and 12" apart inside panel.



FLOOR PANELS

PARTS REQUIRED:

x1





5/8 x 23-7/8 x 92-5/8"
(1,6 x 60,6 x 235,3 cm)

x1




5/8 x 44-5/8 x 96"
(1,6 x 113,39 x 243,8 cm)

x100



- Install **23-7/8" x 92-5/8"** (use **GAA**) and **44-5/8" x 96"** floor panels flush to the installed panels.
Secure panels with 2" nails 6" spaced apart on edges and 12" apart inside panel.




Your floor panels are now installed.

IMPORTANT!




Check that the floor frame is level after installing floor panels.
Re-level if needed.



HINT:

- The floor should be used as a stable work surface for wall construction.
- Organize your assembly procedure during the build process to avoid over-handling of the walls.




SIDE WALLS

PARTS REQUIRED:

x10 **UM**
2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)

x4 **TJ**
2 x 4 x 92-5/8" (5,1 x 10,2 x 235,3 cm)


x40  3" (7,6 cm)



Build (2) identical side walls.



✓ BEGIN

- 1 Orient parts on edge on floor. Measure and mark.
Secure with (2) 3" nails at each mark.




SIDE WALLS

PARTS REQUIRED:



- 2** Install (2) 46-1/8" x 72" wall panels with primed side up. Use **GAA** for 3/4" measurement on frame. Secure panels to frame with 2" nails spaced 6" apart along edges and 12" apart on inside of panel.



Repeat steps to build your 2nd side wall.



Your (2) side walls are now assembled.
Carefully flip the wall over.

BACK WALL

PARTS REQUIRED:

x2 **JBD** 2 x 4 x 20-3/8" (5,1 x 10,2 x 51,8 cm)

x6 **UM** 2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)


x2 **TJ** 2 x 4 x 92-5/8" (5,1 x 10,2 x 235,3 cm)

x28 3" (7,6 cm)




✓ BEGIN

- 1 Orient parts on edge on floor. Measure and mark.
Secure with (2) 3" nails at each mark and (4) 3" nails at seams.




BACK WALL


PARTS REQUIRED:

x2  48" x 72"
(121,9 x 182,9 cm)

x1  23-7/8" x 72"
(60,6 x 182,9 cm)


 **3/4" GAUGE BLOCK**

x122  2" (5,1 cm)




Install all panels with the primed side facing up.

- 2** Install (1) 48" x 72" panel, as shown. Use **GAA** for consistent measurement.
Secure panel to frame with 2" nails spaced 6" apart along edges and 12" apart on inside of panel.



- 3** Install (1) 23-7/8" x 72" panel and (1) 48" x 72" panel flush to each installed panel.
Secure panels to frame with 2" nails spaced 6" apart along edges and 12" apart on inside of panel.



Your back wall is now assembled.
Carefully flip the wall over.

FRONT WALL

PARTS REQUIRED:

x1 **GSB**

2 x 4 x 23-3/4" (5,1 x 10,2 x 60,3 cm)

x6 **UM**

2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)

x2 **KHA**

2 x 4 x 24-1/2" (5,1 x 10,2 x 62,2 cm)

x1 **GBD**

2 x 4 x 89-1/4" (5,1 x 10,2 x 226,7 cm)

x26

3" (7,6 cm)





✓ BEGIN

1






Orient parts on edge on floor. Measure and mark.

Secure with (2) 3" nails at each mark and (4) 3" nails at seam.

HINT:
For easier nailing
stand on frame.




FRONT WALL

PARTS REQUIRED: x2  x116 
 3" (7,6 cm)
 2" (5,1 cm)
 x2  15-7/8" x 72"
 (40,3 x 182,9 cm) x2  11-7/8" x 72"
 (30,2 x 182,9 cm)
 x1  TEMPORARY SUPPORT 69" (175,3 cm) Door Stiffener

Install all panels with the primed side facing up.

2 Install (2) 15-7/8" x 72" panels flush to top of frame and flush along edges, as shown.
 Secure panels with 2" nails spaced 6" apart.

3 Install (2) 11-7/8" x 72" panels flush to installed panels and flush to top of frame.
 Secure panels with 2" nails spaced 6" apart.




4 Install temporary support OO to frame with 3" screws.

FRONT WALL


PARTS REQUIRED:

x1 **HJ**
1 x 3 x 72" (2,5 x 7,6 x 182,9 cm)



- 5** Center **HJ** on front wall flush to the edge of wall panels (**Fig. A**, **Fig. B**).

Secure **HJ** with (5) 2" nails spaced evenly.




Your front wall is now assembled.

Carefully flip the wall over.

RIGHT WALL INSTALLATION

PARTS REQUIRED:

x1 **OO** TEMPORARY SUPPORT
69" (175,3 cm) Door Stiffener




x8 3" (7,6 cm)
x2 3" (7,6 cm)
x18 2" (5,1 cm)

✓ BEGIN


- 1 Center right side wall on the 96" (243,8 cm) floor dimension.
Ensure the 1" (2,5 cm) wall panel overlap is to the bottom.

Install **OO** as a temporary brace.
Secure **OO** with (2) 3" screws.



- 3 Secure lower edge of wall panels to floor frame with 2" nails spaced 6" apart.
Angle nail to hit floor frame (**Fig. A**).






Secure wall bottom plates to floor with 3" nails (**Fig. A**).



Your right side wall is now installed.

BACK WALL INSTALLATION




PARTS REQUIRED: x23  x1 
x13  x2  x10 

✓ **BEGIN**


1

Center back wall assembly on the 120" (304,8 cm) floor dimension.
Ensure the 1" (2,5 cm) wall panel overlap is to the bottom.



2

Secure back wall panel to side wall with (1) 2" screw into side wall top and bottom plate (**Fig. A**, **Fig.B**).



⚠ **ENSURE TOP OF WALL FRAMES ARE FLUSH.**

3



Nail lower edge of wall panels to floor with 2" nails spaced 6" apart.
Angle nails into floor frame (**Fig. C**).

Nail back wall panel to side wall stud with 1-1/2" nails spaced 6" apart.

4

Secure back wall bottom plate to floor with 3" nails (**Fig. C**).






Secure wall top plates with (1) 3" screw angled at the corner (**Fig. D**).



Your back wall is now installed.

LEFT WALL INSTALLATION




PARTS REQUIRED: x18  x1 
x13  x2  x8 

✓ **BEGIN**

1


Center left wall assembly on the 96" (243,8 cm) floor dimension.
Ensure the 1" (2,5 cm) wall panel overlap is to the bottom.



2

Secure back wall panel to side wall with (1) 2" screw into left wall top and bottom plate (**Fig. A, Fig.B**).

⚠ **ENSURE TOP OF WALL FRAMES ARE FLUSH.**



3


Nail lower edge of side wall panels to floor with 2" nails spaced 6" apart.
Angle nails into floor frame (**Fig. C**).

Nail back wall panel to side wall stud with 1-1/2" nails spaced 6" apart.

4

Secure left wall bottom plate to floor with 3" nails (**Fig. C**).


Secure wall top plates with (1) 3" screw angled at the corner (**Fig. D**).



Your left wall is now installed.

FRONT WALL INSTALLATION

PARTS REQUIRED




✓ BEGIN

- 1 Place front wall on floor centered between installed walls.

Secure wall with 2" screws into top and bottom plates (Fig. A, Fig. B).

Secure wall to bottom plate first.

⚠ ENSURE PANEL CORNERS ARE FLUSH. ⚠





- 2 Nail lower edge of panels to floor with 2" nails spaced 6" apart. Angle nails into floor frame (Fig. C).

Nail wall panels to side wall studs with 1-1/2" nails spaced 6" apart.

Secure wall bottom plates to floor with 3" nails (Fig. C).

- 3 Secure wall top plates with 3" screws at each corner at an angle (Fig. D).



FINISH

Your walls are now installed.

SQUARING THE WALLS

PARTS REQUIRED:



x1 2 x 4

x1 2 x 4

You must square the walls after they are standing.

The 120" dimension is taken from the outside of the framing (Fig. A).



A square shed means you will have a straight and professional looking roof.

ALL WALLS MUST BE:


- LEVEL
- PLUMB
- SQUARE

THE FINAL DIMENSIONS WILL BE EQUAL:

- CORNER TO CORNER



- 1 Determine which corner of your shed needs to be lifted to bring the walls into square. Use the method below to help lift the floor up to level.



- 2 Once you have equal dimensions add shims under the floor to keep your shed square.



Your shed is now square and level.

FRONT GABLE UNIT

PARTS REQUIRED:

x2 **CKB**
2 x 3 x 25-1/2" (5,1 x 7,6 x 64,8 cm)

x1
25-3/4 x 48"
(65,4 x 121,9 cm)

x1
23-7/8 x 31-1/2"
(60,6 x 80 cm)

x1
25-3/4 x 48"
(65,4 x 121,9 cm)


x20 1-1/2" (3,8 cm)




Install all panels with the primed side facing up.

✓ BEGIN

- 1 Arrange (2) **CKB** and the 23-7/8" x 31-1/2" center panel as shown.
Secure parts with 1-1/2" nails evenly spaced.



- 2 Instal left and right front gable panels flush to center panel.
Secure parts with 1-1/2" nails evenly spaced.



You have finished assembling your front gable unit.

BACK GABLE UNIT

PARTS REQUIRED:

x2 **BNC**
2 x 3 x 26-1/4" (5,1 x 7,6 x 66,7 cm)

x1
27-1/4 x 48"
(69,2 x 121,9 cm)

x1
23-7/8 x 33"
(60,6 x 83,8 cm)

x1
27-1/4 x 48"
(69,2 x 121,9 cm)


x20 1-1/2" (3,8 cm)




Install all panels with the primed side facing up.

✓ BEGIN

- 1 Arrange (2) **BNC** and the 23-7/8" x 33" center panel as shown.
Secure parts with 1-1/2" nails evenly spaced.




- 2 Instal left and right front gable panels flush to center panel.
Secure parts with 1-1/2" nails evenly spaced.




You have finished assembling your back gable unit.

FRONT GABLE

PARTS REQUIRED:



Front Gable Unit




✓ BEGIN

- 1 Measure 1-1/2" down from top plate and mark at each side as shown. Set gable unit on top plate. Fasten with (1) 2" nail on each side.



⚠ BE SURE GABLE IS CENTERED ON WALL BEFORE NAILING.

- 2 Continue nailing lower edge of panels to gable nailer and top plate with 2" nails spaced 6" apart.




- 3 Working inside, secure gable unit with 3" screws angled into (2) gable connectors **CKB** at an angle (**Fig. A**).



Your front gable unit is now installed.

BACK GABLE

PARTS REQUIRED:



Back Gable Unit




x4 3" (7,6 cm)

x23 2" (5,1 cm)




✓ BEGIN

- 1 Measure 1-1/2" down from top plate and mark at each side as shown.
Set gable unit on top plate. Fasten with (1) 2" nail on each side. 

 **BE SURE GABLE IS CENTERED ON WALL BEFORE NAILING.**

- 2 Continue nailing lower edge of panels to top plate with 2" nails spaced 6" apart.



- 3 Working inside, secure gable unit with 3" screws angled into (2) gable connectors **BNC** at an angle (**Fig. A**).




Your back gable unit is now installed.

FRONT GABLE TRIM FILLER

PARTS REQUIRED:


x2 **DHB**
2 x 3 x 71-1/4" (5,1 x 7,6 x 181 cm)



x16 
1-1/4" (3,2 cm)

✓ **BEGIN**

- 1 Working from inside of gable, install (2) **DHB** flush along edge of gable panels and flush at peak.
Secure **DHB** with 1-1/4" screws spaced evenly..



Repeat steps to install back gable filler





FINISH


Your front and back gable trim fillers are now installed.


SOFFIT TRIM UNITS


PARTS REQUIRED:


x2  3/8 x 2-5/8 x 25-1/8" (1 x 6,7 x 63,8 cm)

x2  3/8 x 2-5/8 x 72" (1 x 6,7 x 182,9 cm)

x2 **EEB**  2 x 3 x 94-1/8" (5,1 x 7,6 x 239,1 cm)

x8  3" (7,6 cm)


x44  1" (2,5 cm)




Install fascia with the primed side facing up.

BEGIN

- 1 Arrange (1) soffit nailer **EEB**, (1) 2-5/8" x 25-1/8" and (1) 2-5/8" x 72" soffit fascia boards on a flat surface. Adjust fascia boards to measurements shown at ends of **EEB**. Flush fascia boards at seam and along **one edge** of **EEB**. Secure parts with 1" screws in pattern shown.



- 2 Install soffit unit flush to top of front and back gable fillers. **Install the 1/8" fascia overlap toward the bottom.** Secure 3/8" fascia to gable filler with (2) 1" screws at each end (**Fig. A**). Secure soffit nailer **EEB** to gable filler with (2) 3" screws at each end (**Fig. A**).



Repeat steps to install opposite side trim unit.




FINISH


Your soffit trim units are now installed.

ROOF PURLINS

PARTS REQUIRED:


x6 **FYA**
2 x 4 x 93-3/8" (5,1 x 10,2 x 237,2 cm)

x24  3-1/2" (8,9 cm)




✓ BEGIN

- 1 Align **FYA** using notches in the gable panel for position (**Fig. A**).
Secure (6) **FYA** with 3-1/2" screws.





Repeat steps for securing purlins at both sides.




Your roof purlins are now installed.

CORNER TRIM

PARTS REQUIRED:

- x4**  3/8" x 1-3/4" x 69" (1 x 4,4 x 175,3 cm)
- x4**  3/8" x 1-3/4" x 70-1/2" (1 x 4,4 x 179,1 cm)




x64  2" (5,1 cm)



✓ BEGIN

- 1** Install **70-1/2"** corner trim under gable panel (**Fig. A**) and flush to eave wall panel (**Fig. B**). Secure with 2" finishing nails spaced evenly.
- 2** Install eave side **69"** corner trim flush to eave soffit (**Fig. A**) and flush along seam of installed corner trim (**Fig. B, Fig. C**). Secure with 2" finishing nails spaced evenly.



Repeat steps for each corner of shed.



FINISH

Your corner trim is now installed.

GABLE TRIM

PARTS REQUIRED:


- x2 **JGR**
19/32" x 3-1/2" x 71-7/8" (1,5 x 8,9 x 182,6 cm)
- x2 **JGL**
19/32" x 3-1/2" x 71-7/8" (1,5 x 8,9 x 182,6 cm)

x2 6-3/4" x 25-7/16"
(17,1 x 64,6 cm)




x64

2" (5,1 cm)




✓ BEGIN

- 1 Install 6-3/4"x 25-7/16" gable filler panel flush to gable filler, as shown.
Secure with 2" finishing nails into framing.



Repeat to install trim panel on opposite side.

- 2 Install **JGL** and **JGR** flush with top of gable filler.
Secure trim with 2" finishing nails spaced evenly, as shown.




Repeat to install gable trim on opposite side.



Your gable trim is now installed.


METAL ROOF PANELS

PARTS REQUIRED:




✓ **BEGIN**

- Using (2) clamps, tightly clamp a string or chalkline to front and back gable trim. Position string flush to top corner edge of gable trim (**Fig. A, Fig. B**).




- Mark each center line dimension shown on top of gable trim. Place the first roof panel with front bottom corner 3/4" back from the gable trim (**Fig. C**) and bottom edge in line with string. Referencing the center line marks on top of the gable trim, secure panel to soffit trim and purlins with (3) 1-1/2" screws. Install screws in panel valley (**Fig. D**) nearest edge.




METAL ROOF PANELS


PARTS REQUIRED:

x4  1-1/2" (3,8 cm)


x1  **Metal Roof Panel**
25-1/4" x 71-1/2" (64,1 x 184,2 cm)



Install roof panel with 3 overlapping contour waves covering the previously installed panel.




- 3** Position 2nd panel overlapping the first panel by 3 panel contour waves (**Fig. D**) and flush to string. Secure panel to trim **EEB** and roof joists **FYA** with (3) 1-1/2" screws in panel valley nearest edge.




METAL ROOF PANELS


PARTS REQUIRED:



Metal Roof Panel
25-1/4" x 71-1/2" (64,1 x 184,2 cm)



- 4** Install (3) more metal roof panels as in STEP - 3.
Overlap the first 2 panels by 3 panel contour waves and overlap the final panel by 4 contour waves.
Install (4) screws in each panel valley nearest edge. Install (8) screws in last panel, as shown.



METAL ROOF PANELS

PARTS REQUIRED:

x10 Closure Strip 24" (61 cm)


x24 1-1/2" (3,8 cm)



- 5** Temporarily back-out the lower (6) screws from metal panels and eave trim (**Fig. E**).

Beginning at the front panel, tuck (5) foam enclosures in between roof panels and eave trim.

Reinstall screws.




- 6** Install (5) roof panels on opposite side of roof following STEPS 1 - 5, beginning at the front gable.

METAL ROOF PANELS - SCREW PATTERN


PARTS REQUIRED:



x64



x24



✓ BEGIN

1 Measure and mark screw type and locations shown in this view. *Use this pattern for all panels.*


X indicates 7/8" Screws (Peak edge of each panel)

○ indicates 1-1/2" Screws


● screws already installed

NOTE:

4th panel screw-spacing is 3rd and 5th valley.



1-1/2" Screws
in valley only



EXAMPLE A

7/8" Screws
at peak edge
only

NOTE:

*Only (3) lower 7/8" screws
per panel at this time.*

METAL RIDGE CAP

PARTS REQUIRED:

x2 


Ridge Cap

4" x 4" x 54" (10,2 x 10,2 x 137,2 cm)

x10 


Closure Strip 24" (61 cm)




x12 
7/8" (2,2 cm)

✓ BEGIN

- 1 Install 1st ridge cap flush to front of roof panels across the peak of the roof.
Foam enclosures go in-between the metal roof and the bottom edge of the ridge cap, as shown.
Secure with (4) 7/8" screws 1/2" from edge of ridge cap (**Fig A**).
Install screws in second peak from end of ridge cap (**Fig B**).



- 2 Install 2nd ridge cap flush to back of roof panels, across the peak of the roof and overlapping the installed ridge cap.
Install foam enclosures as in STEP - 1 with (8) 7/8" screws.
Install screws in second peak from end of ridge cap (**Fig B**).




Your ridge cap are now installed.

METAL DRIP EDGE


PARTS REQUIRED:

x4 Metal Drip Edge
3" x 95-1/2" (7,0 x 217,2 cm)




✓ BEGIN

- 1 Measure and mark 72" (182,9 cm) mark on (1) drip edge strip.
- 2 Using a framing square scribe a 28° line from your center point, cut the line.



- 3 Measure and mark 52-1/4" (132,7 cm) on (1) drip edge strip.




METAL DRIP EDGE (continued)

PARTS REQUIRED:




x16
7/8"
(2,2 cm)

- 4** Install pre-cut 54-1/4" drip edge flush to gable trim.
Secure with (2) 7/8" screws, as shown (**Fig. A**).



- 5** Place 72" drip edge centered at peak of gable. Fold down at center cut over peak of gable.
Position vertical edge of drip edge flush to gable trim.
Secure with (6) 7/8" screws per side, as shown (**Fig. A**).



Repeat steps to install drip edge at opposite gable.








FINISH

Your drip edge is now installed.


DOORS

PARTS REQUIRED:



✓BEGIN


- 1 Orient parts as shown on flat surface. **⚠ 3/8" offset is to top.**
Look for red (right) and green (left) on hinge board.
- 2 Attach temporary support **OO** with 3" screws in middle and at ends as shown.
- 3 Attach temporary support **GAA** with (2) 1-1/4" screws as shown.




DOORS


PARTS REQUIRED:



x1 **OO**
69" (175,3 cm) Door Stiffener


x12  3" (7,6 cm)




- 4** Attach temporary support **OO** as a ledger board flush under wall panels for doors to rest on, using (3) 3" screws (**Fig. A**).



- 5** Center doors on panel seam as shown (**Fig. B**). 
 Check ledger board is still flush under panels.

- 6** Screw hinge boards into wall supports and floor using (10) 3" screws, as shown.
 Make sure screws go into framing and floor (**Fig. C, D**).

Remove temporary supports and check doors open properly.




Your doors are now installed.


DOOR TRIM

PARTS REQUIRED:

x4 **AH**
19/32 x 3 x 26-5/8" (1,5 x 7,6 x 67,6 cm)


x1 **ZJ**
19/32" x 3" x 72" (1,5 x 7,6 x 183 cm)

x5  2" (5,1 cm)

x56  3/4" (1,9 cm)




BEGIN

- 1 Secure door trim from inside using 3/4" screws as shown (**Fig. A**).
- 2 Secure (2) horizontal door rails **AH** with (4) 3/4" screws from behind to center of doors as shown.
- 3 Reinforce the door trim using 3/4" screws through door panel into trim (**Fig. A**).
Locate screws as shown in **Fig. B**. Use (2) screws at seams.
- 4 Center trim **ZJ** over doors and secure using (5) 2" finish nails into framing as shown.



DOOR TRANSOM WINDOWS


PARTS REQUIRED:



✓ BEGIN

- 1 Apply high quality exterior-grade caulk behind frame near edge before installing to seal window.

You must caulk completely around window frame and all exposed door panel edges and trim to validate your warranty. Use a paintable exterior rated caulk.




FRONT SIDE VIEW

- 2 From back side of door, measure 15-13/16" from inside edge of door. Mark center of window opening on door.

Position window in opening flush to bottom of window opening. Center window on mark.

Use (4) screws to secure each window.



BACK SIDE OF DOORS





Your transom windows are installed.

DOOR STIFFENERS

PARTS REQUIRED:

x2 **OO**
69" (175,3 cm) Door Stiffener

x14 
2" (5,1 cm)



✓ BEGIN

- 1 Center **OO** vertically on the left door in the doorway (**Fig. A**) overlapping 1" (2,5 cm) along the edge of door (**Fig. B**).
Secure with (7) 2" screws through outside trim into **OO**.
- 2 Center **OO** vertically on the right door in the door opening offset 1" (2,5 cm) from the edge of door (**Fig. B**).
Secure with (7) 2" screws through outside trim into **OO**.






Fig. A




2"
(5,1 cm)
Screws
x14



Your door stiffeners are now installed.

DOOR HARDWARE

PARTS REQUIRED:




✓ BEGIN

- 1 Measure and mark location of hole on outside of right door as shown **(Fig. A)**. Pre-drill hole with 1/4" drill.
- 2 Re-drill hole with 1/2" drill **(Fig. B)**.



Keep drilled hole square to trim to avoid breaking edge of 1-1/2" x 2-1/2" door stiffener.



- 3 Install decorative hinges on horizontal trim and flush against hinge.

- 4 Insert handle in hole and secure with 1-1/2" screws.


- 5 Install inside handle and secure with set screw.



You have now installed your T-handle and decorative hinges.




DOOR HARDWARE

PARTS REQUIRED:



✓ BEGIN




- 1 Place bolt on **OO** in open position with bolt end 3/8" (9,5 mm) down from frame. Bolt is open when loop is contacting base (**Fig. A**).
- 2 Mark and pre-drill holes for screws. Install bolt with screws supplied. Drill 5/16" (7,9 mm) hole deep enough for bolt to slide into.
- 3 Place bolt on **OO** in open position with bolt end 1/2" (12,7 mm) up from floor. Bolt is open when loop is connecting base (**Fig. B**).
- 4 Mark and pre-drill holes for screws. Install bolt with screws supplied. Drill 5/16" (7,9 mm) hole deep enough for bolt to slide into.



Your spring bolts are now installed.

DOOR HARDWARE / DECORATIVE HINGES

PARTS REQUIRED:



1/2" (1,3 cm) Drill Bit

1/4" (0,6 cm) Drill Bit



✓ BEGIN


- 1 Measure and mark location of hole on outside of right door as shown (Fig. A).

Pre-drill hole with 1/4" drill.


Re-drill hole with 1/2" drill.



Keep drilled hole square to trim to avoid breaking edge of door stiffener.





- 2 Insert handle in hole and secure with 1-1/2" screws.
- 3 Install inside handle and secure with set screw as shown.
- 4 Install decorative hinges on horizontal trim and flush against hinge, as shown. Secure hinges with 3/4" screws.




You have now installed your T-handle and decorative hinges.

WALL BATTENS

PARTS REQUIRED:


- x6**  3/8" x 1-3/4" x 69" (1 x 4,4 x 175,3 cm)
- x2**  3/8" x 1-3/4" x 70-1/2" (1 x 4,4 x 179,1 cm)



✓ BEGIN

1


Install (2) **70-1/2"** front battens under gable panel (**Fig. A**).
Secure with 2" finishing nails spaced evenly.



2




Install (6) eave side **69"** battens flush to eave soffit (**Fig. A**).
Measure and mark centers of battens from corner trim. Middle batten covers the seam.

Secure with 2" finishing nails spaced evenly.



VENTS

- Follow directions provided by manufacturer and these instructions.



✓ BEGIN



- 1 Locate and mark for (2) vents in side and back walls, as shown;

(1) at top and (1) at bottom.

Cut out marked openings.

Caulk behind vent flanges.

Secure with 1/2" screws.



Your vents are now installed.

16553 10' x 8' Order Form

CATEGORY	PART DESCRIPTION	PART SIZE	PART ITEM #	BUILDING QTY.	PART ID
2 X 3	Gable Connector - Back	2 X 3 X 26-1/4" 28" GABLE CONN	Q 26042800000	2	BNC
	Gable Connector - Front	2 X 3 X 25-1/2" 28" GABLE CONN	Q 25082800000	2	CKB
	Gable Nailer	2x3x71-1/4" @ 28" O/E	Q 71042800000	4	DHB
	Soffit Nailer	2x3x94-1/8"	Q 94020000000	2	EEB
2 X 4	Purlin	2x4x93-3/8	O 93060000000	6	FYA
	Sidewall Plate / Backwall Plate "A"	LUM SPF 2X4X92-5/8 #2&BTR	12305	6	TJ
	Backwall Plate "B"	2 X 4 X 20 3/8" DOUBLER	O 20060000000	2	JBD
	Frontwall Top Plate "A"	2x4x89-1/4" Top Plate	O 89040000000	1	GBD
	Frontwall Top Plate "B"	2x4x23-3/4"	O 23120000000	1	GSB
	Frontwall Bottom Plate	2 X 4 X 24-1/2"	O 24080000000	2	KHA
	Wall Stud	2 X 4 X 68" STUD	O 68000000000	22	UM
2 X 4 TREATED FLOOR FRAME	Floor Joist	2 X 4 X 89-5/8" TREATED	P 89100000000	9	---
	Bond Board "A"	LUM TRTD 2 X 4 X 96 #2&BTR	P 96000000000	1	---
	Bond Board "B"	2 X 4 X 24 #2&BTR	P 24000000000	1	---
	Bond Board "C"	LUM TRTD 2 X 4 X 72 #2&BTR	P 72000000000	1	---
	Bond Board "D"	LUM TRTD 2 X 4 X 48 #2&BTR	P 48000000000	1	---
1 X 3 PINE	Over Door Nailer	LUM SPF 1X3 X72" SQ EDGE PET	U 72000000000	1	HJ
	Gauge Block	1 X 3 X 5" PINE FILLER	U 05000000000	1	GAA
5/8 OSB	Floor Panel "A"	OSB 5/8" X 4' X 8'	11117	1	---
	Floor Panel "B"	5/8" OSB 44 5/8" X 96"	E 96004410000	1	---
	Floor Panel "C"	5/8" OSB 23 7/8" X 92 5/8"	E 92102314000	1	---
NO GROOVE SIDING	Front Wall Panel "A"	3/8" NG 15 7/8" X 72"	K 7200151400B	2	---
	Front Wall "B"	3/8" NG 11 7/8" X 72"	K 72001114000	2	---
	Back Wall Panel "B"	3/8"NG 23 7/8" X72" PANEL OR	K 72002314000	1	---
	Gable Filler Panel	3/8"NG 6 3/4" X 25 7/16" GABLE	K 25070612000	2	---
	Front Center Gable Panel	3/8" NG 23 7/8" X 31 1/2" FRON	K 31082314000	1	---
	Back Center Gable Panel	3/8" NG 23 7/8" X 33" BACK	K 3300231400B	1	---
	Front Wing Gable Panels	3/8" NG 25-3/4" X 48" RGT FRT	K 48002512100	1	---
	Front Wing Gable Panels	3/8" NG 25-3/4" X 48" LFT FRT	K 48002512200	1	---
	Back Wing Gable Panels	3/8" NG 27 1/4" X 48" RGT BCK	K 48002704100	1	---
	Back Wing Gable Panels	3/8" NG 27 1/4" X 48" LFT BCK	K 48002704200	1	---
	Front / Back Corner Trim	3/8" NG 1 3/4" X 70 1/2"	K 70080112000	6	---
	Side Corner Trim / Batten	3/8" NG 1 3/4" X 69"	K 69000112000	10	---
	Back Wall Panel "A"	SIDING NGSE 3/8X4'X6"	11509	2	---
	Side Wall Panel "A"	3/8" NG 46 1/8"x 72" PANEL	K 72004602000	4	---
	Eave Fascia "A"	3/8" NG 2-5/8" X 72"	K 72000210000	2	---
	Eave Fascia "B"	3/8" NG 2-5/8" X 25-1/8"	K 25020210000	2	---
19/32 X 3 SMART TRIM	Horizontal Door Rails	19/32 TST 2 1/2" X 26 5/8"	UT26100208000	4	AH
	Door Trim Hinge \ Over Door Trim	19/32 TST 2 1/2" X 72" TRIM	UT72000208000	1	ZJ
19/32 X 4 SMART TRIM	Right Gable Trim	19/32 TST 3 1/2" X 71-7/8" 28"B/E	UT71142828100	2	JGR
	Left Gable Trim	19/32 TST 3 1/2" X 71-7/8" 28"B/E	UT71142828200	2	JGL
PURCHASED COMPONENTS	Door Stiffener	LSL 1-1/4 X 2-1/4 X 69 PET	12715	2	OO
	Wall Vents	VENT 16" X 8" EXTERIOR (WHITE)	15002	2	---
	T & D Handle	HANDLE - T & "D" HANDLES, FAUX	15220	1	---
	Transom Window	WINDOW 9 X 27 TRANSOM (SINGLE)	15235	2	---
	Metal Roof Panels	METAL ROOF MS (GALVALUME) CORR 71-1/2"	15016	10	---
	Metal Rake	1" x 3" x 95-1/2" RAKE FASCIA - 29 GA. GALVALUME	15380	4	---
	Metal Ridge Cap	4" x 4" x 54" RIDGE CAP - 29 GA. GALVALUME	15394	2	---
	Foam Enclosures	FOAM ENCLOSURE - METAL ROOF	15195	20	---
	Hardware Kit	H/K TSC HOMESTEAD 10x8 GABLE	15503	1	---
PACKAGING	Instructions		16553	1	---
Right Door Assembly	30177-R				
	Door Panel	3/8" NG x 31-3/8" x 71-1/2" DO	K 71083106072	1	---
	Right Hinge Assembly	HINGE RIGHT (RED) 19/32x3 THIN TRIM	30121-TT	1	---
	Vertical Door Stiles	19/32 TST 2 1/2" X 71 5/8"	UT71100208000	1	GY
Left Door Assembly	Horizontal Door Rails	19/32 TST 2 1/2" X 26 5/8"	UT26100208000	2	AH
	30177-L				
	Door Panel	3/8" NG x 31-3/8" x 71-1/2" DO	K 71083106072	1	---
	Left Hinge Assembly	HINGE LEFT (GREEN) 19/32x3 THIN TRIM	30131-TT	1	---
	Vertical Door Stiles	19/32 TST 2 1/2" X 71 5/8"	UT71100208000	1	GY
	Horizontal Door Rails	19/32 TST 2 1/2" X 26 5/8"	UT26100208000	2	AH

LIMITED CONDITIONAL WARRANTY*

Backyard Storage Solutions, LLC warrants the following:

1. Every product is warranted from defects in workmanship and manufacturing for 1 year.
2. All accessories, hardware and metal components are warranted for 2 years.
3. All Oriented Strand Board (OSB) is warranted for 2 years
4. Siding and Trim is warranted for 15 years.
5. LP Prostruct® Flooring is warranted for 10 years
6. Cedar lumber is warranted for 15 years.
7. Preserved Pine is warranted for 10 years.
8. Redwood is warranted for 10 years.
9. Metal Roof is warranted for 25 years.

Backyard Storage Solutions, LLC will repair, replace or pay for the affected part. In no event shall Backyard Storage Solutions, LLC pay the cost of labor or installation or any other costs related thereto. All warranties are from date of purchase. If a cash refund is paid on an affected part, it will be prorated from the date of purchase.

CONDITIONS

The warranty is effective only when:

1. The unit has been erected in accordance with the assembly instructions.
2. The unit has been properly shingled and painted or stained and reasonably and regularly maintained thereafter.
3. The failure occurs when the unit is owned by the original purchaser.
4. Backyard Storage Solutions, LLC has received the warranty registration card within thirty (30) days of purchase and notification of the failure in writing within the warranty period specified above.
5. Backyard Storage Solutions, LLC has had reasonable opportunity during the sixty (60) days following receipt of notification to inspect and verify the failure prior to commencement of any repair work.

REQUIREMENTS

Storage Buildings

To validate your warranty, it is necessary to properly maintain your Backyard Storage Solutions, LLC unit; shingle the roof and paint or solid-colored stain the siding using quality, 100% acrylic latex exterior product with a minimum of two (2) coats within thirty (30) days of assembly; caulk above all doors and all horizontal and vertical trim boards; paint and seal all exposed edges, sides and faces of siding/trim and OSB siding to include all exterior walls and all sides and all edges of doors.

Gazebos & Pergolas

To validate your warranty, it is necessary to properly maintain your Backyard Storage Solutions, LLC unit. This includes treating all of the exposed cedar and pine surfaces on your gazebo or pergola structure with an exterior grade wood preservative, an exterior oil-based semi-transparent stain, an acrylic latex exterior paint or an acrylic latex solid color exterior stain within 30 days of assembly and as needed thereafter to maintain your warranty.

Keep vegetation trimmed away from building and make sure siding panels and trim do not come in contact with masonry or cement. The minimum ground clearance for siding must be one half inch ($\frac{1}{2}$ inch) from concrete slab or two and one half inches ($2\frac{1}{2}$ ") from the ground when building is erected or constructed on a treated wood floor kit. Water from sprinklers must be kept off unit. In no event will Backyard Storage Solutions, LLC be responsible for any indirect, incidental, consequential or special damages nor for failure(s) that are caused by events, acts or omissions beyond our control including, but not limited to, misuse or improper assembly, improper maintenance (which eventually leads to rot or decay) and acts of God. Backyard Storage Solutions, LLC will not be held responsible for any labor costs incurred to construct your unit.

This warranty gives you certain specific rights that vary from state to state.

CLAIM PROCEDURE

To make a claim under this warranty, you can either call 1-888-827-9056 or email: customerservice@backyardproducts.com.

Please have ready the information below when you call or include the information in your email:

1. The model and size of the product.
2. A list of the part(s) for which the claim is made.
3. Proof of purchase of the Backyard Storage Solutions, LLC item, as shown on the original invoice or receipt.
4. Run code: found on exterior product label or assembly instructions enclosed in the product package.

All other inquiries can be mailed to:

Backyard Storage Solutions, LLC
Attn: Customer Service
1000 Ternes
Monroe, MI 48162

***WARRANTY TERMS MAY VARY OUTSIDE THE U.S.A.**

IMPORTANT: This is your warranty certificate.

15Y PSS BB GEN LDR: 3/20/2019