




DK2 USA WEST
4301 S Valley View Blvd,
Suite 10-11 , Las Vegas,
Nevada, 89103, United States

DK2 CANADA
1080 Clay Avenue,
Unit 2, Burlington, Ontario,
L7L 0A1 , Canada

DK2 USA EAST
3750 South Avenue,
North Unit, Toledo, Ohio
43615, United States



ABOUT US

DK2 is a leading manufacturer of power products and automotive accessory items. Our line has expanded into 5 categories of products; Snow Plows, Trailers, Winches, Auto Accessories, and Power Products.

We believe in providing quality first and are focused on delivering our products to our customers on time and in accordance with their ever changing needs.

We believe that our business can – and should – have a positive impact on the communities we serve.

With Distribution Centres in both Canada and the US, we service a wide range of wholesale and retail channels by maintaining our commitment of providing products that are designed and created with high ethical standards.

LIMITED 1 YEAR WARRANTY

WHAT IS COVERED

DK2 Inc. warrants to the original purchaser of any DK2 product that it will be free and clear of manufacturing defects in workmanship and materials under normal use and service for a period of one (1) year from the date of the original purchase.

If within one (1) year from the original date of purchase this product fails due to defect in material or workmanship, Detail K2 will repair, replace, or supply any defective part at our option. Upon expiry of one (1) year, Detail K2 will have no further liability related to the product. Detail K2 does not authorize any party, including its authorized distributors or dealers, to offer any other warranty on behalf of Detail K2 Inc.

THIS WARRANTY DOES NOT COVER OR APPLY TO:

- (a) Damage to the product due to misuse, mishandling and abuse
- (b) Improper installation, maintenance and storage
- (c) Expendable parts such as nuts and bolts, pins and springs
- (d) Normal wear and tear
- (e) Consequential damage & incidental damages such as damage to persons or property

PROCEDURE FOR OBTAINING A RETURN AUTHORIZATION

Within the one (1) year warranty period, the purchaser of the product must notify an authorized distributor or dealer of the claimed defect and provide proof of original purchase. At this time the validity of the claim will be determined and a Return Goods Authorization Number (RGA) will be issued if approved. No returned product will be accepted under warranty unless accompanied by an RGA# issued by Detail K2 Inc.

RESOLUTION FOR A DEFECTIVE PRODUCT

Detail K2 Inc. will at its option repair or replace the defective product covered by this warranty. The repaired product will be shipped to the purchaser upon completion. All transportation charges shall be the responsibility of the purchaser. Any damage in transit will be the responsibility of the carrier or at the risk of the purchaser.



**DK2 TRAILERS**

Utility Trailers
Landscape Trailers

PAGES: 4-10**DK2 POWER**

Stump Grinders
Wood Chippers
Log Splitters
Trenchers

PAGES: 11-23**DK2 SNOW PLOWS**

Snow Plows - Hydraulic
Snow Plows - Universal Mount
Snow Plows - Custom Mount

PAGES: 24-29**DK2 AUTO ACCESSORIES**

Bike Carriers
Cargo Carriers
Truck Rack
Motorcycle Carrier
Battery Boosters

PAGES: 30-38**DK2 WARRIOR WINCHES**

Winches - Electric
Winches - Hydraulic
Winch Accessories

PAGES: 39-53



5ⁱⁿ UTILITY TRAILER 5X7

Item Number: MMT5X7
UPC: 826518003391

DESCRIPTION



The single axle multi-utility trailer from DK2 is one of the most versatile trailer on the market. Sitting on a solid square tube cambered axle with 30.5 cm (12 in.) 6 ply bias tires, and a load capacity of 1,639 lb (743.4kg). When the front and back load-bearing gates are down, the trailer bed extends to nearly 3.5 m (11.58 ft.). Another great feature is the tilt/dump capability that makes it easy to load or unload heavy items. Fabricated from 100% steel, all of the components are reinforced, adjustable, removable and / or interchangeable.

SPECIFICATION

GVW:	2,090 lb. 948.0 kg
Curb weight	451 lb. 204.6 kg
Payload capacity	1,639 lb. 743.4 kg
Bed dimensions	52 x 88 to 52 x 136 inches 1.32 x 2.24 to 1.32 x 3.45 m
Overall length	177 in. 4.50m tongue extended
Floor height	20 in. 50.8 cm
Construction	Fully welded tubular steel frame (hot dipped galvanized available)
Side panels	14 in. H 35.6 cm H Corrugated steel
Drop gates	24 in. H 61 cm H Corrugated
Lighting	Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers.
Dump bed	2 position
Hitch height	16 in. 40.6 cm
Flooring	100% steel corrugated welded reinforced bed
Assembly time	60 minutes approx.
Carton dimensions	88.5 x 55 x 8 inches (DWH) 224.79 x 139.7 x 20.32cm

FEATURES

- Back drop gate
- 100% Steel
- Heavy duty
- Best in Class
- Exclusive Design
- Extended bed length: nearly 12 feet / 3.66 metres.
- 2 position dump bed
- Quick release lock pin
- Load bearing gates
- Removable steel side panels
- Corrugated steel floor
- 100% welded tubular steel frame
- Heavy-duty tail light protectors
- Solid square tube cambered axle
- Easy-lube 5 on 4.5 hub assembly
- V tongue for added strength
- 2" coupler with safety chains
- 12 x 5.3 - 6 ply bias tires





5ⁱⁿ UTILITY TRAILER 5X7

Item Number: MMT5X7G

UPC: 826518004848

DESCRIPTION

The new addition to the DK2 trailer line up is the Hot Dipped Galvanized 5 x 7 Utility Trailer. Constructed from 100% steel all the components are reinforced, adjustable, removable or interchangeable. The MMT5X7G is fully welded and hot dipped galvanized to protect the steel from the elements especially in coastal regions. This unit offers the end user excellent value for their money and will dramatically add to the life of the trailer kit. Each trailer ships in a single carton including pre wired LED lighting for easy installation.



SPECIFICATION

GVW:	2,090 lb. 948.0 kg
Curb weight	451 lb. 204.6 kg
Payload capacity	1,639 lb. 743.4 kg
Bed dimensions	52 x 88 to 52 x 136 inches 1.32 x 2.24 to 1.32 x 3.45 m
Overall length	177 in. 4.50m tongue extended
Floor height	20 in. 50.8 cm
Construction	Fully welded hot dipped galvanized tubular steel frame
Side panels	14 in. H 35.6 cm H Corrugated steel
Drop gates	24 in. H 61 cm H Corrugated
Lighting	Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers
Dump bed	2 position
Hitch height	16 in. 40.6 cm
Flooring	100% steel corrugated reinforced bed
Assembly time	60 minutes approx.
Carton dimensions	88.5 x 55 x 8 inches (DWH) 224.79 x 139.7 x 20.32cm (DWH)

FEATURES

- Back drop gate
- 100% Steel
- Heavy duty
- Best in Class
- Extended bed length: nearly 12' / 3.66 metres.
- 2 position dump bed
- Quick release lock pin
- Load bearing gates
- Removable steel side panels
- Corrugated steel floor
- 100% welded tubular steel frame
- Heavy-duty tail light protectors
- Solid square tube cambered axle
- Easy-lube 5 on 4.5 hub assembly
- V tongue for added strength
- 2" coupler with safety chains
- 12 x 5.3 - 6 ply bias tires

5





DK2 LANDSCAPE TRAILER 4 X 6

Item Number: MMT4X60
UPC: 826518005623

DESCRIPTION

The “little brother” of the best-selling DK2 MMT5X7 is specially designed for handling a variety of hauling tasks. This trailer is the perfect solution for anyone needing to pull a trailer behind a small vehicle, full size truck, law tractor, or ATV.


The trailers are engineered to provide exceptional balance and ease of mobility without giving up one ounce of payload capacity. Every trailer is made from 100% welded tubular steel with expanded steel decks. Our back gate design is multi-purpose and can sit flat in the bed, up in a vertical position, or lying down as a ramp for easy loading.

SPECIFICATION

GVW:	1,600 lb. 725.7 kg
Curb weight	305 lb. 138.3 kg
Payload capacity	1,295 lb. 587.4 kg
Bed dimensions	48 x 72 inches (1.21 x 1.82 m)
Overall length	152 in. 3.86m tongue extended
Floor height	18 in. 45.7 cm
Construction	Fully welded HD tubular steel
Side panels	Open Sides
Floating Ramp Gate	36 in. Reinforced square tube steel ramp with heavy duty round tube exterior
Lighting	Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers.
Hitch height	14 in. 35.5 cm
Flooring	100% welded down corrugated steel floor panel

FEATURES

- Capacity: 587.4 kg (1,295 lb.)
- Fully welded heavy-duty powder-coated steel frame
- Corrugated steel floor
- Solid square tube cambered axle
- Drive up rear ramp tailgate
- 2 position dump bed axle mount with quick release lock pin
- Hitch height: 40.6 cm (16 in.)
- Heavy-duty tail light protectors
- LED quick connect lighting with side markers
- Wheel diameter: 12"
- Wheel bolt pattern: 5 on 4-1/2"
- Tire size: 4.80-12
- Load range: C
- Assembly required
- 2" coupler





DK2 LANDSCAPE TRAILER 4 X 6

Item Number: MMT4X6
UPC: 826518004831

DESCRIPTION

The “little brother” of the best-selling DK2 MMT5X7 is specially designed for handling a variety of hauling tasks. This trailer is the perfect solution for anyone needing to pull a trailer behind a small vehicle, full size truck, law tractor, or ATV.


The trailers are engineered to provide exceptional balance and ease of mobility without giving up one ounce of payload capacity. Every trailer is made from 100% welded tubular steel with expanded steel decks. Our back gate design is multi-purpose and can sit flat in the bed, up in a vertical position, or lying down as a ramp for easy loading.

SPECIFICATION

GVW:	1,600 lb. 725.7 kg
Curb weight	305 lb. 138.3 kg
Payload capacity	1,295 lb. 587.4 kg
Bed dimensions	48 x 72 inches (1.21 x 1.82 m)
Overall length	152 in. 3.86m tongue extended
Floor height	18 in. 45.7 cm
Construction	Fully welded HD tubular steel
Side panels	Solid Sides
Floating Ramp Gate	36 in. Reinforced square tube steel ramp with heavy duty round tube exterior
Lighting	Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers.
Hitch height	14 in. 35.5 cm
Flooring	100% welded down corrugated steel floor panel

FEATURES

- Capacity: 587.4 kg (1,295 lb.)
- Fully welded heavy-duty powder-coated steel frame
- Corrugated steel floor & solid side and front panels/rails
- Solid square tube cambered axle
- Drive up rear ramp tailgate
- 2 position dump bed axle mount with quick release lock pin
- Hitch height: 40.6 cm (16 in.)
- Heavy-duty tail light protectors
- LED quick connect lighting with side markers
- Wheel diameter: 12"
- Wheel bolt pattern: 5 on 4-1/2"
- Tire size: 4.80-12
- Load range: C
- Assembly required
- 2" coupler





DK2 FOLDING TRAILER 4 X 8

Item Number: MFT4X8
UPC: 826518005296

DESCRIPTION

The trailer you've always needed has arrived with the DK2 MFT 4x8 Folding Trailer Kit.

High-performing, durable and versatile, the DK2 MFT4x8 trailer is ready for work. Built with a patented welded steel frame and deck for added strength and easy assembly, you'll spend less time reading manuals and more time on the road. For increased safety and secure storage, the DK2 MFT is coated with high-performance anti-slip textured UV powder, all while maintaining its complete folding functionality. When it comes to trailers - there's truly nothing like it.

SPECIFICATION

GVW:	1720 lb 780.1 kg
Nett weight	262 lb 118.8 kg
Payload capacity	1450 lb 657.7 kg
Bed dimensions	48 x 96 inches 1.2 x 2.4 m
Coupler	2 inch 5cm
Wheel Rim	12 x 4 inches 30.4 x 10 cm
Tire Size & Type	5.30-12 6PR 1050lbs
Tire Air Pressure	80 PSI cold
Wheel Lug	5 per rim
Torque	85-90 ft/lbs
Axle	Square Cambered
Hub	Cast Iron Dia 5.6 inch 14.2 cm
Overall Dimension	138 x 64 x 24.5 inches 3.5 x 1.6 x 0.6 m
Lighting	Pre Wired LED
Material	UV powder coated steel



Folds up for
easy storage.

FEATURES

- Overall assembled length is 138 inch and overall width is 64 inch.
- Payload capacity is 1450 lbs. with a 1720-lb. max. GVWR
- Includes two 5.3 -12 inch tires, pre wired led light kit with flat 4-wire harness and connector, safety chain with S-hook, and 2 inch coupler.
- Certificate of origin for registering and licensing is included.



**Ships in a single
carton.**



**Ships in a Stack
on 10.**



DK2 LANDSCAPE TRAILER 5X7

Item Number: MMT5X7-DUG
UPC: 826518005296

DESCRIPTION



The single axle multi-utility trailer from DK2 is one of the most versatile trailer on the market. Sitting on a solid square tube cambered axle with 30.5 cm (12 in.) 6 ply bias tires, and a load capacity of 1,639 lb (743.4kg). When the front and back load-bearing gates are down, the trailer bed extends to nearly 3.5 m (11.58 ft.). Another great feature is the tilt/dump capability that makes it easy to load or unload heavy items. Fabricated from 100% steel, all of the components are reinforced, adjustable, removable and / or interchangeable.

SPECIFICATION

GVW:	2,090 lb. 948.0 kg
Curb weight	451 lb. 204.6 kg
Payload capacity	1,639 lb. 743.4 kg
Bed dimensions	52 x 88 to 52 x 136 inches 1.32 x 2.24 to 1.32 x 3.45 m
Overall length	177 in. 4.50m tongue extended
Floor height	20 in. 50.8 cm
Construction	Fully welded tubular steel frame (hot dipped galvanized available)
Side panels	14 in. H 35.6 cm H Corrugated steel
Drop gates	24 in. H 61 cm H Corrugated
Lighting	Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers.
Dump bed	2 position
Hitch height	16 in. 40.6 cm
Flooring	100% steel corrugated welded reinforced bed
Assembly time	60 minutes approx.
Carton dimensions	88.5 x 55 x 8 inches (DWH) 224.79 x 139.7 x 20.32cm

FEATURES

- Back drop gate
- 100% Steel
- Heavy duty
- Best in Class
- Exclusive Design
- Extended bed length: nearly 12 feet / 3.66 metres.
- 2 position dump bed
- Quick release lock pin
- Load bearing gates
- Removable steel side panels
- Corrugated steel floor
- 100% welded tubular steel frame
- Heavy-duty tail light protectors
- Solid square tube cambered axle
- Easy-lube 5 on 4.5 hub assembly
- V tongue for added strength
- 2" coupler with safety chains
- 12 x 5.3 - 6 ply bias tires





DK2 LANDSCAPE TRAILER 5X7

Item Number: MMT5X7G-DUG
UPC: 826518005302

DESCRIPTION



The new addition to the DK2 trailer line up is the Hot Dipped Galvanized 5 x 7 Utility Trailer. Constructed from 100% steel all the components are reinforced, adjustable, removable or interchangeable. The MMT5X7G is fully welded and hot dipped galvanized to protect the steel from the elements especially in coastal regions. This unit offers the end user excellent value for their money and will dramatically add to the life of the trailer kit. Each trailer ships in a single carton including pre wired LED lighting for easy installation.

SPECIFICATION

GVW:	2,090 lb. 948.0 kg
Curb weight	451 lb. 204.6 kg
Payload capacity	1,639 lb. 743.4 kg
Bed dimensions	52 x 88 to 52 x 136 inches 1.32 x 2.24 to 1.32 x 3.45 m
Overall length	177 in. 4.50m tongue extended
Floor height	20 in. 50.8 cm
Construction	Fully welded hot dipped galvanized tubular steel frame
Side panels	14 in. H 35.6 cm H Corrugated steel
Drop gates	24 in. H 61 cm H Corrugated
Lighting	Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers
Dump bed	2 position
Hitch height	16 in. 40.6 cm
Flooring	100% steel corrugated reinforced bed
Assembly time	60 minutes approx.
Carton dimensions	88.5 x 55 x 8 inches (DWH) 224.79 x 139.7 x 20.32cm (DWH)

FEATURES

- Back drop gate
- 100% Steel
- Heavy duty
- Best in Class
- Extended bed length: nearly 12' / 3.66 metres.
- 2 position dump bed
- Quick release lock pin
- Load bearing gates
- Removable steel side panels
- Corrugated steel floor
- 100% welded tubular steel frame
- Heavy-duty tail light protectors
- Solid square tube cambered axle
- Easy-lube 5 on 4.5 hub assembly
- V tongue for added strength
- 2" coupler with safety chains
- 12 x 5.3 - 6 ply bias tires





12" COMMERCIAL GRADE STUMP GRINDER

Item Number: OPG777

UPC: 826518005524

DESCRIPTION

Powered by 14HP KOHLER® Command PRO commercial engine. Mounted on a Heavy Duty welded 2x2 Steel, solid frame structurally engineered for endurance performance. Extreme duty 2x2 axle with dual locking hitch pins for trouble free wheel brakes and transport over rough terrain. Direct Power Drive delivers 3600RPM and 22.7 Gross Torque FT lb to a 12 inch solid steel cutting wheel mounted on premium pillar bearings.

Demolishes stumps with 9 Carbide teeth cutting 3 ½ inches wide per cut. Cuts any diameter stump 12" high and 9 in below ground. Designed and manufactured for Strength, Durability and Performance. Features Key shut-off, locking throttle, drop stand, solid bar lift handles.

Free towbar included.

SPECIFICATION

Engine Model	KOHLER CH440
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	14 HP
Rated Speed(RPM)	3600
Tires	ATV Locking Heavy Duty Axles
Wheelbase	32"
Stump Dia/Height Max	Any Diameter 12 Inches High
Cutting Blades	9 Dual Carbide Cast Mounted Cutters
Cutting Width	3 ½" Cutting Path
Gearbox	Direct Drive Dual Belts
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	91 x 32 x 52"
Weight	234 lb
Shipping Crate Dims	42 x 23 x 25" - 275lb
Container Qty	158



ATV Tires DUAL Locking - Off Road only



9 Carbide Cutting Head - Direct Drive



Adjustable Bow Handle With Heavy Duty Frame Mounting



Removable Tow Bar



DESCRIPTION

14" 12 cutter commercial performance Stump Grinder.

14 HP electric start KOHLER CH440 Command PRO engine. Performs 4" wide cuts with 12 carbide high speed direct drive teeth. Heavy duty under carriage, ATV wheels. Removable flipbar for towing or easy trolley to and from the work site. New Operator controlled Posi-lok Wheel Brake for pivot grinding. Comfort bow handle with CE safety approved hands off shut down. Demolishes any diameter stump up to 14" above and 10" below ground.

KOHLER 3 yr commercial warranty. 12v battery included.

SPECIFICATION

Engine Model	KOHLER CH440
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	14 HP
Rated Speed(RPM)	3600
Tires	ATV
Stump Dia/Height Max	Any Diameter 14" High
Cutting Blades	12 Carbide Cutters
Cutting Width	4" Cutting Path
Cutting Wheel	Direct Drive
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	102 x 48 x 59"
Weight	285 lb
Shipping Crate Dims	41 x 31 x 23" - 308 lb



14" STUMP GRINDER

Item Number: OPG888E
UPC: 827518006719



12 High speed Machined Carbide Cutters.



Dual direct V-Belt, high speed 3600 rpm drive.



Large multi position adjustable Bow Handle. CE approved safety shut off.



ATV wheels on HD axle. Tire 13.75D x 5.25W 145/70-6.



DKA POWER
KOHLER Engines



ATV TOWABLE 3" CHIPPER SHREDDER

Item Number: OPC503
UPC: 826518005487

DESCRIPTION

ATV towable 3 inch 4000RPM Direct Drive combo chipper shredder. The dual blade, centrifugal force deteriorates trees, branches, leaves, and garden composting.

Additional premium features include extra large feed chutes, drop stand and handy removable tow bar, locking wheels, removable key shutoff, 4 Stage CYCLONIC Filter System, a 7HP KOHLER CH270 Command PRO Engine and a 3YR Commercial warranty .

SPECIFICATION

Engine Model	KOHLER CH270
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	7HP
Rated Speed(RPM)	4000
Tires	ATV Locking
Wheelbase	28"
Tree Diameter	3"
Cutting Blades	Dual Carbide
Chipper Shredder	Leaves Brush Garden Compost
Gearbox	Direct Drive
Expulsion Chute	Adjustable
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	63 x 32 x 43"
Weight	170 lb
Shipping Crate Dims	33 x 29 x 44" 198 lb
Container Qty	84




ATV Tires-locking - Off Road only



1 7/8" Removable Tow Bar



Large Feed Chute



Lock Out Safety Keys

13



3" 3-IN-1 CHIPPER SHREDDER WITH VACUUM HOSE & ATV TIRES

Item Number: OPC503V
UPC: 827518006979

DESCRIPTION

ATV towable 3" 4000 rpm 3-IN-1 Chipper Shredder with Vacuum Hose.

Double edge cutting blades with direct shaft drive centrifugal force deteriorates trees, branches, leaves, and garden composting. Extra-large feed chutes, drop stand and handy removable tow bar for compact storage, locking wheels. Removable Key lock shutoff.

Off road ATV tires. 7 HP KOHLER Command PRO engine 3 year commercial warranty.

SPECIFICATION

Engine Model	KOHLER CH270
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	7 HP
Rated Speed(RPM)	4000
Tires	Locking
Tree Diameter	3"
Cutting Blades	Dual
Chipper Shredder	Quad
Expulsion Chute	Adjustable
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	63 x 32 x 43" (L x W x H)
Weight	200 lb
Shipping Crate Dims	32 x 29 x 43" - 225 lb



Removable tow bar with trolley wheel for compact storage and easy transport.



4 hammer Shredder.



Top loading for compost, garden waste, leaves and yard clean up.



6" Leaf Vacuum with ergonomic handle.



5" AUTO FEED CHIPPER SHREDDER

Item Number: OPC505A
UPC: 826518005739

DESCRIPTION

5" chipper self contained auto feed system with hydraulic roller speeds up to 600 rpm.

Self adjusting feed chamber, large feed chute, adjustable chip chute. ATV tires with included tow bar. Advanced centrifugal clutch.

DK2 POWER manufactures performance equipment, driven by Kohler, CH440 14 HP 3 yr commercial warranty.

SPECIFICATION

Engine Model	KOHLER CH440
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	14 HP
Rated Speed(RPM)	3600
Tires	ATV Locking
Tree Diameter	5"
Cutting Blades	Auto Feed
Expulsion Chute	Steel Adjustable
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	91 x 40 x 61"
Weight	638 lb
Shipping Crate Dims	63 x 35 x 49" - 727 lb
Container Qty	28



ATV Tires



1 7/8 inch removable tow bar.



Adjustable feed speed controls.



Kohler 14 HP CH440 Engine - 3 Year Warranty



CYCLONIC CUTTERS



DESCRIPTION

3600 RPM CYCLONIC Chipper Shredder. Direct Drive, Dual Swing Chutes for quick drum access.

6 inch chipping capacity, reversible dual edge high speed cutting blades. Auto Adjusting CYCLONIC drum chamber deteriorates trees and brush up to 6.25 inches in diameter all from one feed chute. Large quick open hoppers, 59" truck bed height chip chute with adjustable cast iron rotating hood, easy drop stand, removable tow bar, 2 inch hitch.

Premium built-in tool box, Key shutoff with lock out safety switch. Extended 48 inch safety stability axle with DOT tires. Safety kit includes, tools, glasses, ear protection and gloves. Integrated chute handles, powder coated for durability.

SPECIFICATION

Engine Model	KOHLER CH440
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	14 HP
Rated Speed(RPM)	3600
Tires	D.O.T. 45 MPH
Wheelbase	47"
Tree Diameter	6"
Cutting Blades	Dual Reversible Double Edge
Chipper Shredder	Auto Adjusting 6" To 1/8" Materials
Gearbox	Dual Direct Drive
Expulsion Chute	Cast Iron Adjustable 180°
	59" Pickup Bed Height
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	102 x 47 x 59"
Weight	375 lb
Shipping Crate Dims	44 x 25 x 44" - 452 lb
Container Qty	72



6" CYCLONIC DIRECT DRIVE CHIPPER SHREDDER

Item Number: OPC506
UPC: 826518005517




25MPH D.O.T. Tires



2 inch removable tow bar - D.O.T. Road Legal



Extended Axle / Dual Swing Chutes / Tool Box



Lock Out Safety Keys



6" CHIPPER SHREDDER

Item Number: OPC566E
UPC: 827518006757

DESCRIPTION

6" kinetic cyclonic chipper, electric start 3600 rpm 14 HP CH440 KOHLER Commercial Command PRO engine.

Dual edge reversible 12" cutting blades auto adjust to pulverize brush up to 6.25" diameter trees. Tool Free Dual Swing Chutes quickly open for easy drum access. D.O.T. road legal tires. 48" extended axle for uneven ground and towing stability. Front articulated ground wheels for easy equipment moving. 2" ball tow bar. Rotational chip chute pickup truck height for bed loading.

3 year KOHLER warranty.

DK2 Power manufactures commercial performance equipment.

SPECIFICATION

Engine Model	KOHLER CH440
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	14 HP
Rated Speed(RPM)	3600
Tires	D.O.T.
Tree Diameter	6.25"
Cutting Blades	12" Reversible
Expulsion Chute	Pickup Height
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	102 x 47 x 59" (L x W x H)
Weight	594 lb
Shipping Crate Dims	44 x 30 x 41" - 638 lb



Front articulated ground wheels for easy equipment moving.



Rotational chip chute pickup truck bed height.



DOT tires size 16.5D X 6.5W.



Dual tool free swing open chutes for fast drum access.



40 TON KINETIC 1 SEC LOG SPLITTER

Item Number: OPS240
UPC: 826518005746

DESCRIPTION

40 Ton Kinetic Ultimate speed 1 sec Commercial Grade Log Splitter.

KOHLER Command PRO 4000 RPM CH270 3YR warranty engine. Oversized reinforced steel work table, safety lockout, Clam shell quick access body. Extended stability axle with ATV tires. 2 IN ball hitch, 22 inch long logs.

This machine gets it done, quality manufactured for top performance. Auto retraction bearing guided ram. This powerful splitter performs during 40 ton force cycles.

SPECIFICATION

Engine Model	KOHLER CH270
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	7HP
Rated Speed(RPM)	4000
Tires	ATV Tires
Max Log Length	22"
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	120 x 37 x 44"
Weight	573 lb
Shipping Crate Dims	71 x 27 x 23" - 607 lb
Container Qty	68
Tow Bar	2" Ball
Log Rails	Slide Reload
Wedge	8" Expansive
Cycle Time	1 Second
Ram Speed	½ Second Deployment




8" Expansive solid steel wedge



Oversize steel work table



ATV Tires



2 inch ball hitch



1100LB ELECTRIC DUMP CART

Item Number: OPD811
UPC: 826518005722

DESCRIPTION

All terrain BIG DUMP moves 1100 LBS with self drive electric power. Run your Big Dump 6 to hours on one charge.

Hydraulic electric lift cylinder tip bucket to 90 degrees vertical to clean your load. Throttle bar speed control with articulated floating rear wheels keep your load level and steady.

At 6 MPH quickly move about your job site. Dual front wheel drive climbs over rough terrain with ease.

SPECIFICATION

Max Capacity	1100 lb
Max Speed	6 mph
Charge Time	5 hours
Run Time	6 hours
Wheels	All terrain
Warranty	1YR Chassis
Assembled Dimensions	85 x 46 x 42"
Weight	320 lb
Shipping Crate Dims	54 x 32 x 35" 508 lb
Container Qty	69



1100lb Max Capacity



All terrain tires



Max speed 6 mph



Vertical dump 90 degrees



DKA POWER
KOHLER Engines



18" COMMERCIAL TRENCHER

Item Number: OPT118
UPC: 826518005586

DESCRIPTION

Direct Chain Drive Trencher. High pressure sintered carbide teeth. 5 depth positions, dual locking wheels for digging in reverse. 3/8" plow plates with quick change teeth. Adjustable handle, Keyed safety lock out, 6 inch direct drive auger. Heavy gauge steel construction.

4000 RPM direct drive, 400 RPM tri-cut teeth chain drive.
200FT per hour dig rate.

SPECIFICATION

Engine Model	KOHLER CH270
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	7HP 208CC 10.5 FT lb torque @ 4000RPM
Rated Speed(RPM)	4000
Chain Speed	1800 FT Per Minute
Chain Dimension	63"
Trench	4" x 18"
Cutting Teeth	21 Carbide Alloy High Pressure Teeth. 400 RPM
Wheels	Dual Auto Lock In Reverse Dig
Gearbox	Dual Belt Chain Drive Auger
Auger	Side Offload Direct Drive
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	71 x 36 x 48"
Weight	320 lb
Shipping Crate Dims	41 x 30 x 34" 374 lb
Container Qty	99




Tri-Cut High Carbide Teeth



Trolley Wheel



Lock out safety keys - Locking Throttle



Auger guard



DKA POWER
KOHLER Engines



24" COMMERCIAL TRENCHER

Item Number: OPT124
UPC: 826518005463

DESCRIPTION

Direct Chain Drive Trencher. High pressure sintered carbide teeth. 5 depth positions, dual locking wheels for digging in reverse. 3/8" plow plates with quick change teeth. Adjustable handle, Keyed safety lock out, 6 inch direct drive auger. Heavy gauge steel construction.

3600 RPM direct drive, 400 RPM tri-cut teeth chain drive. 200FT per hour dig rate.

SPECIFICATION

Engine Model	KOHLER CH440
Engine	Command PRO Commercial
Rated Power[Kw(HP)]	14HP 429CC 22.7 FT lb torque @ 3600RPM
Rated Speed(RPM)	3600
Chain Speed	1800 FT Per Minute
Chain Dimension	79"
Trench	4" x 24"
Cutting Teeth	27 Carbide Alloy High Pressure Teeth. 400 RPM
Wheels	Dual Auto Lock In Reverse Dig
Gearbox	Dual Belt Chain Drive Auger
Auger	Side Offload Direct Drive
Warranty	3YR Engine - 1YR Chassis
Assembled Dimensions	85 x 36 x 48"
Weight	375 lb
Shipping Crate Dims	44 x 31 x 38" 474 lb
Container Qty	60




Tri-Cut High Carbide Teeth



Trolley Wheel



Lock out safety keys - Locking Throttle



Auger guard



EVEREST SNOW PLOW FULLY HYDRAULIC Custom Mount

Item Number: EVST9022
UPC: 826518005579

DESCRIPTION

DK2 is proud to bring you the ultimate snow plow solution in our line up - the DK2 Everest.

This prosumer, fully hydraulic snow plow kit provides you the opportunity to clear your parking lot, driveway, or laneway whenever required. With our fully hydraulic system you can raise, lower, and angle the snow plow blade from inside your vehicle using our wired hand held remote.

For extreme durability against the elements and rust, DK2 combines an industrial powder-coated paint finish on the blade with hot dipped galvanized hardware components to keep your plow looking new for years.

The plow itself simply clips to a DK2 custom fitted vehicle mounting system and can pretty much mount to anything that's fit to push snow.

SPECIFICATION

- Blade (W x H): 88" x 22"
- Assembled Plow Weight: 380 lbs
- Shipping Dims (wdh):
Box 1: 46.5" x 24.25" x 14"
Box 2: 37" x 34" x 23"
- Shipping Weight: 425 lbs
- Construction: Steel tube & sheet
- Colour/Finish: Black industrial powder coated blade skin and all other components
- Lift System: Hydraulic
- Angling System: Hydraulic, multiple positions
- Control System: Wired remote control to lift, lower, angle left or right
- Vehicle Mounting System: Custom bolt-on mounting brackets *Sold Separately
- Scraper Blade: Powder coated steel, replaceable
- Included: Snow Deflector, Skid Shoes



FEATURES

- Ships partially assembled (mount & wiring required).
- Simple bolt on custom fitted mounting brackets, no drilling or welding required (sold separately).
- Hydraulic system lifts and lowers blade (a more reliable repetitive-use mechanism than a winch).
- Light weight, no need to alter stock suspension.
- Black UV powder coated components with an industrial painted blade skin.
- Self leveling foot provides max blade tip clearance when the blade is fully raised.
- Skid shoes to assist guiding the blade edge over uneven terrain or from possibly marking those more delicate driveways.
- Snow Deflector to assist directing snow forward and also minimizing windshield spray.
- Blade markers to point out blade tips.
- Hydraulic positioning.
- Wired hand held control.
- Reliable industrial hydraulic lift systems.
- Blade hardware holds the hydraulic pump so it can get rolled away from the vehicle rather than being left on the truck with the mount.
- Thicker trip springs to ensure tension remains strong and coils tight for optimal performance when encountering obstacles.
- Existing holes in plow frame make it easy to add bolt-on accessories.
- Bolt on accessories and upgrades available.
- One-year manufacturers warranty.





AVALANCHE SNOW PLOWS Universal Mount

Item Numbers:

AVAL8219

AVAL8422

AVAL8826

DESCRIPTION

Wireless Winch

Our brand new DK2 Avalanche Snow Plow kits combine the simplicity of our original T-Frame plow with the strength of our custom mount frame.

The DK2 Avalanche Snow Plow allows you to quickly and effectively remove snow from your driveway or small parking lot. The Avalanche simply slides into a 2" front mount receiver for easy removal and storage.

Each snow plow ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a 3,000lb wireless electric winch. Each Avalanche plow will also include a set of blade stiffeners for added strength by creating a 3 point connection.

SPECIFICATION

• Item Number: AVAL8219

- Blade Dimensions: 82 x 19 Inches H
- Assembled Weight: 265 lbs
- Gross Weight: 321 lbs
- Box Dimensions: 46 x 36 x 18 Inches
- UPC: 826518004992

• Item Number: AVAL8422

- Blade Dimensions: 84 x 22 inches H
- Assembled Weight: 283 lbs
- Gross Weight: 334 lbs
- Box Dimensions: 44 x 32 x 18 inches
- UPC: 826518005005

• Item Number: AVAL8826

- Blade Dimensions: 88 x 26 inches H
- Assembled Weight: 296 lbs
- Gross Weight: 341 lbs
- Box Dimensions: 46 x 35 x 17 inches
- UPC: 826518005708



FEATURES

- Fits most light trucks and SUV's
- Easy to mount – simply slides into a 2" class III front mount receiver in seconds. Slide out and roll away for storage
- An electric winch lifts the blade, controlled from inside your warm vehicle for easy up and down snow control
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- Powder coated all-steel with UV protected paint
- Flip down locking castors allow easy plow attachment, removal, and roll away storage – just lower the wheels and roll the unit to wherever you want it
- Each snow plow kit also includes a set of blade stiffeners for added strength
- ISO 9001 certified manufacturer
- 1 year limited warranty
- Ships in a single carton on a standard size pallet

23



AVALANCHE ELITE SNOW PLOWS Universal Mount

Item Numbers:

AVAL8219ELT

AVAL8422ELT

AVAL8826ELT

DESCRIPTION

Wireless Actuator

The Elite version of the DK2 Avalanche Snow Plow still combine the simplicity of our original T-Frame plow with the strength of our custom mount frame but also use a wireless actuator instead of a winch.

The DK2 Avalanche Snow Plow allows you to quickly and effectively remove snow from your driveway or small parking lot. The Avalanche simply slides into a 2" front mount receiver for easy removal and storage.

Each elite snow plow ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a wireless actuator. Each Avalanche plow will also include a set of blade stiffeners for added strength by creating a 3 point connection.

SPECIFICATION

• Item Number: AVAL8219ELT

- Blade Dimensions: 82 x 19 Inches H
- Assembled Weight: 265 lbs
- Gross Weight: 321 lbs
- Box Dimensions: 46 x 36 x 18 Inches
- UPC: 826518005661

• Item Number: AVAL8422ELT

- Blade Dimensions: 84 x 22 inches H
- Assembled Weight: 283 lbs
- Gross Weight: 334 lbs
- Box Dimensions: 44 x 32 x 18 inches
- UPC: 826518005685

• Item Number: AVAL8826ELT

- Blade Dimensions: 88 x 26 inches H
- Assembled Weight: 296 lbs
- Gross Weight: 341 lbs
- Box Dimensions: 46 x 35 x 17 inches
- UPC: 826518005715



FEATURES

- Fits most light trucks and SUV's
- Easy to mount – simply slides into a 2" class III front mount receiver in seconds. Slide out and roll away for storage
- A wireless actuator lifts the blade, controlled from inside your warm vehicle for easy up and down snow control
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- Powder coated all-steel with UV protected paint
- Flip down locking castors allow easy plow attachment, removal, and roll away storage – just lower the wheels and roll the unit to wherever you want it
- Each snow plow kit also includes a set of blade stiffeners for added strength
- ISO 9001 certified manufacturer
- 1 year limited warranty
- Ships in a single carton on a standard size pallet



SNOW PLOW KITS

Custom Mount

Item Numbers:

RAMP8219

STOR8422

SUMM8826

DESCRIPTION

Wireless Winch

All DK2 Snow Plows allow you to quickly & effectively remove snow from your driveway or small parking lot. DK2's range of personal plows each mount on to a vehicle specific custom mounting brackets.

Ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a 3,000lb wireless electric winch.

SPECIFICATION

• RAMPAGE II

• Item Number: RAMP8219

- Blade Dimensions: 82 x 19 inches
- Assembled Weight: 265 lbs
- Gross Weight: 315 lbs
- Box Dimensions: 43 x 32 x 18 inches
- Custom mount sold separately
- UPC: 693495992167

• STORM II

• Item Number: STOR8422

- Blade Dimensions: 84 x 22 inches
- Assembled Weight: 283 lbs
- Gross Weight: 325 lbs
- Box Dimensions: 44 x 32 x 18 inches
- Custom mount sold separately
- UPC: 693495992174

• SUMMIT II

• Item Number: SUMM8826

- Blade Dimensions: 88 x 26 inches
- Assembled Weight: 296 lbs
- Gross Weight: 341 lbs
- Box Dimensions: 46 x 35 x 17 inches
- Custom mount sold separately
- UPC: 693495992181



Upgraded Winch



Upgraded Wireless Control



Custom Mount

FEATURES

- Fits most light trucks and SUV's
- Easy to mount – simply slides onto your custom vehicle specific mounting brackets in seconds. Slide out and roll away for storage
- An wireless winch lifts the blade, controlled from inside your warm vehicle for easy up and down snow control
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- Powder coated all-steel construction with UV protected paint
- Locking castors allow easy plow attachment, removal, and roll away storage – just lower the wheels and roll the unit to wherever you want it
- ISO 9001 certified manufacturer
- 1 year limited warranty
- Ships in a single carton on a standard size pallet

25



ELITE SNOW PLOW KITS Custom Mount

Item Numbers:
RAMP8219ELT
STOR8422ELT
SUMM8826ELT

DESCRIPTION

Wireless Actuator

DK2's line of personal snow plows just got better! The DK2 ELITE SERIES Snow Plow line up takes its simple yet effective design and improves on it with a wireless actuator for ultimate reliability.

DK2's ELITE SERIES each mount on to a vehicle specific custom mounting brackets. Each snow plow ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a wireless electric actuator kit.

SPECIFICATION

- **RAMPAGE II ELITE**
- **Item Number: RAMP8219ELT**
- Blade Dimensions: 82 x 19 inches
- Assembled Weight: 265 lbs
- Gross Weight: 315 lbs
- Box Dimensions: 43 x 32 x 18 inches
- Custom mount sold separately
- UPC: 826518005326
- **STORM II ELITE**
- **Item Number: STOR8422ELT**
- Blade Dimensions: 84 x 22 inches
- Assembled Weight: 283 lbs
- Gross Weight: 325 lbs
- Box Dimensions: 44 x 32 x 18 inches
- Custom mount sold separately
- UPC: 826518005333
- **SUMMIT II ELITE**
- **Item Number: SUMM8826ELT**
- Blade Dimensions: 88 x 26 inches
- Assembled Weight: 296 lbs
- Gross Weight: 341 lbs
- Box Dimensions: 46 x 35 x 17 inches
- Custom mount sold separately
- UPC: 826518005340



Wireless
Actuator



Upgraded
Wireless
Control



Custom
Mount

FEATURES

- Fits most light trucks and SUV's
- Easy to mount – simply slides onto your custom vehicle specific mounting brackets in seconds. Slide out and roll away for storage
- An electric actuator lifts the blade, controlled from inside your warm vehicle for easy up and down snow control
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- Powder coated all-steel construction with UV protected paint
- Locking castors allow easy plow attachment, removal, and roll away storage – just lower the wheels and roll the unit to wherever you want it
- ISO 9001 certified manufacturer
- 1 year limited warranty
- Ships in a single carton on a standard size pallet



TRUNK MOUNTED BIKE CARRIER

**Mounts to the trunk
of most cars**

Item Number: BCR190

UPC: 827518007129

DESCRIPTION

Just because you don't have a receiver hitch on your vehicle doesn't mean you can't take your bikes with you. The DK2 BCR190 allows you to strap our carrier to the trunk of your car or small SUV and haul up to 3 bikes with you. Adjustable for most makes and model of vehicles and easy to assemble. Soft rubber cradles and strap allow you to secure the bikes to the carrier without managing the finish or performance of your bicycles. Six adjustable straps will securely hold the bikes in place for whatever trip you take!



Folding adjuster.



Attachment Straps.



Frame straps are easy to use and long lasting. (We tested this over 5000 times without breaking!)



FEATURES

- UV Resistant.
- Extreme Temperature Resistant.
- N.W: 6.61 lbs (3kg)
- G.W: 9 lbs (4.1kg)
- Size: 27.7 x 12.7 x 25.9"
(62.8 x 32.5 x 66 cm)
- Box size: 29.5 x 6.1 x 18.8"
(75 x 15.5 x 48cm)



HITCH MOUNTED BIKE CARRIER

**Mounts to the hitch
of most cars**

Item Number: BCR290

UPC: 827518007136

DESCRIPTION

The DK2 Hitch Mounted Bike Carrier is the perfect way to transport your bicycles on those long road trips. Quick and easy assembly takes only minutes. The BCR290 is constructed of UV power coated steel to help resist damage from harsh weather conditions. Simply slide the bike carrier into your 2 inch receiver hitch and secure using the anti wobble hitch pin. No mark straps allow you to secure up to 4 bikes to your carrier for transportation. The carrier also tilts away for easy access to your trunk.

FEATURES

- Mounts up to 4 bikes
- Powder coated steel
- Easy to assemble
- Can be folded when not in use
- Can open trunk when fitted
- N.W: 19.9 lbs (9.07kg)
- G.W: 21.7 lbs (9.87kg)
- U Pipe Size: 24.4" (62cm)
Height: 35.4" (90cm)
- Box size: 26.4 x 13.7 x 3.5"
(67.3 x 34.8 x 8.9cm)

28



Fits any 2" Receiver.



Easy to assemble.



Frame straps are easy to use and long lasting. (We tested this over 5000 times without breaking!)



WWW.DETAILK2.COM



HITCH MOUNTED BIKE CARRIER

**Mounts to any 2"
hitch receiver**

Item Number: BCR490

UPC: 827518001172

DESCRIPTION

Family holidays are always better when you take the bikes along too. Detail K2 offers two different hitch mounted bike racks to do just that. Carry up to 4 bicycles easily.



Three different positions allow you to minimize distance bike carrier extends while also being able to swing the unit away and access the rear of your vehicle.



FEATURES

- Carries up to four bicycles on individually adjustable cradles
- Padded no-mark cradles with dual bike retention straps
- Cradle bar folds down when not in use
- Carries up to 4 bicycles on adjustable saddles
- Saddle bar folds down when not in use
- Unit swings down for access to the rear of vehicle
- Steel construction
- Black powder coat finish resists scratches and corrosion
- Slides into a standard 2" hitch receiver, Class III or IV (optional 1-1/4" adaptor kit available upon request)
- Shipped unassembled
- Weight: 44 lb. (19.96 kg)

29



HITCH MOUNTED BIKE PLATFORM RACK

**Mounts to any 2" or
1.25" hitch receiver**

Item Number: BCR590
UPC: 827518007112

DESCRIPTION

The DK2 Hitch Mounted BCR590 Bike Carrier fits into either a 1-1/4" or 2" receiver hitch. This unit allows you to transport two bicycles by securing them to carrier. The BCR590 adjusts in width and height to fit your bike while making sure the no mark straps do not damage the finish of your bike. The carrier folds up when not in use and the center arm can fold down to allow access to the rear of the vehicle without removing the rack. Light weight and easy to assemble the BCR590 is the perfect solution for those long road trips!



Fit for 1 1/4" and 2"
and hitch Receiver.



Safe bike holder
with adjustable
height.



Can adjust the rack according to the bike tire size and
secure with the rubber straps.



FEATURES

- Easily adjustable to all frame size.
- Transports up to 2 bikes
- Push button ratcheting arms
- Easily adjusts to all frame sizes
- Rack folds for easy storage
- Folding center arm allows for easy rear vehicle access
- Material: Steel
- Finish: Black power coating
- 2" hitch & 1 1/4" hitch
- N.W: 28.6 lbs (13kg)
- G.W: 30.4 lbs (13.8kg)
- Size: 38.1 x 11 x 5.9"
(97 x 28 x 15cm)
- Box size: 40.5 x 9.8 x 5.3"
(103 x 25 x 13.5cm)



HITCH MOUNTED CARGO CARRIER

***Mounts to any 2"
hitch receiver***

**Item Number: HCC602
UPC: 827518001165**

DESCRIPTION

Increase the cargo capacity of your vehicle or haul bulky, messy items like luggage, coolers or firewood. Easy assembly. Conveniently mounts to any 2" hitch receiver on cars, SUVs, trucks, or vans.



Flips up when not in use, and stows up against the rear of the vehicle.

FEATURES

- Black powder-coat finish resists corrosion.
- Carrying capacity dependent on receiver strength: 500 lb. (226.8 kg) when used with a Class III / IV hitch.
- Heavy-duty tubular and expanded steel mesh construction.
- Mounts to any 2" hitch receiver.
- Conveniently flips up when not in use.
- Ships unassembled.
- Dimensions: 60 x 20 x 6 inches (152.4 x 50.8 x 15.2 cm).
- Assembled weight: 59.5 lb. (27 kg).

31





ALUMINIUM HITCH MOUNTED CARGO CARRIER

**Mounts to any 2"
hitch receiver**

**Item Number: HCC502A
UPC: 826518005051**

DESCRIPTION

The DK2 Hitch Mounted Aluminum Cargo Carrier allows you to immediately increase the cargo capacity of your vehicle so you can haul bulky, messy items like luggage, coolers or firewood. This functional item has a 500lb carrying capacity and also flips up close to your vehicle when not in use. The aluminum construction is lightweight while still being durable and rust proof.



TECHNICAL SPECS

Assembled Product:

- Height: 6.5 Inches
- Width: 49.5 Inches
- Depth: 22.25 Inches
- Weight: 29 lbs.

Packaged Product:

- Height: 4 Inches
- Width: 50 Inches
- Depth: 24 Inches
- Weight: 32 Lbs

FEATURES

- Increase The Cargo Capacity Of Your Vehicle.
- Easy Assembly.
- Mounts To Any 2 in. Hitch Receiver.
- Flips Up When Not In Use; Stows Against Rear Of Vehicle.
- Aluminum Finish Resists Corrosion.
- Includes threaded anti-wobble hitch pin for added stability.
- Carrying Capacity Dependent On Receiver Strength.
- Ships Unassembled.
- Reflectors for added safety.



HITCH-MOUNTED MOTORCYCLE CARRIER

**Mounts to any 2"
hitch receiver**

Item Number: TMC201
UPC: 693495970561

DESCRIPTION

How to determine weight capacity

To determine the weight capacity for the Detail K2 Hitch Mounted Motorcycle Carrier, you must first determine the tongue weight limit of your hitch receiver AND the tongue weight limit of your vehicle. Take the lesser of these two figures and see the chart opposite:

Hitch / Vehicle Tongue Weight Limit (use lowest figure)		Max. Carrying Capacity of K2 Carrier	
300 lb.	136 kg	180 lb.	82 kg
350 lb.	159 kg	225 lb.	102 kg
500 lb.	227 kg.	350 lb.	159 kg
750 lb.	340 kg	450 lb.	204 kg

Example 1 If you have an SUV with a hitch receiver max. tongue weight of 500 lbs, AND your SUV manufacturer states that the maximum tongue weight for your vehicle is 500 lbs, then the maximum weight you can load on the Detail K2 Hitch Mounted Motorcycle Carrier is 350 lbs.

Example 2 If you have an SUV with a hitch receiver max. tongue weight of 500 lbs, BUT your SUV manufacturer states that the maximum tongue weight for your vehicle is only 350 lbs, then the maximum weight you can load on the Carrier is 225 lbs.



FEATURES

- Extremely versatile, Extremely secure and stable: patent-pending design results in snug, "anti-wobble" fit.
- Tilts down to allow easy loading: one-person operation
- Easily installed and removed: no extra tools required
- Ideally suited for SUV, RV, or pickup truck with cap
- Features adjustable front wheel channel (to accommodate different sized bikes) and retractable tie-down bar
- Comes with safety chains and hitch pin
- Fits standard 2-" class III or IV hitch receiver: weight capacity dependent on receiver strength
- Black UV powder-coat finish

33



DK2 FLIP RACK

***Easy, no drilling
installation***

**Item Number: TFR150
UPC: 693495970721**

DESCRIPTION

The TFR150 give you flexibility and combines the safety and security of a headache rack with the functionality of an elevated ladder rack. Installation takes minutes, requires no drilling and fits most full size trucks.

With a simple flip up and back of the crossbar the rack immediately gives you the ability to transport everyday things that require extra length. Ladders, pipe, lumber and even canoes all easily tie down fixed and secure on the upper deck. Once you're done the crossbar is easily flipped forward and down and secured back to its starting position against the headache rack.


AVAILABLE ACCESSORIES

- Light Bar
- Boat Rack
- Adaptor Kit for Hard Top Tonneau Covers

FEATURES

- Converts from a window guard into a full-length utility rack with a simple "flip" of a crossbar
- Strong and rigid: heavy-duty steel construction
- Cargo can be secured to window guard to prevent shifting loads
- Rack can support up to 225 kg / 500 lbs (distributed) in open position: ladders, lumber, etc.
- Easily installed and removed
- No drilling truck (clamps provided)
- Fits most makes and model trucks
- Pkg. dim.: 54.0 x 24.0 x 5 inches (1372 x 610 x 127 mm)
- Gross weight: 121.25 lb. (55 kg)
- Minimum bed width is 51 inches





HEAVY DUTY PORTABLE BATTERY BOOSTER PACK

Item Number: GL10
UPC: 826518004916

DESCRIPTION

New to the DK2 family is the GL10 Portable Battery Booster. This unit is industry leading in every way and can provide a portable emergency power source when you need it most.

The GL10 comes with intelligent clamps that fit both 12V and 24V car jump starters. There is intelligent detection circuit which can tell the output voltage of 12V and 24V car jump starter, and start different protection system accordingly. The unit also has a warning sound and LED light reminder.

Overall protection functions include: back charge protection, overcharge protection, over discharge protection, shortage protection and reverse polarity protection, as well as function of testing the situation of the cars battery.



ACCESSORIES

- Starting Power Bank
- Home Charger
- Micro Cable
- Jump Cable Battery Clamps
- 12 V Output Converter
- 24 V Output Converter
- User Manual
- Carrying Bag

SPECIFICATION

- Battery Capacity: 88.8 Wh
- Start Current: 400 A
- Peak Current: 800 A
- Input: 15 V / 2 A
- Output: 5 V / 2 A, 12 V / 24 V for Jump Start
- Charging Time: 4.5 Hours
- Life Time: > 800 Cycles
- Size: 7" L x 2.5" W x 2.5" H
- Weight: 1040g

35



DESCRIPTION

The DK2 Power 2 Go is the incredibly powerful yet versatile battery jump starter that literally sits in the palm of your hand.

Slightly larger than your Smartphone, it is powerful enough to jumpstart most full sized cars and trucks. All this power and it can still be easily stored in your glove box. With multiple ports and adapters included, there's no longer a need to panic when your Smartphone, tablet or laptop is running low on power. Simply plug into your DK2 Power 2 Go and watch in amazement as your device quickly charges.

The P2G can be used on: Cars, Bobcats, ATV's, UTV's, Snow-mobiles, Golf carts, and Boats.



POWER 2 GO PORTABLE BATTERY CHARGER

Item Number: P2G850
UPC: 826518005142

FEATURES

- Built in rechargeable high output Lithium-iron battery
- 14,000 mAh capacity
- Upgraded Copper Booster cables and clamps
- Output: 12V / 5V, 2 A
- Peak Current 400A
- 850 Cold Cranking amps starting current
- Can boost a single vehicle 20 times on a single charge
- Overload and over-charge protection
- Charging adapters for most major electronic devices

SPECIFICATION

- Item Number: P2G850
- Unit Dimensions: 6.3 x 3.0 x 1.4"
- Assembled Weight: 2 lbs
- Gross Weight: 3 lbs
- Box Dimensions: 11 x 2 x 8"



4^{IN}

CORDLESS VEHICLE KIT

Item Number: CHPW102
UPC: 827518007105

DESCRIPTION

Gone are the days of having too many tools that serve only one purpose.

A pressure washer, blower, inflator, and vacuum all in one, the DK2 4 in 1 Cordless Kit is a first of its kind. The lightweight and secure handle is designed to make switching attachments effortless, while the high capacity battery won't run out until the job is done.

Don't let its compact size fool you, the DK2 4-in-1 Cordless Kit's convenient size is designed for anyone to tackle any job.

CONTENTS INCLUDE

- 20v x 2.0AS Lithium Battery x 2
- 1-hour quick charging station
- High Pressure Washer Attachment (330 PSI max pressure)
- 20 ft Water Hose
- Inflator attachment
- Blower Attachment
- Vac Cleaner Attachment

FEATURES

- 1 hour quick charge.
- 1 year warranty

SPECIFICATION

Cordless Pressure Washer:

- Max pressure: 360 PSI / 25 bar
- Flow: 2.5 L per min.
- 1 x 6 m (19.8 ft.) hose
- 1 x short lance
- 1 x spray nozzle

Cordless Inflator:

- Max pressure: 100 PSI / 7 bar
- 1 x 50 cm (19.7 in.) inflator hose
- 1 x ball adaptor
- 1 x air bed adaptor

Cordless Vacuum Cleaner:

- No-load speed: 0-15000 RPM
- Blower air flow: 2.5 m³ per minute
- Vacuum: 8000 Pa
- Container capacity: 0.6 L

Cordless Blower:

- No-load speed: 0-15000 RPM
- Blower air flow: 2.5 m³ per minute

37



DESCRIPTION

ELECTRIC HOISTS

Compact, general purpose 240v electric hoist is ideal for all manner of lifting applications. Easy to install, with easy change cable design. It is supplied with special fixing clamps for simple section beam fitting (square section beams). This hoist also has the facility to add a wireless remote control as an option.



HOISTS

DK2 WARRIOR HOISTS

Item Numbers:
EH250, EH500

SPECIFICATIONS

Model: EH250 (120v)

Max Load

Single Pull: 275 lbs (125 kg)

Double Pull: 551 lbs (250 kg)

Lift Speed p/min

Single Pull: 59 ft (8m)

Double Pull: 29 ft (4m)

Cable: 0.12 in x 59ft
3mm x 18m

Rating: IP54

Model: EH500 (120v)

Max Load

Single Pull: 551 lbs (250 kg)

Double Pull: 1102 lbs (500 kg)

Lift Speed p/min

Single Pull: 59 ft (8m)

Double Pull: 29 ft (4m)

Cable: 0.15 in x 59ft
4mm x 18m

Rating: IP54



DESCRIPTION

Ideal for large ATV's and small trailers. A huge high power motor, heavy duty clutch, heavy duty steel gearing and heavy duty waterproof contactors ensure the ultimate in performance and reliability. Strengthened Steel drum makes it ideal to use with Synthetic Rope.

Watertight 4 Pin connection allows the use of 'Plug and Play' Wireless.

SPECIFICATION

C2500N

RATED LINE PULL: 2500lbs(1134kg)
MOTOR: 12v : 1.35hp / 0.95kw
GEARING: 170:1
BRAKING ACTION: Dynamic
DRUM SIZE Dia x L: 1.5 x 3.1"
CABLE Dia x L: 0.2" x 46 ft WR
0.2" x 46 ft SR
MOUNT PATTERN: 3.1"
DIMENSIONS: 13.2 x 4.4 x 6.5"

C3500N

RATED LINE PULL: 3500lbs (1588kg)
MOTOR: 12v : 1.95hp / 1.37kw
GEARING: 170:1
BRAKING ACTION: Dynamic
DRUM SIZE Dia x L: 1.5 x 3.1"
CABLE Dia x L: 0.2" x 42 ft WR
0.2" x 46 ft SR
MOUNT PATTERN: 3.1"
DIMENSIONS: 13.7 x 4.6 x 6.5"



NINJA

NINJA SERIES ATV WINCHES

Item Numbers:

**C2500N, C2500N-SR C3500N,
C3500N-SR**

FEATURES

- Sealed High Power Motor
- Heavy Duty Watertight Contactors
- Full Steel Planetary Gearing
- Strengthened Steel Drum (suitable for Synthetic rope)
- Watertight Controller Socket
- Gloss Chip Resistant Paint

INCLUDED

- Steel Cable
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- 3 Tonne Pulley Block
- Mounting plate & Hardware
- 1/4 hook



NINJA

NINJA SERIES TRAILER WINCHES

Item Numbers:

C4500N

C4500N-SR

DESCRIPTION

High quality three stage planetary gearing ensure this is one of the quietest and smoothest winches on the market.


The silky smooth performance and the full load holding brake make it the perfect solution for high spec applications.

SPECIFICATION

RATED LINE PULL: 4500lbs (2041kg)
MOTOR: 12v : 1.95hp / 1.37kw
GEARING: 172:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 1.7 x 3.8"
CABLE Dia x L: 0.25" x 47.5ft WR
 0.24" x 49 ft SR
MOUNT PATTERN: 5 x 3.7"
DIMENSIONS: 14.4 x 4.9 x 6.4"
WEIGHT: 28.6 lbs

Layer of wire rope	Line pull lbs (kg)
1	4500 (2401)
2	3642 (1652)
3	3060 (1388)
4	2638 (1196)

Line pull lbs (kg)	Line speed ft/min	Line speed m/min	Amp draw 12v	Amp draw 24v
0	11.6	3.6	20	15
1500 (680)	9.2	2.8	70	40
2500 (1134)	7.8	2.4	100	65
3500 (1587)	6.6	2.0	140	80
4500 (2041)	4.9	1.5	200	130



Steel version available



FEATURES

- Power in and Power out
- High Torque 1.95hp Motor
- HD Waterproof Contactors
- Full Steel Planetary Gearing
- Mount Plate as Standard
- Full Load Holding Break
- Can fit tow ball mount

INCLUDED

- 0.25" x 47.5ft Steel Cable
- 3m Remote Handset
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- Mounting plate
- Mounting hardware
- 3/8 hook
- *ATV remote available



PORTABLE UTILITY WINCH

Item Numbers:

40PUS12

40PUA12

DESCRIPTION

The Trojan Portable Utility Winch is a complete winching solution in a convenient kit that features a 4,000 lb rated line pull winch on a unique powder coated winch platform, all in a compact, easy to carry composite tool box. The kit is easy to store, use, and repack. Completely portable, the Trojan requires no installation and does not require a winch mount; however, it can be permanently mounted on a trailer and be used as a utility winch if desired.

SPECIFICATION

RATED LINE PULL:	4000lbs (1814kg)		
MOTOR: 12v:	1.4 hp (1.0 kW)		
GEARING:	166:1		
CABLE Dia x L:	5.4mm x 12.8m		
	(Synthetic Version: 5mm x 15m)		
WEIGHT:	20.5kg		
	(Synthetic Version: 19 kg)		

Line pull		Line speed		Amp draw
lbs (kg)		ft/min	m/min	12v
0		20	6	20
4000 (1814)		5.5	1.6	220



FEATURES

- 4000 lb Pulling Power
- Synthetic or Wire Rope version available
- Built in 1/4 inch hardened steel plate
- Can be permanently mounted
- Quick plug and play functionality

INCLUDED

- 6 000 lb pulley block
- Quick connect cord with alligator clips
- Three 20,000 lb D-shackles
- 2 x 8 ft HD straps rated 8,000lbs
- 12ft Hand Help Remote
- 10 foot quick connect power cord
- Heavy Duty leather palmed winch gloves





SPARTAN

SPARTAN 6000 ELECTRIC WINCH

Item Numbers:

6000

6000-SR

DESCRIPTION

Warrior Winches are delighted to announce the arrival of the new member of Spartan Series, Tough, Strong and ready for Battle. The Spartan 6000 Lb short drum model is ideal where space and payload are limited. The winch has a short drum and is less than 66Lbs, however the extended drum supports allow it to carrier up to 131ft of 0.28" cable. The Synthetic rope version comes fitted with 0.27" x 98ft.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

With great performance, outstanding features included as standard, & backed by the Warrior Winches un-rivalled limited Lifetime Warranty, this should make a Spartan the first choice for all serious enthusiasts.

SPECIFICATION

RATED LINE PULL: 6000 lbs (2727kg)
MOTOR: 12V: 4.5hp / 3.4kW
GEARING: 230:1
DRUM SIZE Dia x L: 2.48 x 4.2"
CABLE Dia x L: 0.28" x 131 ft WR
 0.28" x 98 ft SR
DIMENSIONS: 17.4 x 7.7 x 10.8"
WEIGHT: 66 lbs



Layer of wire rope	Line Pull lbs (kg)	Cable Cap ft (m)
1	6000 (2727)	9.8 (3.0)
2	4979 (2258)	22.0 (6.7)
3	4255 (1930)	36.1 (11.0)
4	3714 (1685)	52.2 (15.9)
5	3296 (1495)	70.5 (21.5)
6	2962 (1344)	90.9 (27.7)
7	2690 (1220)	113.2 (34.5)
8	2463 (1117)	131.2 (40.0)

Line pull lbs (kg)	Line speed ft/min	Line speed m/min	Amps 12v
0	19.4	5.9	80
2000 (907)	13.1	1.0	140
4000 (1814)	9.2	2.8	210
6000 (2727)	7.2	2.2	285

FEATURES

- Weather Sealed High Performance Motor
- Heavy Duty 3 Stage Gearbox
- Heavy Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch is 100% Load Tested
- Chip Resistant Gloss Paint Finish

INCLUDED

- 10ft Remote Handset
- 5/16 Hook
- Aluminium or Roller Fairlead (Synthetic rope or steel cable)
- Heavy Duty Battery Leads
- Stainless Steel Mounting Hardware
- 0.27" x 98ft Synthetic Rope or 0.28" x 131ft Steel Cable



SPARTAN

SPARTAN SERIES ELECTRIC WINCH

Item Numbers:
8000, 8000-SR
9500, 9500-SR
12000, 12000-SR

DESCRIPTION

We are delighted to announce the arrival of the Spartan Series, Tough, Strong and ready for a Battle, these Winches really will challenge all before them. We have reluctantly termed them as 'entry level', however this describes the price point, not the performance.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

SPECIFICATION

8000

RATED LINE PULL: 8000lbs(3629kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 233:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.3" x 85 ft WR
 0.35" x 82 ft SR
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 21.3 x 6.3 x 8.6"



9500

RATED LINE PULL: 9500lbs(4500kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.36" x 82 ft WR
 0.35" x 82 ft SR
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 21.3 x 6.3 x 8.6"

12000

RATED LINE PULL: 12000lbs (5400kg)
MOTOR: 12v : 6.0hp / 4.6kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.4" x 82 ft WR
 0.43" x 82 ft SR
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 22.8 x 6.3 x 8.6"

FEATURES

- Weather Sealed High Performance motor
- Heavy-Duty 3 Stage Gearbox
- Heavy-Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch 100 % load tested
- Chip Resistant Gloss Paint Finish

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Steel Roller Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- Clevis hook



SAMURAI SERIES ELECTRIC WINCH

Item Numbers:

S8000, S8000-SR

S9500, S9500-SR,

S12000, S12000-SR

DESCRIPTION

Superb high specification winch. Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing.

Comes with stainless steel roller fairlead and fittings as standard. Complete with Heavy Duty integrated wireless remote. Available with Armortek Synthetic Rope and Aluminum Fairlead.

SPECIFICATION

S8000

RATED LINE PULL: 8000lbs(3629kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 210:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.3" x 95 ft
MOUN PATTERN: 10 x 4.5"
DIMENSIONS: 21.3 x 6.3 x 8.6"

S9500

RATED LINE PULL: 9500lbs(4500kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.4" x 85 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 21.3 x 6.3 x 8.6"



S12000

RATED LINE PULL: 12000lbs(5400kg)
MOTOR: 12v : 6.5hp / 4.6kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.4" x 85 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 22.8 x 6.3 x 8.6"

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



SAMURAI

SAMURAI 9,500 LB HIGH SPEED PERFORMANCE WINCH

Item Numbers:

S9500HS

S9500HS-SR



DESCRIPTION

The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing.

Complete with heavy duty integrated wireless remote. Available with Steel Rope or Armortek Synthetic Rope and Aluminum Fairlead.

SPECIFICATION

RATED LINE PULL: 9500lbs(4500kg)
MOTOR: 12v : 6.5hp / 4.5kw
GEARING: 110:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 8.8"
CABLE Dia x L: 0.4" x 98 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 22.7 x 6.3 x 8.5"



Layer of wire rope	Line pull lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5400 (2400)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	65	19.8	80	45
4000 (1818)	12.5	3.8	300	175
6000 (2722)	11.81	3.6	400	230
9500 (4309)	8.86	1.9	530	335

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Integrated Wireless Remote

INCLUDED

- Wire rope 0.4" x 98ft
- 10ft Remote Handset
- Roller Fairlead (does not attach to winch)
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



SAMURAI

SAMURAI 9,500 LB SHORT DRUM WINCH

Item Numbers:

S9500SD

S9500SD-SR

DESCRIPTION

The narrow drum version of the best selling 9500. A total width of 17.2 inches ensures this is the perfect product for limited space. The 5.0hp motor delivers 9500lb of pulling power in space normally designed for Winches with half the power.

The Short Drum winch is the preferred choice of the British Military on specialist vehicles currently serving in action. Available with synthetic rope and aluminium fairlead, to give a total weight of 44 lbs.

SPECIFICATION

RATED LINE PULL: 9500lbs(4500kg)
MOTOR: 12v : 5.0hp / 3.5kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 2.5 x 4.7"
CABLE Dia x L: 0.4" x 46 ft
MOUNT PATTERN: 5.9 x 4.5"
DIMENSIONS: 17.2 x 6.3 x 10.7"



Layer of wire rope	Line pull lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5593 (2537)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	23	7	80	70
3000 (1361)	12.5	3.8	170	140
6000 (2722)	9.8	3	260	210
9500 (4309)	6.4	1.9	380	270

FEATURES

- Power in and Power out
- High Quality 5.0hp Series Wound Motor
- Heavy Duty Waterproof Contactors
- Full Steel Planetary Gearing
- Double sealed motor and drum
- Full Load Holding Brake
- Integrated Wireless remote

INCLUDED

- 0.4" x 46ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



Item Numbers:

S14500

S14500-SR

DESCRIPTION

Our premium "Next Generation" Samurai range are even faster, with a lower current draw and now boast a revolutionary external brake, more capable of load holding & lowering, as well as ensuring there's no heat build up in the drum, perfect for Armortek Ropes.

Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with solid brass contacts, heavy duty 4 pin waterproof contactors, double sealed drum on maintenance free bearings and quiet, efficient full steel planetary gearing. Comes with Aluminium Hawse Fairlead and fittings as standard. The 12V version comes complete with heavy duty integrated wireless remote.

SPECIFICATION

RATED LINE PULL:	14500 lbs (6577kg)
MOTOR: 12v :	7.2hp / 5.4kw
GEARING:	253:1
BRAKING ACTION:	External Brake
DRUM SIZE Dia x L:	2.48 x 8.77"
CABLE Dia x L:	0.43 in x 82 ft
	0.4" x 83.6ft WR
DIMENSIONS:	23.3 x 6.3 x 9.8"



Layer of wire rope	Line pull lbs (kg)
1	14500 (6577)
2	11519 (5224)
3	9556 (4334)
4	8163 (3702)

Line pull lbs (kg)	Line speed ft/min	Line speed m/min	Amp draw 12v	Amp draw 24v
0	31.16	9.5	60	50
6000 (2728)	12.46	3.8	200	140
10000 (4545)	5.57	1.7	310	190
12000 (5443)	4.9	1.5	380	230
14500 (6577)	3.28	1.0	430	260

FEATURES

- 4 Pin Waterproof Connector
- Solid Brass Contacts Direct to the Motor
- Silver Copper Motor with Copper Brush Holders
- Chip Resistant Powder Coated Finish
- Extensive Waterproof Sealing to IP68 Standard
- Removable Heavy Duty Hook
- Wireless 2.4G Upgraded Remote
- Stainless Steel 4 Way Fairleads
- HRC50 Full Steel Gears
- Revolutionary Design External Brake
- Laser Etched Extruded Aluminium Tie Bars
- 600 amp Silver Tip Contactor

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Aluminium Fairlead or Heavy Duty Stainless Steel Fairlead
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote

**SAMURAI**

SAMURAI 17500 & 20000 LB WINCHES

Item Numbers:

S17500, S17500-SR**S20000, S20000-SR**

DESCRIPTION

Warrior Winches are excited to announce the arrival of the colossal Samurai 17500 & 20000lb Winches. Designed for the toughest of applications & tested in the most extreme environments imaginable, these Winches boasts a massive 7.0 & 7.5 hp Series wound motors respectively.

48

Double sealed drum on maintenance free bearings and quiet, fully sealed efficient full steel planetary gearing ensures these Immense Warriors are ready for any battle.

SPECIFICATION

S17500 Winch

RATED LINE PULL: 17 500lbs (7938kg)
MOTOR: 12v : 7.0hp / 4.9kw
GEARING: 430:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 3.5 x 8.6"
CABLE Dia x L: 0.5" x 85 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 24 x 8.5 x 10"
WEIGHT: 147.7 lbs



S20000 Winch

RATED LINE PULL: 20 000lbs (9072kg)
MOTOR: 12v : 7.5hp / 5.4kw
GEARING: 430:1
BRAKING ACTION: Automatic in the drum
DRUM SIZE Dia x L: 3.5 x 8.6"
CABLE Dia x L: 0.47" x 87 ft
MOUNT PATTERN: 10 x 4.5"
DIMENSIONS: 24 x 8.6 x 10.7"
WEIGHT: 158.7 lbs

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Reinforced Plastic Contactor Cover
- Double Sealed Drum (G-box/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- High Quality Steel Drum Supports

INCLUDED

- 0.5" x 85ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead (Wire version)
- Alloy Fairlead (Rope version)
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Wireless Remote



DESCRIPTION

The Predator is designed for hard-core competition. Two powerful 7.2HP sealed motors provide performance that is truly out of this World. Together with a 108:1 ratio 3 stage planetary gearbox, this winch handles the most extreme off-road punishment.

With a surprisingly low draw of only 140 amps (at no load), the Predator also contains an innovative “multi stop” 10% ratchet brake design, which provides zero drag when returning the “cable in”, and is situated away from the drum to prevent any damaging heat transferring to your Armortek or Synthetic rope.

The steel drum flanges are precision machined to 0.39” on either side to resist the unique loading characteristics of synthetic rope, while the Alloy Carbon gears are heat treated and tempered to 62HRC rating for extra strength. This Warrior from another dimension will mercilessly prey on its weaker rivals, hunting the opposition down. At 10kg lighter than any of its nearest competitors, with off-load line speeds from 65ft per minute & available with or without synthetic rope, there’s a Predator out there, ready & waiting, for everyone!

SPECIFICATION

RATED LINE PULL:	10 000lbs (4536kg)
MOTOR: 12v :	7.2hp / 5.4kw
GEARING:	108:1
DRUM SIZE Dia x L:	2.8 x 8.42”
CABLE Dia x L:	0.35” x 124ft
MOUNT PATTERN:	10 x 4.5”
DIMENSIONS:	18.8 x 10.3 x 13.9”
WEIGHT:	99lbs

Layer of wire rope	Line pull lbs (kg)	Total Rope on drum ft(m)	Line pull lbs (kg)	Line speed ft(m)/min 12v	Amp draw 12v
1	10000 (4536)	18.4 (5.6)	0	66 (20)	140
2	8153 (3698)	41.0 (12.5)	4000 (1816)	19.7 (6.0)	400
3	6881 (3131)	68.9 (21)	6000 (2722)	16.7 (5.1)	560
4	5953 (2700)	101 (30.8)	8000 (3629)	13.1 (4.0)	690
5	5245 (2379)	131.2 (40)	10000 (4536)	10.5 (3.2)	790

PREDATOR

PREDATOR 10,000 LB DUAL MOTOR PERFORMANCE WINCH

Item Number:
P10000D-SR

FEATURES

- Dual 7.2HP (5.4KW) Sealed Motors
- Sealed Motor conforms to IP67
- Sealed Waterproof Contactor
- “Multi Stop” 10% Ratchet Brake Design
- Sealed 3 Stage Planetary Gears
- Alloy Carbon Gears hardened to 62HRC Rating
- No load speed of 65ft/min

INCLUDED

- 0.35” x 124ft Synthetic Armortek Rope
- Wireless remote with LCD Display
- Heavy Duty Remote Control
- Silver Warrior Aluminum Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- 12 Ton Competition Hook



T1000

T1000 ELITE COMBAT WINCHES

Item Numbers:

T1000-100

T1000-145

T1000-220

DESCRIPTION

The T1000 Series Winches are built specifically for military use, able to withstand extreme climates and temperatures. Features include hardened 3 stage planetary gears for reliable and efficient use in the harshest environments. The waterproof remote control has thermometric LED indicators signals to monitor the temperature of the motor and high temp lithium grease is used which doesn't solidify in extreme climates. Coupled with corrosion & chemical resistant matte black powder coat & a stainless steel fairlead makes this a formidable winch able to withstand whatever is thrown at it.

SPECIFICATION

T1000-100 Elite Combat Winch

RATED LINE PULL: 10000lbs (4535kg)
MOTOR: 12v: 4.6kw / 6.2hp
GEARING: 228:1
DRUM SIZE Dia x L: 63 x 217mm
CABLE Dia x L: 9mm x 25m (9.1 x 25m WR)
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 638 x 214 x 289mm



T1000-145 Elite Combat Winch

RATED LINE PULL: 14000lbs (6350kg)
MOTOR: 12v: 5.4kw / 7.2hp
GEARING: 228:1
DRUM SIZE Dia x L: 63 x 217mm
CABLE Dia x L: 11mm x 20m (11 x 23m WR)
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 638 x 214 x 289mm

T1000-220 Elite Combat Winch

RATED LINE PULL: 22000lbs (9978kg)
MOTOR: 12v: 5.5kw / 7.4hp
GEARING: 450:1
DRUM SIZE Dia x L: 88 x 214mm
CABLE Dia x L: 14mm x 20m (13.8 x 24m WR)
MOUNTING PATTERN: 254 x 114.3mm / 254 x 165.1mm
DIMENSIONS: 638 x 214 x 289mm

FEATURES

- IP68 Rated Military Grade Winch & Control Box.
- Hardened 3 stage planetary gears.
- Waterproof remote control with LED indicators.
- Corrosion & Chemical Resistant Powder Coat.
- High Temperature Lithium Grease that won't solidify in extreme temperatures.

INCLUDED

- Armortek Winch Rope (or Steel Rope available)
- Aluminum Fairlead (or Stainless Steel Fairlead for wire rope)
- Stainless Steel Mounting hardware
- Hook



NH SERIES HYDRAULIC WINCHES

Item Numbers:

10000NH

15000NH

DESCRIPTION

Compact, tough. A hydraulic winch for industrial and commercial applications. The unique patented steel gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding. Stainless steel roller fairleads and fittings are standard.

SPECIFICATION

10 000 NH HYDRAULIC Winch

RATED LINE PULL:	10 000lbs (4536kg)
MAX LINE PULL:	12 500lbs (5670kg)
MOTOR:	Hydraulic Dis 50 ml/r
GEARING:	33:1
DRUM SIZE Dia x L:	2.8 x 8.8"
CABLE Dia x L:	0.4" x 87ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	20 x 7.3 x 8.8"

15 000 NH HYDRAULIC Winch

RATED LINE PULL:	15 000lbs (6804kg)
MAX LINE PULL:	17 000lbs (7711kg)
MOTOR:	Hydraulic Dis 80 ml/r
GEARING:	37:1
DRUM SIZE Dia x L:	3.5 x 8.8"
CABLE Dia x L:	0.5 x 87ft
MOUNT PATTERN:	10 x 4.5"
DIMENSIONS:	20.9 x 8.1 x 9.7"

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Stainless Steel fairlead and Fittings
- Rugged and compact for Long Life

INCLUDED

- Steel cable (see below)
- Heavy Duty Roller Fairlead (10000/15000NH)
- 5/16 or 3/8 Hook



NW SERIES HYDRAULIC WINCHES

Item Numbers:

10000NW**15000NW**

DESCRIPTION

Compact, tough. A hydraulic winch for industrial and commercial applications. The special heat treated planetary gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding.

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Rugged and Compact for Long Life
- Meets the requirements of SAE J706

SPECIFICATION

10 000 NW Winch

RATED LINE PULL:	10 000lbs (4536kg)
MAX LINE PULL:	12 500lbs (5670kg)
MOTOR:	Hydraulic Dis 100.8 ml/r
GEARING:	16:1
DRUM SIZE Dia x L:	3.9 x 9.9"
CABLE Dia x L:	1/2" x 86 ft
MOUNTING:	14.6 x 4.5" (11.34 x 4.5")
DIMENSIONS:	25 x 10.33 x 9.39"

15 000 NW Winch

RATED LINE PULL:	15000lbs(6810kg)
MAX LINE PULL:	17 500lbs (7954kg)
MOTOR:	Hydraulic Dis 160 ml/r
GEARING:	17.2:1
DRUM SIZE Dia x L:	5 x 10.6"
CABLE Dia x L:	0.6" x 92 ft
MOUNTING:	11.9 x 4.5" (14.5 x 4.6")
DIMENSIONS:	28.2 x 11.1 x 12"

INCLUDED

- 86 ft x 1/2" steel cable
- 5/16 Hook
- Tensioner included



JP SERIES HYDRAULIC WINCHES

Item Numbers:

**10TJP, 13.5TJP, 15TJP
20TJP, 30TJP, 40TJP**

DESCRIPTION

Tough and compact, the JP series are heavy duty hydraulic winches designed and tested for toughest applications.

Minimum rope to drum ratio of 10:1, multi disc frictional brake, balance valve and rope tensioner as standard.

Available from 10 tonne to 40 tonne. Manufactured to meet GJB82-86 National Military Standard.



SPECIFICATION

	10TJP	13.5TJP	15TJP
RATED LINE PULL (btm layer):	10 000 kg 22046 lbs	13 500 kg 29762 lbs	15 000 kg 33069 lbs
WORKING SPEED (btm layer):	21.6ft/min*	24.6ft/min	20ft/min
ARRESTER RESP PRESS:	5 Mpa	<2.5 Mpa	<2.5 Mpa
WORKING PRESSURE:	20 Mpa	17 Mpa	17 Mpa
OIL FLOW:	15-75 L/min	110 L/min	110 L/min
DRUM SIZE:	5.4x12.4"	15.7x8.3x13.4"	15.7x8.3x13.4"
REC ROPE SIZE:	157ft x 0.6"	131ft x 0.7"	230ft x 0.9"
WEIGHT:	363 lbs	578 lbs	628 lbs

	20TJP	30TJP	40TJP
RATED LINE PULL (btm layer):	20 000 kg 44092 lbs	30 000 kg 66138 lbs	40 000 kg 88184 lbs
WORKING SPEED (btm layer):	20ft/min	18ft/min	10ft/min
ARRESTER RESP PRESS:	<2.5 Mpa	<2.5 Mpa	<2.5 Mpa
WORKING PRESSURE:	17 Mpa	17 Mpa	17 Mpa
OIL FLOW:	120 L/min	120 L/min	120 L/min
DRUM SIZE:	20.9x8.3x13.4"	20.9x11x14.2"	23.7x11x18.9"
REC ROPE SIZE:	197ft x 1"	197ft x 1.3"	213ft x 1.4"
WEIGHT:	650 lbs	1257 lbs	1763 lbs

*when oil flow 60L/min

FEATURES

- Full Float Heavy Duty Planetary Gearing
- Multi Disc Friction Brake
- Minimum 10:1 Rope/Drum Ratio
- High Torque Industrial Motor
- Air and Manual Clutch Operation

INCLUDED

- Heavy Duty Rope Tensioner as Standard
- Balance Valve as Standard

AMORTEK WINCH ROPE

ARMORTEK WINCH ROPES

Armortek synthetic rope is 70% stronger than wire!

- Armortek weighs 6 times less than wire.
- Unlike wire, Armortek will not whiplash if broken.
- Armortek is rated at 70% stronger than wire.
- Armortek floats, wire doesn't.
- Armortek is coated to prevent abrasion.
- You don't have to worry about wire splinters.

Diameter	6mm (3/16")	9.5mm (3/8")
Breaking Load	3200 kg (7040 Lb)	7500 kg (16500 Lb)

Part no: HW0884-CAD: 6mm x 16m (1/4" X 50') Synthetic Rope

Part no: HW0932/45-CAD: 10mm x 14m (3/8" x 45') Synthetic Rope

Part no: HW0932/85-CAD: 10mm x 26m (3/8" x 85') Synthetic Rope



CENTURION WIRELESS REMOTE

CENTURION

The ultimate remote for the professional user.

- Two-way Closelink wireless communication.
- Distinct source code so no interference from other remotes in the vicinity.
- Centurion devices are perfectly watertight.
- Output protection from short circuits & surges.
- Manufactured in highly resistant moulded plastic with a rubber shell for protection.
- The absence of mechanical elements enables functioning in unfavourable environments, with a temperature range from -20°C to +55°C.



Part no: CENT12/242FCT - Centurion Remote

54

ROLLER FAIRLEAD



Part No: RFF400-CAD
Chrome 4 Way Roller Fairlead For Winches Up to 4500 lb.

ROLLER FAIRLEAD



Part No: RFS150-CAD
Stainless Fairlead With Hole Centres 255mm.

ALUMINIUM FAIRLEADS



ALI450-CAD - 2500/3500 Winch.
ALXT450-CAD - 4500 XT Winch.

ALUMINIUM FAIRLEADS



ALI950-CAD - 9500SD Winch.
ALI015-CAD - 8000/9500/12000 Winch.

HOOK & RELEASE PIN



CHK014-CAD - 1/4 Steel Hook
CHK038-CAD - 3/8 Steel Hook
CHK516-CAD - 5/16 Steel Hook

2T PULLEY BLOCK



Part No: PBK300-CAD
2 Tonne Pully Block Hook Type.

4T PULLEY BLOCK



Part No: PBK900-CAD
4 Tonne Swingway Pully Block.

8T PULLEY BLOCK



Part No: PBK150-CAD
8 Tonne Swingway Pully Block.

WINCH KIT



Part No: AWK001-CAD
Warrior Bag, 1m Strop, 1/4 Shackle, 4T Pully Block.

WINCH KIT PRO



Part No: LWK001-CAD
Warrior bag, 2m Strop, Gloves, 4.75 Shackle, 8T Pully Block.

WINCH COVER SMALL



Part No: SWC001-CAD
ATV Small Winch Cover.

WINCH COVER



Part No: LWC003-CAD
Winch Cover For Heavy Duty Winches up to 13000lbs.

SHACKLES

SHK325-CAD - 3.25 Tonne Shackle.
SHK475-CAD - 4.75 Tonne Shackle.

TREE STROP

Part No: STP002-CAD
2m x 60mm - 14 Tonne tree strop.

WINCH STOPPER

Part No: RWS001-CAD
Rubber removable winch stopper.

PORTABLE BUMPER

Part No: PWM001-CAD
Portable bumper.

INSTALLATION PLATE

Part No: IST900-CAD
Winch installation plate for
Winches up to 9 000lb.

INSTALLATION PLATE

Part No: IST500-CAD
Winch installation plate for 9500
SD Winches.

INSTALLATION PLATE

Part No: IST600-CAD
Winch installation plate for
Winches up to 15 000lb.

INSTALLATION PLATE

Part No: IST200-CAD
Winch installation plate for
Winches up to 20 000lb.

WIRED REMOTE

Part No: HRO001-CAD
Toggle (WARN Type) Hand Held
Wired Remote.

WIRED REMOTE

Part No: HRO002-CAD
Hand held remote for XT and A
Series (air socket).

ATV HANDLEBAR REMOTE

Part No: ATR001-CAD
ATV / Quad Handlebar Remote.

WIRELESS REMOTE

Part No: CPW001-CAD
Wireless Remote Control With Key
Fob Handset / Air Socket.

WIRELESS REMOTE

Part No: EWX001-CAD
Heavy Duty Wireless Remote
Control / NO Socket.

WIRELESS REMOTE

Part No: EWX002-CAD
Heavy Duty Wireless Remote
Control with Socket.

WIRELESS REMOTE

Part No: EWX003-CAD
Wireless Remote Control for XT
and A series (Air Socket).

ATV CONNECTOR

Part No: AIRS01-CAD
ATV to Standard Socket
Connector.

Y CABLE

Part No: AIRS02-CAD
Y Cable For Dual Connection.

SOLENOID SET

Part No: ATC012-CAD
Solenoid Set For Up to 4500lbs
Winch.

ISOLATION SWITCH

Part No: BAT001-CAD
Battery Isolation Switch.

EXTENSION SOCKET

Part No: EXT001-CAD
Solenoid Box Extension Socket.

HD CONTACTOR

Part No: CON012-CAD
12v Heavy Duty Contactor.

WINCH UPGRADE KIT

Part No: AUK001-CAD
Universal 12v Winch Upgrade Kit &
Mini Thumbswitch.

SNAP CONNECTOR

Part No: QCC400-CAD
400 amp Snap Connector.

6.5 HP 12V MOTOR

Part No: EPW012-CAD
6.5 HP 12v Motor.



DK2 USA WEST
4301 S Valley View Blvd,
Suite 10-11 , Las Vegas,
Nevada, 89103, United States

DK2 CANADA
1080 Clay Avenue,
Unit 2, Burlington, Ontario,
L7L 0A1 , Canada

DK2 USA EAST
3750 South Avenue,
North Unit, Toledo, Ohio
43615, United States

TEL: 1-888-277-6960 WWW.DETAILK2.COM