

DK2 CANADA 1080 Clay Avenue, Unit 2, Burlington, Ontario, L7I 0A1 , Canada DK2 USA 6245 Industrial Parkway Whitehouse, Ohio, 43571, United States

TEL: 1-888-277-6960 WWW.DETAILK2.COM





Detail K2 Warrior Winches are the #1 selling brand of winches in Europe and are now proudly available in North America. In partnership with our distributors we supply the North American market with a complete range of electric, worm drive, and hydraulic winches.

DK2 WARRIOR WINCHES

In the most extreme conditions, when lesser products might be found wanting, DK2 Warrior Winches will deliver what your customer demands and our service levels will raise the bar in the process.

Whatever the requirement and whatever the vehicle we can supply a DK2 Warrior Winch that will provide exceptional performance and be backed by only the highest level of customer service and after sales support thus our motto" Value Without Compromise".

Value for money specification

Features



At Detail K2 Inc. we recognize that our customers want an all-inclusive price and do not want the bother of searching through a long, expensive extras list. It's for this reason that each one of our Winches is supplied as standard, with a specification that translates into exceptional value for your hard earned money.

Highest quality motors are the powerhouse, 3 stage Planetary Gears provide the right ratios for any task. Our water resistant solenoids and fully sealed housings deliver reliability in the field regardless of what Mother Nature throws your way.

Limited Lifetime Warranty



It shouldn't come as a surprise that every DK2 Warrior Winch is backed by a no quibble Limited Lifetime Warranty. We are so confident in our product that in the unlikely event something should go wrong there will be a simple and direct commitment to rectifying the problem. It's this integrity that translates into knowing our service and reputation will deliver when called on.

A 1 year warranty if offered for commercial and industrial applications. For more warranty information please visit our website at www.detailk2.com





Ideal for large ATV's and small trailers. A huge high power motor, heavy duty clutch, heavy duty steel gearing and heavy duty waterproof contactors ensure the ultimate in performance and reliability. Strengthened Steel drum makes it ideal to use with Synthetic Rope.

Watertight 4 Pin connection allows the use of 'Plug and Play' Wireless.

NINJA SERIES

NINJA SERIES ATV WINCHES

Item Numbers: C2500N, C2500N-SR C3500N, C3500N-SR

FEATURES

- Sealed High Power Motor
- Heavy Duty Watertight Contactors
- Full Steel Planetary Gearing
- Strengthened Steel Drum (suitable for Synthetic rope)
- Watertight Controller Socket
- Gloss Chip Resistant Paint

SPECIFICATION

C2500N

RATED LINE PULL: 2500lbs(1134kg) **MOTOR: 12v:** 1.35hp / 0.95kw

GEARING: 170:1 **BRAKING ACTION:** Dynamic **DRUM SIZE Dia x L:** 1.5 x 3.1" **CABLE Dia x L:** 0.2" x 46 ft **MOUNT PATTERN:** 3.1"

DIMENSIONS: 13.2 × 4.4 × 6.5"

C3500N

RATED LINE PULL: 3500lbs (1588kg) **MOTOR: 12v:** 1.95hp / 1.37kw

 GEARING:
 170:1

 BRAKING ACTION:
 Dynamic

 DRUM SIZE Dia x L:
 1.5 x 3.1"

 CABLE Dia x L:
 0.2" x 42 ft

 MOUNT PATTERN:
 3.1"

DIMENSIONS: 13.7 × 4.6 × 6.5"

INCLUDED

• Steel Cable

Synthetic version available

- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- 3 Tonne Pulley Block
- Mounting plate & Hardware
- 1/4 hook







High quality three stage planetary gearing ensure this is one of the quietest and smoothest winches on the market.

The silky smooth performance and the full load holding brake make it the perfect solution for high spec applications.

Synthetic version available

NIN S



SPECIFICATION

RATED LINE PULL: 4500lbs (2041kg) **MOTOR: 12v:** 1.95hp / 1.37kw

GEARING: 172:1

BRAKING ACTION: Auto in the drum

 DRUM SIZE Dia x L:
 1.7×3.8 "

 CABLE Dia x L:
 0.25" $\times 47.5$ ft

 MOUNT PATTERN:
 5×3.7 "

DIMENSIONS: 14.4 × 4.9 × 6.4"

WEIGHT: 28.6 lbs

Layer of	Line pull
wire rope	lbs (kg)
1	4500 (2401)
2	3642 (1652)
3	3060 (1388)
4	2638 (1196)

Line pull	Line speed		Amp	draw
lbs (kg)	ft/min	m/min	12v	24v
0	11.6	3.6	20	15
1500 (680)	9.2	2.8	70	40
2500 (1134)	7.8	2.4	100	65
3500 (1587)	6.6	2.0	140	80
4500 (2041)	4.9	1.5	200	130

NWAR

NINJA SERIES
TRAILER WINCHES

Item Numbers: C4500N C4500N-SR

FEATURES

- Power in and Power out
- High Torque 1.95hp Motor
- HD Waterproof Contactors
- Full Steel Planetary Gearing
- Mount Plate as Standard
- Full Load Holding Break
- Can fit tow ball mount

- 0.25" x 47.5ft Steel Cable
- 3m Remote Handset
- · Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- Mounting plate
- Mounting hardware
- 3/8 hook
- *ATV remote available







Warrior Winches are delighted to announce the arrival of the new member of Spartan Series, Tough, Strong and ready for Battle. The Spartan 6000 Lb short drum model is ideal where space and payload are limited. The winch has a short drum and is less than 66Lbs, however the extended drum supports allow it to carrier up to 131ft of 0.28" cable. The Synthetic rope version comes fitted with 0.27" x 98ft.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

With great performance, outstanding features included as standard, & backed by the Warrior Winches un-rivalled limited Lifetime Warranty, this should make a Spartan the first choice for all serious enthusiasts.

SPECIFICATION

RATED LINE PULL: 6000 lbs (2727kg) **MOTOR: 12V:** 4.5hp / 3.4kW

GEARING: 230:1

DRUM SIZE Dia x L: 2.48 × 4.2"

CABLE Dia x L: 0.28" × 131'

DIMENSIONS: 17.4 × 7.7 × 10.8"

WEIGHT: 66 lbs



Steel Cable version available

Layer of wire rope	Line Pull lbs (kg)	Cable Cap ft (m)
1	6000 (2727)	9.8 (3.0)
2	4979 (2258)	22.0 (6.7)
3	4255 (1930)	36.1 (11.0)
4	3714 (1685)	52.2 (15.9)
5	3296 (1495)	70.5 (21.5)
6	2962 (1344)	90.9 (27.7)
7	2690 (1220)	113.2 (34.5)
8	2463 (1117)	131.2 (40.0)

Line speed		Amps
ft/min	m/min	12v
19.4	5.9	80
13.1	1.0	140
9.2	2.8	210
7.2	2.2	285
	19.4 13.1 9.2	19.4 5.9 13.1 1.0 9.2 2.8

SPARTAN

SPARTAN 6000 ELECTRIC WINCH

Item Numbers: 6000 6000-SR

FEATURES

- Weather Sealed High Performance Motor
- Heavy Duty 3 Stage Gearbox
- Heavy Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch is 100% Load Tested
- Chip Resistant Gloss Paint Finish

- 10ft Remote Handset
- 5/16 Hook
- Aluminium or Roller Fairlead (Synthetic rope or steel cable)
- Heavy Duty Battery Leads
- Stainless Steel Mounting Hardware
- 0.27" x 98ft Synthetic Rope or 0.28" x 131ft Steel Cable







We are delighted to announce the arrival of the Spartan Series, Tough, Strong and ready for a Battle, these Winches really will challenge all before them. We have reluctantly termed them as 'entry level', however this describes the price point, not the performance.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

SPECIFICATION

8000

RATED LINE PULL: 8000lbs(3629kg) MOTOR: 12v: 4.6hp / 3.2kw **GEARING:** 233:1

BRAKING ACTION: Auto in the drum DRUM SIZE Dia x L: 2.5 x 8.8" CABLE Dia x L: 0.3" x 85 ft MOUNT PATTERN: 10 x 4.5" **DIMENSIONS:** 21.3 x 6.3 x 8.6"

Synthetic versions

available

9500

RATED LINE PULL: MOTOR: 12v: 4.6hp / 3.2kw **GEARING:** 230.1 **BRAKING ACTION:**

DRUM SIZE Dia x L: CABLE Dia x L: **MOUNT PATTERN:**

DIMENSIONS:

9500lbs(4500kg)

Auto in the drum

2.5 x 8.8" 0.36" x 82 ft 10 x 4.5"

21.3 x 6.3 x 8.6"

12000

12000lbs (5400kg) 6.0hp / 4.6kw 230:1 Auto in the drum 2.5 x 8.8" 0.4" x 82 ft 10 x 4.5"22.8 x 6.3 x 8.6"

SPARTAN

SPARTAN SERIES **ELECTRIC WINCH**

Item Numbers: 8000, 8000-SR 9500, 9500-SR 12000, 12000-SR

FEATURES

- Weather Sealed High Performance motor
- Heavy-Duty 3 Stage Gearbox
- Heavy-Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch 100 % load tested
- Chip Resistant Gloss Paint Finish

- Galvanized steel cable
- 10ft Remote Handset
- · Heavy Duty Steel Roller Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- Clevis hook







Superb high specification winch. Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing.

Comes with stainless steel roller fairlead and fittings as standard. Complete with Heavy Duty integrated wireless remote. Available with Armortek Synthetic Rope and Aluminum Fairlead.

Synthetic version available

SPECIFICATION

S8000

RATED LINE PULL: 8000lbs(3629kg) 4.6hp / 3.2kw 4.6hp / 3.2kw 210:1 2.5×8.8 " 2.5×8.8

S9500

8000lbs(3629kg) 9500lbs(4500kg) 4.6hp / 3.2kw 4.6hp / 3.2kw 210:1 230:1 Auto in the drum 2.5 x 8.8" 2.5 x 8.8" 0.3" x 95 ft 0.4" x 85 ft 10 x 4.5" 21.3 x 6.3 x 8.6" 21.3 x 6.3 x 8.6"

S12000

22.8 x 6.3 x 8.6"

RATED LINE PULL:12000lbs(5400kg)MOTOR: 12v:6.5hp / 4.6kwGEARING:230:1BRAKING ACTION:Auto in the drumDRUM SIZE Dia x L: 2.5×8.8 "CABLE Dia x L:0.4" $\times 85$ ftMOUNT PATTERN: 10×4.5 "

SANURAK

SAMURAI SERIES ELECTRIC WINCH

Item Numbers: \$8000, \$8000-\$R \$9500, \$9500-\$R, \$12000, \$12000-\$R

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



DIMENSIONS:





The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing.

Complete with heavy duty integrated wireless remote. Available with Steel Rope or Armortek Synthetic Rope and Aluminum Fairlead.



Steel Cable version available

SPECIFICATION

RATED LINE PULL: 9500lbs(4500kg) **MOTOR: 12v:** 6.5hp / 4.5kw

GEARING: 110:1

BRAKING ACTION: Auto in the drum

 DRUM SIZE Dia x L:
 2.5×8.8 "

 CABLE Dia x L:
 0.4" $\times 98$ ft

 MOUNT PATTERN:
 10×4.5 "

 DIMENSIONS:
 $22.7 \times 6.3 \times 8.5$ "

Layer of	Line pull
wire rope	lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5400 (2400)

Line pull	Line speed		Amp	draw
lbs (kg)	ft/min	m/min	12v	24v
0	65	19.8	80	45
4000 (1818)	12.5	3.8	300	175
6000 (2722)	11.81	3.6	400	230
9500 (4309)	8.86	1.9	530	335

SAWURAK

SAMURAI 9,500 LB HIGH SPEED PERFORMANCE WINCH

Item Numbers: \$9500HS \$9500HS-SR

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Integrated Wireless Remote

- Wire rope 0.4" x 98ft
- 10ft Remote Handset
- Roller Fairlead (does not attach to winch)
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook







The narrow drum version of the best selling 9500. A total width of 17.2 inches ensures this is the perfect product for limited space. The 5.0hp motor delivers 9500lb of pulling power in space normally designed for Winches with half the power.

The Short Drum winch is the preferred choice of the British Military on specialist vehicles currently serving in action. Available with synthetic rope and aluminium fairlead, to give a total weight of 44 lbs.

Steel Cable version available

SPECIFICATION

RATED LINE PULL: 9500lbs(4500kg) **MOTOR: 12v:** 5.0hp / 3.5kw

GEARING: 230:1

BRAKING ACTION: Auto in the drum

DRUM SIZE Dia x L: 2.5×4.7 " 0.4" $\times 46$ ft **MOUNT PATTERN:** 5.9×4.5 " $17.2 \times 6.3 \times 10.7$ "

Layer of	Line pull
wire rope	lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5593 (2537)

Line pull	Line speed		Amp	draw
lbs (kg)	ft/min	m/min	12v	24v
0	23	7	80	70
3000 (1361)	12.5	3.8	170	140
6000 (2722)	9.8	3	260	210
9500 (4309)	6.4	1.9	380	270

SAWURAK

SAMURAI 9,500 LB SHORT DRUM WINCH

Item Numbers: S9500SD S9500SD-SR

FEATURES

- Power in and Power out
- High Quality 5.0hp Series Wound Motor
- Heavy Duty Waterproof Contactors
- Full Steel Planetary Gearing
- Double sealed motor and drum
- Full Load Holding Brake
- Integrated Wireless remote

- 0.4" x 46ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook







Warrior Winches are excited to announce the arrival of the colossal Samurai 17500 & 20000lb Winches. Designed for the toughest of applications & tested in the most extreme environments imaginable, these Winches boasts a massive 7.0 & 7.5 hp Series wound motors respectively.

Double sealed drum on maintenance free bearings and quiet, fully sealed efficient full steel planetary gearing ensures these immense Warriors are ready for any battle.

SPECIFICATION

S17500 Winch

RATED LINE PULL: 17 500lbs (7938kg) **MOTOR: 12v:** 7.0hp / 4.9kw

GEARING: 430:1

BRAKING ACTION: Auto in the drum

 DRUM SIZE Dia x L:
 3.5×8.6 "

 CABLE Dia x L:
 0.5" $\times 85$ ft

 MOUNT PATTERN:
 10×4.5 "

 DIMENSIONS:
 $24 \times 8.5 \times 10$ "

 WEIGHT:
 147.7 lbs

\$20000 Winch

RATED LINE PULL: 20 000lbs (9072kg) **MOTOR: 12v:** 7.5hp / 5.4kw

7.511p / 5.4kl

GEARING: 430

BRAKING ACTION: Automatic in the drum

 DRUM SIZE Dia x L:
 3.5×8.6 "

 CABLE Dia x L:
 0.47" $\times 87$ ft

 MOUNT PATTERN:
 10×4.5 "

 DIMENSIONS:
 $24 \times 8.6 \times 10.7$ "

 WEIGHT:
 158.7 lbs



SAMURAI 17500 & 20000 LBS WINCHES

Item Numbers: \$17500 \$20000

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Reinforced Plastic Contactor Cover
- Double Sealed Drum (G-box/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- High Quality Steel Drum Supports

- 0.5" x 85ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Wireless Remote





The Predator is designed for hard-core competition. Two powerful 7.2HP sealed motors provide a performance that is truly out of this World, coupling this with a 108:1 ratio 3 stage planetary gearbox enables this performance winch to handle even the most extreme offroad punishment.

With a surprisingly low draw of only 140 amps (at no load), the Predator also contains an innovative "multi stop" 10% ratchet brake design, which provides zero drag when returning the "cable in", and is situated away from the drum to prevent any damaging heat transferring to your Armortek or Synthetic rope.

The steel drum flanges are precision machined to 0.39" on either side to resist the unique loading characteristics of synthetic rope, while the Alloy Carbon gears are heat treated and tempered to 62HRc rating for extra strength. This Warrior from another dimension will mercilessly prey on its weaker rivals, hunting the opposition down. At 10kg lighter than any of its nearest competitors, with off-load line speeds from 65ft per minute & available with or without synthetic rope, there's a Predator out there, ready & waiting, for everyone!

SPECIFICATION

RATED LINE PULL: 10 000lbs (4536kg)

MOTOR: 12v: 7.2hp / 5.4kw

GEARING: 108:1

DRUM SIZE Dia x L: 2.8×8.42 "CABLE Dia x L:0.35" \times 124ftMOUNT PATTERN: 10×4.5 "

DIMENSIONS: 18.8 x 10.3 x 13.9"

WEIGHT: 99lbs

Layer of wire rope	Line pull lbs (kg)	Total Rope on drum ft(m)
1	10000 (4536)	18.4 (5.6)
2	8153 (3698)	41.0 (12.5)
3	6881 (3131)	68.9 (21)
4	5953 (2700)	101 (30.8)
5	5245 (2379)	131.2 (40)

Line pull	Line speed	Amp draw
lbs (kg)	ft(m)/min 12v	12v
0	66 (20)	140
4000 (1816)	19.7 (6.0)	400
6000 (2722)	16.7 (5.1)	560
8000 (3629)	13.1 (4.0)	690
10000 (4536)	10.5 (3.2)	790



PREDATOR 10,000 LB
DUAL MOTOR
PERFORMANCE WINCH

Item Number: P10000D-SR

FEATURES

- Dual 7.2HP (5.4KW) Sealed Motors
- Sealed Motor conforms to IP67
- Sealed Waterproof Contactor
- "Multi Stop" 10% Ratchet Brake Design
- Sealed 3 Stage Planetary Gears
- Alloy Carbon Gears hardened to 62HRc Rating
- No load speed of 65ft/min

- 0.35" x 124ft Synthetic Armortek Rope
- Wireless remote with LCD Display
- Heavy Duty Remote Control
- Silver Warrior Aluminum Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- 12 Ton Competition Hook







Compact, tough. A hydraulic winch for industrial and commercial applications. The unique patented steel gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding. Stainless steel roller fairleads and fittings are standard.

SPECIFICATION

10 000 NH HYDRAULIC Winch

RATED LINE PULL: 10 000lbs (4536kg) **MAX LINE PULL:** 12 500lbs (5670kg) **MOTOR:** Hydraulic Dis 50 ml/r

GEARING: 33:1

15 000 NH HYDRAULIC Winch

RATED LINE PULL: 15 000lbs (6804kg)
MAX LINE PULL: 17 000lbs (7711kg)
MOTOR: Hydraulic Dis 80 ml/r

GEARING: 37:1

DRUM SIZE Dia x L: 3.5×8.8 ° CABLE Dia x L: 0.5×87 ft MOUNT PATTERN: 10×4.5 °

DIMENSIONS: 20.9 x 8.1 x 9.7"



NH SERIES HYDRAULIC WINCHES

Item Numbers: 10000NH 15000NH

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Stainless Steel fairlead and Fittings
- Rugged and compact for Long Life

- Steel cable (see below)
- Heavy Duty Roller Fairlead (10000/15000NH)
- 5/16 or 3/8 Hook







Compact, tough. A hydraulic winch for industrial and commercial applications. The special heat treated planetary gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding.

SPECIFICATION

10 000 NW Winch

RATED LINE PULL: 10 000lbs (4536ka) MAX LINE PULL: 12 500lbs (5670kg) MOTOR: Hydraulic Dis 100.8 ml/r

GEARING: 16:1

DRUM SIZE Dia x L: 3.9 x 9.9" 1/2" x 86 ft CABLE Dia x L:

MOUNTING: 14.6 × 4.5" (11.34 × 4.5") DIMENSIONS: 25 x 10.33 x 9.39"

15 000 NW Winch

RATED LINE PULL: 15000lbs(6810kg) **MAX LINE PULL:** 17 500lbs (7954kg) **MOTOR:** Hydraulic Dis 160 ml/r

17.2:1 **GEARING: DRUM SIZE Dia x L:** 5 x 10.6" CABLE Dia x L:

0.6" x 92 ft

11.9 x 4.5" (14.5 x 4.6") **MOUNTING:**

DIMENSIONS: 28.2 x 11.1 x 12"



NW SERIES HYDRAULIC WINCHES

Item Numbers: 10000NW 15000NW

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Rugged and Compact for Long Life
- Meets the requirements of SAE J706

- 86 ft x 1/2" steel cable
- 5/16 Hook
- Tensioner included









Tough and compact, the JP series are heavy duty hydraulic winches designed and tested for toughest applications.

Minimum rope to drum ratio of 10:1, multi disc frictional brake, balance valve and rope tensioner as standard.

Available from 10 tonne to 40 tonne. Manufactured to meet GJB82-86 National Military Standard.



JP SERIES HYDRAULIC WINCHES

Item Numbers: 10TJP, 13.5TJP, 15TJP 20TJP, 30TJP, 40TJP

FEATURES

- Full Float Heavy Duty Planetary Gearing
- Multi Disc Friction Brake
- Minimum 10:1 Rope/Drum Ratio
- High Torque Industrial Motor
- Air and Manual Clutch Operation

SPECIFICATION

10TJP RATED LINE PULL (btm layer): 10 000 kg

22046 lbs

5 Mpa

20 Mpa

5.4x12.4"

363 lbs

15-75 L/min

157ft x 0.6"

WORKING SPEED (btm layer): 21.6ft/min* **ARRESTER RESP PRESS: WORKING PRESSURE: OIL FLOW: DRUM SIZE: REC ROPE SIZE: WEIGHT:**

13.5**TJP** 15TJP

13 500 kg 29762 lbs 24.6ft/min <2.5 Mpa 17 Mpa 110 L/min 131ft x 0.7"

15 000 kg 33069 lbs 20ft/min <2.5 Mpa 17 Mpa 110 L/min 15.7x8.3x13.4" 15.7x8.3x13.4" 230ft x 0.9" 628 lbs

578 lbs

20TJP RATED LINE PULL (btm layer): 20 000 kg

44092 lbs WORKING SPEED (btm layer): 20ft/min **ARRESTER RESP PRESS:** <2.5 Mpa **WORKING PRESSURE:** 17 Mpa OIL FLOW: 120 L/min **DRUM SIZE: REC ROPE SIZE:** 197ft x 1" **WEIGHT:** 650 lbs

30TJP

30 000 kg 66138 lbs 18ft/min <2.5 Mpa 17 Mpa 120 L/min 20.9x8.3x13.4" 20.9x11x14.2" 197ft x 1.3" 1257 lbs

40TJP

40 000 kg 88184 lbs 10ft/min <2.5 Mpa 17 Mpa 120 L/min 23.7x11x18.9" 213ft x 1.4" 1763 lbs

- Heavy Duty Rope Tensioner as Standard
- Balance Valve as Standard





WIDE RANGE AVAILABLE

AMORTEK WINCH ROPE

N C H

Armortek synthetic rope is 70% stronger than wire!

- Armortek weighs 6 times less than wire.
- Unlike wire, Armortek will not whiplash if broken.
- Armortek is rated at 70% stronger than wire.
- Armortek floats, wire doesn't.
- Armortek is coated to prevent abrasion.
- You don't have to worry about wire splinters.

Diameter	6mm (3/16")	9.5mm (3/8")
Breaking	3200 kg	7500 kg
Load	(7040 Lb)	(16500 Lb)

Part no: HW0884-CAD: 6mm x 16m (1/4" X 50') Synthetic Rope Part no: HW0932/45-CAD: 10mm x 14m (3/8"x 45') Synthetic Rope Part no: HW0932/85-CAD: 10mm x 26m (3/8" x 85') Synthetic Rope

CENTURION WIRELESS REMOTE



The ultimate remote for the professional user.

- Two-way Closelink wireless communication.
- Distinct source code so no interference from other remotes in the vicinity.
- Centurion devices are perfectly watertight.
- Output protection from short circuits & surges.
- Manufactured in highly resistant moulded plastic with a rubber shell for protection.
- The absence of mechanical elements enables functioning in unfavourable environments, with a temperature range from -20°C to +55°C.



Part no: CENT12/242FCT - Centurion Remote

ROLLER FAIRLEAD

ROLLER FAIRLEAD



Part No: RFS150-CAD Chrome 4 Way Roller Fairlead For Stainless Fairlead With Hole Centres 255mm

ALUMINIUM FAIRLEADS



ALI450-CAD - 2500/3500 Winch . ALXT450-CAD - 4500 XT Winch.

ALUMINIUM FAIRLEADS



ALI950-CAD - 9500SD Winch. ALI015-CAD - 8000/9500/12000

HOOK & RELEASE PIN

Part No: RFF400-CAD

Winches Up to 4500 lb.

2T PULLY BLOCK



Part No: PBK300-CAD 2 Tonne Pully Block Hook Type.

4T PULLY BLOCK



Part No: PBK900-CAD 4 Tonne Swingway Pully Block.

8T PULLY BLOCK



Part No: PBK150-CAD 8 Tonne Swingway Pully Block.

WINCH KIT

Warrior Bag, 1m Strop, 1/4 Shackle,

CHK014-CAD - 1/4 Steel Hook

CHK038-CAD - 3/8 Steel Hook

CHK516-CAD - 5/16 Steel Hook

WINCH KIT PRO



Warrior bag, 2m Strop, Gloves,

WINCH COVER SMALL



Part No: SWC001-CAD ATV Small Winch Cover.

WINCH COVER



Part No: LWC003-CAD Winch Cover For Heavy Duty Winches up to 13000lbs.

Part No: AWK001-CAD

4T Pulley Block.

SHACKLES

TREE STROP

WINCH STOPPER

PORTABLE BUMPER



SHK325-CAD - 3.25 Tonne Shackle. SHK475-CAD - 4.75 Tonne Shackle.



Part No: STP002-CAD 2m x 60mm - 14 Tonne tree strop.



Part No: RWS001-CAD Rubber removable winch stopper.



Part No: PWM001-CAD Portable bumper.

INSTALLATION PLATE

INSTALLATION PLATE

INSTALLATION PLATE

INSTALLATION PLATE



Part No: IST900-CAD Winch installation plate for Winches up to 9 000lb.



Part No: IST500-CAD Winch installation plate for 9500 SD Winches.



Part No: IST600-CAD
Winch installation plate for
Winches up to 15 000lb.



Part No: IST200-CAD Winch installation plate for Winches up to 20 000lb.

WIRED REMOTE

WIRED REMOTE

ATV HANDLEBAR REMOTE

WIRELESS REMOTE



Part No: HRO001-CAD Toggle (WARN Type) Hand Held Wired Remote



Part No: HRO002-CAD Hand held remote for XT and A Series (air socket).



Part No: ATRO01-CAD ATV / Quad Handlebar Remote.



Part No: CPW001-CAD Wireless Remote Control With Key Fob Handset / Air Socket.

WIRELESS REMOTE



Part No: EWX001-CAD Heavy Duty Wireless Remote Control / NO Socket.

WIRELESS REMOTE



Part No: EWX002-CAD Heavy Duty Wireless Remote Control with Socket.

WIRELESS REMOTE



Part No: EWX003-CAD Wireless Remote Control for XT and A series (Air Socket).

ATV CONNECTOR



Part No: AIRS01-CAD ATV to Standard Socket Connector

Y CABLE

SOLENOID SET

e de



Part No: ATC012-CAD Solenoid Set For Up to 4500lbs Winch.

ISOLATION SWITCH



Part No: BAT001-CAD Battery Isolation Switch.

EXTENSION SOCKET



Part No: EXTO01-CAD Solenoid Box Extension Socket.

HD CONTACTOR

Y Cable For Dual Connection.



Part No: CON012-CAD 12v Heavy Duty Contactor.

Part No: AIRSO2-CAD

WINCH UPGRADE KIT



Part No: AUKOO1-CAD Universal 12v Winch Upgrade Kit & Mini Thumbswitch.

SNAP CONNECTOR



Part No: QCC400-CAD 400 amp Snap Connector.

6.5 HP 12V MOTOR



Part No: EPW012-CAD 6.5 HP 12v Motor.



DK2 CANADA 1080 Clay Avenue, Unit 2, Burlington, Ontario, L7l 0A1 , Canada DK2 USA 6245 Industrial Parkway Whitehouse, Ohio, 43571, United States

TEL: 1-888-277-6960 WWW.DETAILK2.COM