Indoor/Outdoor UL507 Certified Wall, Ceiling or Pole Mount Fan

The Indoor/Outdoor POW (Premium Outdoor Waterproof) fan from J&D Manufacturing is a durable, three-speed, waterproof fan. These fans come pre-wired for 115 Volts with an 8′ cord and 3-prong plug for "No Electrician+ Needed" installation.
These fans are perfect in areas around the farm that may come in contact with rain, humidity, and water spray.

No electrician needed!
Hang it up
Plug it in

POW18B

POW18

3 Speed

Features

- 18″ model available in white or black
- High output performance
- 3-speed pull chain
- Attached 8′ cord with 3-prong plug pre-wired for 115 Volts
- Versatile powder coated mounting bracket allows for easy tilt and swivel of fan to quickly change direction and angle of air movement, a perfect work station fan
- UL507 certified for indoor and outdoor use
- Aluminum blades
- Direct drive quiet operation
- Corrosion-resistant, powder coated fan guards meet OSHA 1910.212(a)(5) requirements for installation at any height
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a **1 Year Warranty**
- Rated for use with our misting/fogging products to increase cooling abilities

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/ Watt	Drive	Prop
Single Phase							
White							
POW14	14″	1	3(H)	**1,090**	**13.6**	Direct	3-Alm
			(M)	**1,000**	**15.2**		
			(L)	**870**	**15.5**		
POW18	18″	1	3(H)	**2,210**	**13.9**	Direct	3-Alm
			(M)	**1,870**	**13.4**		
			(L)	**1,420**	**12.7**		
Black							
* POW18B	18″	1	3(H)	**2,210**	**13.9**	Direct	3-Alm
			(M)	**1,870**	**13.4**		
			(L)	**1,420**	**12.7**		
Optional Bracket							
POWTPB	Bracket, Post/Pole, White Powder Coat, w/U-bolt & Hdwr						

* Best sellers/recommended models

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

+GFCI (Ground Fault Circuit Interrupter) recommended on all circuits

POWTPB - Optional Bracket for post or pole