

# Indoor/Outdoor UL507 Certified Oscillating Wall Mount Fan

The Indoor/Outdoor Wall Mount POW (Premium Outdoor Waterproof) fan from J&D Manufacturing is an oscillating, three-speed, waterproof fan with quiet operation. The POW Wall Mount fan includes a wall mount bracket and an attached 10' cord pre-wired for 115 volts so no electrician<sup>+</sup> is needed. These fans are perfect in areas around the farm that may come in contact with rain, humidity, and water spray.

<sup>+</sup>GFCI (Ground Fault Circuit Interrupter) recommended on all circuits

## Features

- Available in 24" and 30"
- Includes powder coated steel wall bracket
- High output performance and quiet operation
- 3-speed pull chain
- Attached 10' cord with 3-prong plug pre-wired for 115 Volts
- Range of oscillation – 93°
- UL507 certified for indoor and outdoor use
- Aluminum blades - painted
- Corrosion-resistant, powder coated fan guards meet OSHA 1910.212(a)(5) requirements for installation at any height
- Totally enclosed, maintenance-free, direct drive, high-efficiency motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a **1 Year Warranty**
- Rated for use with our misting/fogging products to increase cooling abilities
- Minimal assembly required

**3  
Speed**



**No electrician needed!  
Hang it up  
Plug it in**

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
<b>Single Phase</b>							
* POW24OSC	24"	1	3(H) (M) (L)	<b>3,470</b> 2,930 2,550	<b>13.1</b> 16.3 16.4	Direct	3-Alm
POW30OSC	30"	1	3(H) (M) (L)	<b>4,790</b> 3,960 3,310	<b>17.7</b> 20.6 20.7	Direct	3-Alm

\* Best sellers/recommended models

^ Variable speed fans require separate variable speed control to adjust fan speed

**Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12**