

POWERMATE®

PORTABLE GENERATORS

DUAL FUEL

4500 - 7500 WATT SERIES

Ideal for use around the home or the next DIY project, the PM4500DF and PM7500DF Dual Fuel portable generators are the ideal portable power solution. Featuring Dual Fuel functionality, the PM4500DF and PM7500DF are capable of running on either gasoline or an LP gas fuel source with the simple turn of a dial. These generators are powerful enough to run small electrical appliances at any picnic, campground or tailgate and versatile enough to power tools for your next DIY project.



3-YEAR
LIMITED WARRANTY

POWERED BY GENERAC

PM4500DF

PORTABLE GENERATOR

GAS: 4500 STARTING WATTS | 3600 RUNNING WATTS
 LP: 4180 STARTING WATTS | 3240 RUNNING WATTS

IDEAL FOR*

RECREATION


WORK

EFFORTLESS STARTING
 With easy to use POWERDIAL™ or available One-Touch Electric Start*


POWERFUL & LIGHTWEIGHT
 High Output Portable Power

VERSATILE
 Enhanced features for multiple applications


LIGHTS




RADIO




FAN




TV




COFFEE MAKER




REFRIGERATOR




HAIR DRYER




SPACE HEATER



AIR COMPRESSOR (1HP)



AIR CONDITIONER



*Do not overload the generator. All devices may not be powered at the same time.

PM7500DF

PORTABLE GENERATOR

GAS: 7500 STARTING WATTS | 6000 RUNNING WATTS
 LP: 7180 STARTING WATTS | 5640 RUNNING WATTS

IDEAL FOR*

RECREATION

WORK


EMERGENCY BACKUP

EFFORTLESS STARTING
 With easy to use POWERDIAL™ or available One-Touch Electric Start*


DURABLE
 Heavy duty steel frame allows strong, stable operation

MULTIPLE DEVICES
 Maximum output for various applications and tools


LIGHTS




SUMP PUMP




SAW




TV




REFRIGERATOR




STOVE



SPACE HEATER



AIR COMPRESSOR (1HP)



*Do not overload the generator. All devices may not be powered at the same time.



*Product feature available on select models

*Product feature available on select models

SPECIFICATIONS

SERIES	PM4500DF	PM7500DF
Model #	P0081700	P0081800
Configuration	49 ST / CSA	49 ST / CSA
Starting Watts	4500 (Gas) / 4180 (LPG)	7500 (Gas) / 7180 (LPG)
Running Watts	3600 (Gas) / 3240 (LPG)	6000 (Gas) / 5640 (LPG)
Rated AC Voltage	120 VAC	120/240 VAC
Rated AC Frequency	60 Hz	60 Hz
Rated 120 VAC Amperage	30 (Gas) / 27 (LP)	50 / 25 (Gas) / 47 / 23.5 (LP)
Engine Displacement	224cc	420cc
Engine Type	OHV	OHV
Engine RPM	3600	3600
CO Shutdown	Yes	Yes
Recommended Oil	10W-30	10W-30
Lubrication Method	Splash	Splash
Choke Location	On Engine	On Engine
Fuel Shut Off	On Fuel Tank	On Fuel Tank
Starting Method	Recoil Pull Start	Recoil Pull Start
Low Oil Shutdown	Low Level	Low Level
Neutral Bonded to Ground	Yes	Yes
Start Switch Type	On/Off	On/Off
Fuel Selector	On Control Panel	On Control Panel
Start Switch Location	On Control Panel	On Control Panel
Fuel Tank Capacity Gal (L)	5 (18.9)	8 (30.3)
Run Time at 25% of Rated Load (Hours)	19 (Gas) / 14 (LPG)	14.5 (Gas) / 8.3 (LPG)
Run Time at 50% of Rated Load (Hours)	14 (Gas) / 10.5 (LPG)	11 (Gas) / 6 (LPG)
Warranty- Residential	3 Year Limited	3 Year Limited
Warranty- Commercial	90 Day	90 Day

* LP run times are based on use with a 20lb cylinder.

For more information, such as FAQ's,
visit us online at www.powermate.com

201905252 01/22

©2022 Powermate, LLC All Rights Reserved

Specifications are subject to change without notice.

Powermate, LLC.
S45W29290 Hwy. 59, Waukesha, WI 53189
1-800-445-1805

WWW.POWERMATE.COM