# **K&H Rectangle Booster Pet Seat**Assembly & Installation Instructions



Thank you for purchasing the Rectangle Booster Pet Seat by K&H Pet Products. This product was designed to elevate your pet for a better view while riding in the car and can help keep pets in place while operating a motor vehicle. When used properly, your Rectangle Booster Pet Seat will last for many years to come.


#### ASSEMBLY INSTRUCTIONS:


- Lay all parts of your Rectangle Booster Pet Seat out on a table. You should have a fabric cover, a 3 inch soft cushion with removable cover, 4 white foam pieces, and 4 white corner reinforcement stickers. See FIGURE 1.
  - Use this diagram in FIGURE 1 to identify each foam piece. The two foam pieces A in this diagram will form the two sloped side walls of the pet seat. Foam piece B in the diagram will form the back wall, and the "U" shaped foam piece **C** will form the front of the pet seat.
- Start by connecting one of the side walls (foam piece  ${\bf A}$ ) to the back wall (foam piece B). Note: Make sure the edge with the single notch on the side wall of A is facing down. See FIGURE 2.
- Next connect the second side wall (foam piece A) to the other side of the back wall (foam piece B). The single notch on the side wall of A should be facing down. See FIGURE 3.
- Finish closing the walls of the pet seat frame by connecting the front wall (foam piece C, the "U" shaped piece), to both side walls A. Locate the white corner reinforcement stickers and attach one of the stickers to one of the connecting edges. Overlap the sticker over the corner and press to adhere. See FIGURE 4. Add a corner reinforcement sticker to the remaining 3 corners of the pet seat's foam frame.
- Lay out the fabric cover and separate the seat's attached fleece interior section from its attached bottom section. Lay the fleece section to the side and place the foam frame into the bottom section of the other side. Pull the outer edges of the fabric cover over the bottom half of the foam frame. See FIG-**URE 5.** NOTE: The "U" shaped foam piece **C** is the front of the pet seat. It needs to face the fleece section of the cover before the cover is installed.
- Take the attached fleece section of the cover and lay it inside the foam frame. Pull the outer edges of the cover over the top half of the foam frame working your way around to the other side. See FIGURE 6.
- Make any final adjustments to the cover then zip the cover together. See FIGURE 7. Place the pillow inside the booster seat and it's now ready to be installed into your vehicle.


### VEHICLE INSTALLATION INSTRUCTIONS ON BACK:


#### **CARE INSTRUCTIONS:**


Remove pillow cover and machine wash on cold then line dry. To wash outer pet seat cover, unzip, remove all interior foam pieces, and machine wash then line dry.
















#### **K&H Limited One Year Warranty**

Our warranty is as follows: K&H Pet Products warrants to the original consumer, that this product will be free of defects and workmanship for a period of one year from the date of purchase. The manufacturer's liability hereunder is limited to replacement of the product. This warranty is void if the product has been damaged by accident, unreasonable use, neglect, tampering, or other causes not arising from defects in material and workmanship.

To exercise your warranty: If, during the warranty period, your product malfunctions, return it to the place of purchase with your original purchase receipt. If this cannot be done, return the product, postage prepaid, to K&H Pet Products, with a dated proof of purchase or original date receipt. A return authorization number can be obtained by calling (719) 591-6950 and must accompany all returns to manufacturer. Please include a note explaining the problem when returning the product.

## **K&H Rectangle Booster Pet Seat** Vehicle Installation Instructions

### VEHICLE INSTALLATION INSTRUCTIONS for the Rectangle Booster Pet Seat:

- To install the Rectangle Booster Pet Seat in your vehicle, lift the cushion out of the pet seat and thread the seat belt of the back seat through the side opening closest to you. See FIGURE 1.
- After the seat belt is in the interior of the car seat, run it through the sewn-in safety loop. See FIGURE 2. Once through the safety loop, thread the seat belt through the second opening on the opposite side of the pet seat.
- Grab the seat belt with your other hand and pull it through the opening on the far side of the pet seat and then snap the seat belt securely into the buckle. See FIGURE 3. Return the cushion to the pet car set.
- For added protection to help keep your pet in the car seat, it is always recommended to use the two provided leads located under the cushion while operating your motor vehicle. You can adjust the length of the leads for your specific pet. Attach the leads to either your pet's harness or collar. See FIGURE 4.







