

10 HP RS Series Open Rotary Screw

39 cfm @ 150 psi



Compressor Features

- Spin on separator
- Spin on oil filter
- Simplified operating controls
(No complicated micro-processor)
- Single control solenoid operation
- UL control components
- Alpha profile rotors
- Air/oil cooler
- Easy to remove bolt on oil cooler
- Standard operating pressure 150 psi
- Extended oil drain for easy service
- Factory filled with premium synthetic fluid
- ASME/CRN powder coated receiver
- Heavy duty air filter
- Automatic tank drain
- Smart contractor
- Vibration isolation pads
- Tank discharge ball valve
- Free freight in IG freight pre-paid area
- High air temperature switch
- Automatic belt tensioner
- 2pc tank and top plate



THE STATS:

Model Number	Phase	Voltage	Tank	Length	Width	Height
R101V83	1	208-230	80 Gallon Vertical	36	25	78
R103V83	3	208-230/460-480	80 Gallon Vertical	36	25	78
R101H83	1	208-230	80 Gallon Horizontal	78	26	50
R103H83	3	208-230/460-480	80 Gallon Horizontal	78	26	50
R101BM3	1	208-230	Basemount	36	26	30
R103BM3	3	208-230/460-480	Basemount	36	26	30

No Start Up Kit Required

Optional Lifetime Airend/Sump/Oil Cooler Warranty

See catalog for additional options

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2020

