



SUPERIOR
ACCESSORIES

BLACK DIAMOND

NO-FAIL MANUAL NOZZLE



◆ **Black Diamond Durability**

The *Black Diamond* endurance surface minimizes friction which allows the components to glide through each squeeze of the trigger. Nozzles fail because of friction and wear between the valve stem and trigger.

**THE MOST DURABLE,
BEST PERFORMING NOZZLE
ON THE PLANET**

DESIGNED TO LAST A LIFETIME



*Extended warranty coverage requires registration with GPI. Default warranty is 90 days. Visit gpi.net/product-registration/




Nozzles stay put with the improved security hook.



Easy to install with flat surfaces for a wrench to grip.



Quad-Ring™ upgrade: better sealing and lubrication retention.



LOWER PRESSURE DROP than previous models



equals BETTER FLOW performance

OLD VS NEW



Metal on metal contact creates friction and quickly wears surfaces.



The *Black Diamond* endurance surface minimizes friction and streamlines movement.

MADE IN THE U.S.A.

ASSEMBLED IN WICHITA, KS

Reshoring Efforts:

Bring nozzle production back to the United States from overseas.

MODELS / SPECIFICATIONS

CONSTRUCTION

Housing, Trigger, and Spout:	Diecast Aluminum
<i>Black Diamond</i> Endurance Surface:	Acetal
Valve Seal:	Viton
Stem Shaft Seal:	Quad-Ring™

TEMPERATURE RATING

-20°F (-29°C)

◆ Patent Pending

COMPATIBLE FLUIDS

Designed, tested and approved for use with gasoline, diesel fuel, and kerosene.

Surpassed Testing Standards



- ◆ UL cycle test requirement is 100,000 cycles
- ◆ GPI has surpassed this and still going strong

Part No.	Model No.	Description	Flow Rates	Spout Diameter	Discontinued SKUs
155000-01	M2-06N-U	¾ in. Manual Unleaded (MU)	Unleaded, up to 20 GPM	0.840 in.	Replaces 110155-1
155000-04	M2-08N-D	1 in. Manual Diesel (MD)	Leaded and Diesel, up to 35 GPM	0.937 in.	Replaces 110155-4