



CAT[®]

POWER TOOLS





THE NAME YOU KNOW.
NOW IN YOUR TOOL BOX.

Globally, the Cat® brand is recognized for its grit and toughness. Cat® power tools are here to bring that legendary reputation to professional contractors, with advanced engineering and superior build quality to take on the most difficult applications.

PREPARE FOR THE REVOLUTION

18V GRAPHENE BATTERY™

THE FUTURE OF TOOL POWER HAS ARRIVED.



4x

THE BATTERY LIFE CYCLE

3x

FASTER CHARGING

2x

HIGHER AMP DRAW

1+ ALL


SINGLE BATTERY FOR ALL

18V GRAPHENE™

HIGHER ELECTRICAL CONDUCTIVITY

HIGH HEAT CONDUCTANCE

FASTER CHARGING CELLS



SLIDE LOCK STORAGE TECH



TRANSPORT. PROTECT. ORGANIZE.

Tools are your livelihood. Slide Lock modular storage system brings organization to the job site! Engineered with impact resistant materials these kits withstand the toughest jobsite conditions. The innovative locking technology connects kits quickly for easy transport.



ENGINEERED TO CONNECT & PROTECT



SLIDE LOCK CONNECTION



HEAVY DUTY LATCHES



IMPACT RESISTANT MATERIAL



DUST AND WATER RESISTANT



18V LI-ION

CORDLESS


CORDLESS DRILLS



DX13

CORDLESS 18V 1/2 IN BRUSHLESS HAMMER DRILL

1239017



NEW GRAPHENE Battery technology delivers 4x longer life, faster charging, and more power

700 IN/LBS of torque

Drives 0-8,800/0-35,200bpm

Removeable, lock-on auxiliary handle Slide Slock case for a stackable storage solution

Compatible with the **1 FOR ALL** 18V Platform


2-speed all metal gear box

SPECIFICATIONS

Voltage	18V	Max cutting capacity	Wood 2-5/32"
Chuck size	1/2"		Metal 1/2"
No load speed	0-550/0-2,200 rpm		Masonry 5/8"
Impact rate	0-8,800/0-32,000 bpm		

INCLUDED

5.0 Ah Graphene battery pack	Auxiliary handle
15A charger	Slide Lock storage case
Belt clip	



**BRUSHLESS™
MOTOR**

10x

LONGER
LIFE

25%

MORE
POWER

50%

MORE
RUNTIME

DX11

CORDLESS 18V 1/2 IN BRUSHLESS DRILL DRIVER

1239015



600 IN/LBS of torque

2-speed all metal gear box

Textured over mold grip increases user comfort

Variable speed trigger provides greater user control

Compatible with the 1 FOR ALL 18V Platform

SPECIFICATIONS

Voltage	18V	Max torque	600 in/lbs
Chuck size	1/2" keyless metal chuck	Max drilling capacity	wood 1-5/8"
No load speed	0-600/0-2,000 rpm		metal 1/2"

INCLUDED

(2) 2.0Ah Li-ion batteries	Belt clip
4A charger	Slide Lock storage case



DX12

CORDLESS 18V 1/2 IN BRUSHLESS HAMMER DRILL

1239016



600 IN/LBS of torque

2-speed all metal gear box

Textured over mold grip increases users comfort

Compatible with the 1 FOR ALL 18V Platform

Drives 0-8,000/0-32,000bpm to for a variety of concrete and masonry applications

SPECIFICATIONS

Voltage	18V	Max torque	600 in/lbs
Chuck size	1/2" keyless metal chuck	Max drilling capacity	Wood 1-5/8"
No load speed	0-600/0-2,000 rpm		Metal 1/2"
Impact rate	0-8,000/0-32,000 bpm		Masonry 5/8"

INCLUDED

(2) 2.0Ah Li-ion batteries	Belt clip
4A charger	Slide Lock storage case





DX12K

CORDLESS 18V BRUSHLESS 1/4 IN IMPACT DRIVER & 1/2 IN HAMMER DRILL KIT

1239173



DX12

2-speed all metal gear box

Textured over-mold grip increases user comfort

Compatible with the 1 FOR ALL 18V Platform

DX71

3-speed gear box

Textured over mold grip increases users comfort

Compatible with the 1 FOR ALL 18V Platform

SPECIFICATIONS

DX12		DX71	
Voltage	18V	Voltage	18V
Chuck size	1/2" keyless metal chuck	Chuck size	1/4" hex
No load speed	0-600/0-2,000 rpm	No load speed	0-1,300/2,100/3,200 rpm
Impact rate	0-8,000/0-32,000 bpm	Impact rate	0-1,600/2,900/3,600 bpm
Max torque	600 in/lbs	Max Torque	1,900 in/lbs

INCLUDED

(2) 2.0 Ah Li-ion batteries

4A charger

(2) Belt clips

Slide Lock storage case





DX21

CORDLESS 18V BRUSHLESS SDS-PLUS ROTARY HAMMER

1239307



2.2 Joules (1.6 FT/LBS) of impact energy

360° side handle with depth gauge

5 functions: Drill, Hammer Drill, Chisel, Bit Rotation and Impulse tile drilling

Anti-vibration design to reduce user fatigue

Mechanical and automatic electronic dual safety clutch system providing maximum protection

Textured over mold grip increases users comfort

Compatible with the 1 FOR ALL 18V Platform

SPECIFICATIONS

Voltage	18V	Max torque	2.2 Joules (1.6 ft/lbs)
Chuck size	1" SDS Plus	Max drilling capacity	Wood 1-1/4"
No load speed	0-1,210 rpm		Steel 1/2"
Impact rate	0-5,400 bpm		Concrete 1"

INCLUDED

4.0 Ah Li-ion battery

4A charger

Auxiliary handle

Depth gauge

Slide Lock storage case



SAWS/SANDERS

CORDLESS

18V

DX532

CORDLESS 18V 7-1/4 IN BRUSHLESS CIRCULAR SAW

1265004



Magnesium base and upper and lower guard for light weight design

7-1/4" thin kerf blade optimizes performance for faster more efficient cutting

Beveltrack technology improves accuracy when cutting a variety of angles

0-56° bevel capacity

Advanced overload protection and electronic brake

Textured over mold grip increases users comfort

Spindle lock and hex key storage for fast blade changes

SPECIFICATIONS

Voltage	18V	Bevel capacity	0-56°
Blade size	7-1/4"	Max cutting capacity	45° 1-3/16"
No load speed	5,500 rpm		90° 2-9/16"

INCLUDED

(2) 4.0 Ah Li-ion batteries	Rafter hook
4A charger	24T TCT blade
Hex key	Parallel guide
Vacuum adapter	



DX41B

CORDLESS 18V BRUSHLESS OSCILLATING TOOL

1280007



Multi-tool can be used for Cutting, detailing, or sanding

Battery and charger not included

Textured over mold grip increases users comfort

Tool-free universal attachment system makes changing accessories quick and easy

Variable speed dial for precision control

SPECIFICATIONS

Voltage	18V	No load speed	8,000-19,000 opm
Oscillation angle	4.0°		

INCLUDED

1-3/8" Precise end cutting	Scraper blade
1-3/8" Bi-metal end cutting blade	Sanding base
3-1/8" HSS segment saw blade	(9) Sanding sheets (40#/80#/120#)



DX51B

CORDLESS 18V BRUSHLESS JIGSAW

1280005



4-Position orbital action delivers precise cutting and control of cut

Tool-Free blade clamp accepts T-Shank blades for professional results

Tool-Free bevel base adjustment for 0-45° cutting left or right

Textured over mold grip increases users comfort

Battery and charger not included

Non-marring shoe cover to protect finished surfaces

SPECIFICATIONS

Voltage	18V	Max cutting capacity	Wood 4-3/4"
Stroke length	1"		Steel 25/64"
No load speed	0-3,500 spm		PVC 25/32"
Impact rate	0-45°		

INCLUDED

Blade for wood	Base cover
Dust adapter	Parallel guide





DX52

CORDLESS 18V BRUSHLESS RECIPROCATING SAW

1270210



4.0Ah 18V Lithium Ion battery that communicates with the tool for ultimate performance

Orbital action function facilitates aggressive cutting

Textured over mold grip increases users comfort

Tool Free adjustable shoe

Tool Free blade clamp

Compatible with the **1 FOR ALL** 18V Platform

SPECIFICATIONS

Voltage	18V	Max cutting capacity	Wood 11-3/4"
Stroke length	1-3/16"		Steel sheet 1/2"
No load speed	0-3,000 spm		

INCLUDED

Blade for wood	4A Charger
4.0 Ah Li-ion battery	Slide Lock storage case



DX42B

CORDLESS 18V BRUSHLESS PALM SANDER

1262005



2-in-1 function: random orbit sander or polisher

Dust sealed ON/OFF switch with brake function

Universal hook & loop system allows for easy sandpaper installation

Dust bag can be easily removed for emptying or to connect sander to dust collection system

Compatible with the **1 FOR ALL** 18V Platform

Battery and charger not included

SPECIFICATIONS

Voltage	18V	No load speed	3,000-11,000 rpm
Base size	5" (for Sanding)	Orbital diameter	3/32"
	6" (for Polishing)		

INCLUDED

Dust bag	(3) Sanding papers (60#/80#/120#)
6" polishing foam pad	



CORDLESS

BATTERIES/CHARGERS

18V

GXB5 18V 5.0 AH GRAPHENE BATTERY

5350040

18V



GRAPHENE™



Slide pack design 100% compatible with all 1 FOR ALL 18V cordless tools

On-board fuel gauge provides charge status

NEW GRAPHENE Battery technology delivers 4x longer life, faster charging, and extreme low temperature operation

4X Faster charging speed, with 15A charger (DXC15) Graphene battery fully charges within 20 minutes.

SPECIFICATIONS

Voltage	18V	Watt hour	90
Battery capacity	5.0 Ah		



GRAPHENE™
BATTERY™



DXB2

18V 2.0 AH LI-ION BATTERY

5350039

18V



Slide pack design 100% compatible with all **1 FOR ALL** 18V cordless tools

Communication technology allows battery and tool to talk providing maximum performance

On-board fuel gauge provides charge status

BMS (battery management system) communicates with tool to provide maximum performance

SPECIFICATIONS

Voltage	18V	Watt hour	36
Battery capacity	2.0 Ah		



DXB4

18V 4.0 AH LI-ION BATTERY

5350038

18V



Slide pack design 100% compatible with all **1 FOR ALL** 18V cordless tools

Communication technology allows battery and tool to talk providing maximum performance

On-board fuel gauge provides charge status

BMS (battery management system) communicates with tool to provide maximum performance

SPECIFICATIONS

Voltage	18V	Battery capacity	72
Battery capacity	4.0 Ah		



DXC4

18V 4A QUICK CHARGER

5350039

Charging diagnostics provides battery state of health and charge indication

Pre-charging with lower current when the battery is on low voltage

CMS (Charge Management System) intelligently identifies each battery pack to provide the fastest charge time



SPECIFICATIONS

Voltage	120V~60Hz	Input power	95W
Output voltage	20W	Charge current	4A

DXC15

18V 15A EXPRESS CHARGER

5350038

Charging diagnostics provides battery state of health and charge indication

Pre-charging with lower current when the battery is on low voltage

CMS (Charge Management System) intelligently identifies each battery pack to provide the fastest charge time



SPECIFICATIONS

Voltage	120V~60Hz	Input power	380W
Output voltage	20W	Charge current	4A (DXB2)
			8.0A (DXB4)
			15A (GXB5)



CORDED

DRILLS

CORDED

DX161U

CORDED 8.5A 1/2 IN HAMMER DRILL

1240002



1/2 in.
CHUCK



**VARIABLE
SPEED**
WITH REVERSE



3000
RPM



10
FT



8.5 AMP

Aluminum gear box delivers the ultimate durability for the toughest applications

Lock-on switch for continuous use

Rubber over-mold grip with 360° side handle with depth gauge

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated Power	8.5A	Drilling capacity	masonry 3/4"
Chuck size	1/2" Heavy duty metal chuck		metal 1/2"
No load speed	0-3,000 rpm		wood 1-3/8"
Impact rate	0-48,000 bpm		

INCLUDED

Depth gauge	Auxiliary handle
-------------	------------------



DX26U

CORDED 1 IN SDS-PLUS ROTARY HAMMER

1239600



Select from 4 versatile functions to Drill, Hammer Drill, Bit Rotation and Chisel

Swiveling ball joint cord connection for ease of mobility and prolonged cord life

Lock-on switch for continuous use

Extra-long 10ft. trade-length power cord

Rubber over-mold grip with 360° side handle with depth gauge

SPECIFICATIONS

Rated power	8A	Impact energy	3 Joules (2 ft-lbs)
Chuck Type	1" SDS-Plus	Drilling capacity	Masonry 1"
No-load Speed	0-1,200 rpm		Metal 1/2"
Impact Rate	0-5,300 bpm		Wood 1-3/16"

INCLUDED

Auxiliary handle	Dust cover
Depth gauge	BMC case

DX27U

CORDED 1-1/4 IN SDS-PLUS ROTARY HAMMER

1239601



Select from 4 versatile functions to Drill, Hammer Drill, Bit Rotation and Chisel

Rubber over-mold grip with 360° side handle with depth gauge

Lightweight aluminum gear box delivers the ultimate durability for the toughest applications

Swiveling ball joint cord connection for ease of mobility and prolonged cord life

Anti-vibration design to maximize users' comfort

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated power	12.5A	Impact energy	5 Joules (3.7 ft-lbs)
Chuck Type	SDS-Plus	Drilling capacity	Masonry 1-1/4"
No-load Speed	0-920 rpm		Metal 1/2"
Impact Rate	0-3,700 bpm		Wood 1-1/2"

INCLUDED

Auxiliary handle	Dust cover
Depth gauge	BMC case



SAWS/SANDERS

CORDED

DX57

CORDED 7A JIG SAW

1268601



Lock-on switch for continuous operation

4-Position orbital action

Lightweight aluminum gear box delivers the ultimate durability for the toughest applications

Tool-less blade clamp

Tool-less left-to-right beveling base adjustment allows the user to cut up to 45°

Rubber over-mold grip increases users' comfort and control

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Voltage	7A	Cutting capacity	Wood 4"
No load speed	800-3,000 spm		Aluminum 1"
Bevel capacity	0-45°		Steel 3/8"

INCLUDED

Vacuum adapter	Wood cutting blade
Parallel guide	



DX49U

CORDED 3.5A OSCILLATING MULTI-TOOL

1281864



Powerful 3.5A motor delivers variable speed from 11,000-20,000 OPM to provide optimal control in any application

Slide on/off switch for continuous operation

Lightweight aluminum gear box delivers the ultimate durability for the toughest applications

Tool-free universal attachment system makes changing accessories quick and easy

Rubber over-mold grip increases users' comfort and control

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated power	3.5A	Oscillations angle	3.2°
No-load speed	11,000-20,000 OPM		

INCLUDED

1-3/8" Precise end cutting blade	Sanding base
1-3/8" Bi-metal end cutting blade	Sanding sheets (40#/80#/120#)
3-1/8" HSS segment saw blade	Slide Lock storage case
Scraper blade	



DX58U

CORDED 12A RECIPROCATING SAW

1270002



Powerful 12A motor delivers 2,800spm to provide optimal control in any application

4 stage orbital action provides fast and aggressive cutting

Lightweight aluminum gear box delivers the ultimate durability for the toughest applications

Tool-free blade clamp

Tool Free Shoe Adjustment

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated power	12A	Cutting capacity	Wood 11-3/4"
No-load speed	0-2,800 SPM		Steel sheet 1/2"
Stroke length	1-3/16"		

INCLUDED

Wood cutting blade	Rafter hook
--------------------	-------------





DX361U

CORDED 13A 5 IN ANGLE GRINDER

1250002



5in.



10000
OPM



10
FT



13AMP

Powerful 13A motor delivers 10,000RPM for tough grinding and cutting applications

Soft start function to ensure smooth start-ups

Spindle lock for disc and accessory changes

2 position anti-vibration auxiliary handle design to maximize users' comfort

Advanced ventilation system

Rubber over-mold grip increases users' comfort and control

Innovative on-board storage for spanner wrench in auxiliary handle

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated power	13A	No-load speed	10,000 opm
Disc size	5"		

INCLUDED

Anti-vibration auxiliary handle	Quick change grinding guard
Spanner wrench	Quick change cutting guard
5" Grinding wheel	



DX36U

CORDED 13A 5 IN ANGLE GRINDER

1250001



4.5in.



12000
RPM



10
FT



7AMP

Powerful 7A motor delivers 12,000RPM for tough applications

Slim body design for reduced user fatigue and improved control

Slide on/off switch for continuous operation with accidental start protection

Spindle lock for disc and accessory changes

2 position anti-vibration auxiliary handle designed to maximize users' comfort

Advanced ventilation system

Detachable grating system protects from debris damage

Innovative on-board storage for spanner wrench in auxiliary handle

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated power	7A	No-load speed	12,000 opm
Disc size	4.5 in		

INCLUDED

Anti-vibration auxiliary handle	4.5" Grinding wheel
Spanner wrench	Quick change grinding guard

DX48U

CORDED 8.5A BELT SANDER

1262800



1150
SFPM



8.5AMP

Powerful 8.5A motor delivers variable speed control from 790-1,150SFPM so you can match the speed to the desired material removal rate

Lock-on switch for continuous operation

Rubber over-mold grip

Belt centering system adjustment

Dust Collection System to keep your material clear of debris

Quick release belt change lever to quickly remove/install sanding belts

Extra-long 10ft. trade-length power cord

SPECIFICATIONS

Rated power	8.5A	Belt size	3"x21"
No-load speed	790-1150 SFPM		

INCLUDED

Dust bag	3" x21" Sanding belt
-----------------	-----------------------------



DX47U

CORDED 2.4A 1/4 SHEET SANDER

1262303



14000
OPM



2.4 AMP



CDS

Powerful 2.4A motor delivers 14,000OPM for smooth sanding leaving a superior finish

Dust sealed ON/OFF switch

Hook & loop quick clamp system allows for easy sandpaper installation

CDS™ (Cyclonic Dust/Air Separator) effectively separates dust from the air and maintains constant suction. No bag = No loss of air suction

Swiveling ball joint cord connection for ease of mobility and prolonged cord life

Extra-long 10 FT. trade-length power cord

SPECIFICATIONS

Rated power	2.4A	Orbital diameter	1/16"
No-load speed	14000 OPM		

INCLUDED

80 grit sanding paper	Paper punch
Cyclone bin	Vacuum adapter





DX46U

CORDED 3A 5 IN RANDOM ORBIT SANDER

1262004



Powerful 3A motor delivers variable speed control from 5,000-14,000OPM for smooth finish sanding

Rubber over-mold grip increases users' comfort and control

Dust sealed ON/OFF switch for continuous operation with brake function

Swiveling ball joint cord connection for ease of mobility and prolonged cord life

Universal hook & loop system allows for easy sandpaper installation

Extra-long 10ft. trade-length power cord

CDS™ (Cyclonic Dust/Air Separator) effectively separates dust from the air and maintains constant suction, No bag = No loss of air suction

SPECIFICATIONS

Rated power	3A	No-load speed	5000-14000 opm
Base diameter	5"		

INCLUDED

Cyclone bin	Vacuum adapter
80 grit clamp sanding paper	





©2021 Caterpillar. CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. Positec Group Limited, a licensee of Caterpillar Inc.