



SUMMER 2022

NEW PRODUCT CATALOG

DK2 CANADA

5330 Mainway
Burlington, Ontario
L7L 6A4, Canada

DK2 USA WEST

3311 Meade Avenue Ste
E Dock 13, Las Vegas
Nevada, 89102, United States

DK2 USA EAST

3750 South Avenue
North Unit, Toledo, Ohio
43615, United States

1 (888) 277-6960
info@detailk2.com
detailk2.com

27-TON HORIZONTAL & VERTICAL HYDRAULIC LOG SPLITTER



ITEM NUMBER

OPS227

UPC

827518008577

DESCRIPTION

Introducing the 27-ton horizontal and vertical hydraulic log splitter. The DK2 POWER OPS227 is driven by a powerful KOHLER® SH265 6.5HP 196cc engine.

This machine is capable of splitting up to 25.5 inches in length and 19.6 inches in diameter with uncompromising force at a cycle speed of 13 seconds, all while using the full potential of its welded cross wedge. The OPS227 sits on 16-inch 4.8-8 tires and includes a tow bar for easy job site moving. This unit is not designed for highway towing.

SPECIFICATION

ENGINE	KOHLER® SH265 6.5HP 196cc
LOG CAPACITY	25.5" (L) x Ø21.6" 64.7cm (L) x Ø54.8cm
CYCLE TIME	13 seconds
CYLINDER	Ø4" (Ø10.2cm) x 24" (61cm) stroke
PUMP	15GPM (56.8LPM), two-Stage
WEDGE	8" (20.3cm) high, heat-treated steel
BEAM	8" (20.3cm) foot plate
HYDRAULIC CAPACITY	6.5 gallons (24.6 litres) max
VALVE	Auto-return with adjustable detent
WHEELS	D.O.T. approved 16" (40.6cm) O.D. road tires Not highway towable and 25mph (40km/h) maximum
COUPLER	2" (5.08cm) ball with safety chains
ASSEMBLED DIMENSIONS & WEIGHT	87.4" (L) x 49.2" (W) x 35.8" (H) @ 507lb 222cm (L) x 125cm (W) x 91cm (H) @ 230kg
SHIPPING DIMENSIONS & WEIGHT	70.9" (L) x 31.5" (W) x 19.7" (H) @ 551.2lb 180cm (L) x 80cm (W) x 50cm (H) @ 250kg
WARRANTY	2-year KOHLER® warranty 1-year DK2 limited warranty on chassis



FEATURES

- Powered by a KOHLER® SH265 6.5HP 196cc engine
- 25.5" x Ø19.6" (64.8cm x Ø49.8cm) log capacity
- Welded cross wedge **1**
- 13-second cycling time
- D.O.T. approved 16" O.D. road tires **(NOT highway towable and 25mph (40km/h) maximum) 2**
- Folds 90° for both horizontal and vertical log splitting capability **3**
- Two-stage 15GPM (56.8LPM) pump
- 6.5 gallon (24.6 litres) hydraulic fluid capacity
- Auto-return valve with adjustable detent
- 2" (5.08cm) ball coupler with safety chains
- Includes 2-year KOHLER® warranty and 1-year DK2 chassis warranty

DISTRIBUTOR PRICE

\$1,675.00 USD



32-TON HORIZONTAL & VERTICAL HYDRAULIC LOG SPLITTER



ITEM NUMBER

OPS232

UPC

827518008584

DESCRIPTION

Introducing the 32-ton horizontal and vertical hydraulic log splitter. The DK2 POWER OPS232 is driven by a powerful KOHLER® SH265 6.5HP 196cc engine.

This machine is capable of splitting up to 25.5 inches in length and 21.6 inches in diameter with uncompromising force at a cycle speed of 13 seconds, all while using the full potential of its welded cross wedge. The OPS232 sits on 16-inch 6.5-8 tires and includes a tow bar for easy job site moving. This unit is not designed for highway towing.

SPECIFICATION

ENGINE	KOHLER® SH265 6.5HP 196cc
LOG CAPACITY	25.5" (L) x Ø21.6" 64.7cm (L) x Ø54.8cm
CYCLE TIME	13 seconds
CYLINDER	Ø4.5" (11.4cm) x 24" (61cm) stroke
PUMP	15GPM (56.8LPM), two-Stage
WEDGE	8.5" (21.6cm) high, heat-treated steel
BEAM	8.5" (21.6cm) foot plate
HYDRAULIC CAPACITY	8.5 gallons (32.2 litres) max
VALVE	Auto-return with adjustable detent
WHEELS	D.O.T. approved 16" (40.6cm) O.D. road tires Not highway towable and 25mph (40km/h) maximum
COUPLER	2" (5.08cm) ball with safety chains
ASSEMBLED DIMENSIONS & WEIGHT	89.3" (L) x 51.2" (W) x 37.4" (H) @ 529.1lb 227cm (L) x 130cm (W) x 95cm (H) @ 240kg
SHIPPING DIMENSIONS & WEIGHT	70.9" (L) x 31.5" (W) x 19.7" (H) @ 573.2lb 180cm (L) x 80cm (W) x 50cm (H) @ 260kg
WARRANTY	2-year KOHLER® warranty 1-year DK2 limited warranty on chassis



FEATURES

- Powered by a KOHLER® SH265 6.5HP 196cc engine
- 25.5" x Ø21.6" (64.8cm x Ø54.9cm) log capacity
- Welded cross wedge **1**
- 13-second cycling time
- D.O.T. approved 16" O.D. road tires **(NOT highway towable and 25mph (40km/h) maximum) 2**
- Folds 90° for both horizontal and vertical log splitting capability **3**
- Two-stage 15GPM (56.8LPM) pump
- 8.5 gallon (32.2 litres) hydraulic fluid capacity
- Auto-return valve with adjustable detent
- 2" (5.08cm) ball coupler with safety chains
- Includes 2-year KOHLER® warranty and 1-year DK2 chassis warranty

DISTRIBUTOR PRICE

\$1,825.00 USD



17" x 21" GAS POWERED PLATE COMPACTOR

ITEM NUMBER

OPV425

UPC

827518008249



DESCRIPTION

Featuring a large 17" x 21" base plate, the OPV425 Plate Compactor doesn't disappoint when it comes to performance, and the power that drives this machine comes from a KOHLER® CH270 7HP 208cc Command Pro Commercial Engine.

With a compacting force of 3,600 pounds (16 kilonewtons) at 4,750 vibrations per minute, this unit is the perfect solution for your compacting needs.

Designed with conveniently placed, foldable handles for easy transportation and storage, open design to reduce dirt build-up, and a central-mounted, fully enclosed exciter for even compactive force over the entire base plate.

FEATURES

- Powered by a KOHLER® CH270 7HP 208cc Command PRO® Commercial Engine
- Conveniently placed, foldable handles for easy transportation and storage **1**
- Open design to reduce dirt build-up **2**
- Central-mounted, fully enclosed exciter for even compactive force over entire base plate **3**
- Includes 3-year KOHLER® commercial warranty and 1-year DK2 Chassis warranty

DISTRIBUTOR PRICE

\$995.00 USD

SPECIFICATION

ENGINE MODEL KOHLER® CH270 7HP 208cc Command PRO® Commercial

BASE PLATE 17" x 21" (43.2cm x 53.3cm)

VIBRATION FREQUENCY 4,750vpm

CENTRIFUGAL FORCE 3,600lbf (16kn)

COMPACTION DEPTH 11.8" (30cm)

WARRANTY 3-year engine
1-year chassis



**FORGE
YOUR
OWN
PATH.**





SUMMER 2022

NEW PRODUCT CATALOG

DK2 CANADA

5330 Mainway
Burlington, Ontario
L7L 6A4, Canada

DK2 USA WEST

3311 Meade Avenue Ste
E Dock 13, Las Vegas
Nevada, 89102, United States

DK2 USA EAST

3750 South Avenue
North Unit, Toledo, Ohio
43615, United States

1 (888) 277-6960

info@detailk2.com

detailk2.com