

32-TON HORIZONTAL & VERTICAL HYDRAULIC LOG SPLITTER



ITEM NUMBER

OPS232

UPC

827518008584

DESCRIPTION

Introducing the 32-ton horizontal and vertical hydraulic log splitter. The DK2 POWER OPS232 is driven by a powerful KOHLER® SH265 6.5HP 196cc engine.

This machine is capable of splitting up to 25.5 inches in length and 21.6 inches in diameter with uncompromising force at a cycle speed of 13 seconds, all while using the full potential of its welded cross wedge. The OPS232 sits on 16-inch 6.5-8 tires and includes a tow bar for easy job site moving. This unit is not designed for highway towing.

SPECIFICATION

ENGINE	KOHLER® SH265 6.5HP 196cc
LOG CAPACITY	25.5" (L) x Ø21.6" 64.7cm (L) x Ø54.8cm
CYCLE TIME	13 seconds
CYLINDER	Ø4.5" (11.4cm) x 24" (61cm) stroke
PUMP	15GPM (56.8LPM), two-Stage
WEDGE	8.5" (21.6cm) high, heat-treated steel
BEAM	8.5" (21.6cm) foot plate
HYDRAULIC CAPACITY	8.5 gallons (32.2 litres) max
VALVE	Auto-return with adjustable detent
WHEELS	D.O.T. approved 16" (40.6cm) O.D. road tires Not highway towable and 25mph (40km/h) maximum
COUPLER	2" (5.08cm) ball with safety chains
ASSEMBLED DIMENSIONS & WEIGHT	89.3" (L) x 51.2" (W) x 37.4" (H) @ 529.1lb 227cm (L) x 130cm (W) x 95cm (H) @ 240kg
SHIPPING DIMENSIONS & WEIGHT	70.9" (L) x 31.5" (W) x 19.7" (H) @ 573.2lb 180cm (L) x 80cm (W) x 50cm (H) @ 260kg
WARRANTY	2-year KOHLER® warranty 1-year DK2 limited warranty on chassis



FEATURES

- Powered by a KOHLER® SH265 6.5HP 196cc engine
- 25.5" x Ø21.6" (64.8cm x Ø54.9cm) log capacity
- Welded cross wedge **1**
- 13-second cycling time
- D.O.T. approved 16" O.D. road tires **(NOT highway towable and 25mph (40km/h) maximum) 2**
- Folds 90° for both horizontal and vertical log splitting capability **3**
- Two-stage 15GPM (56.8LPM) pump
- 8.5 gallon (32.2 litres) hydraulic fluid capacity
- Auto-return valve with adjustable detent
- 2" (5.08cm) ball coupler with safety chains
- Includes 2-year KOHLER® warranty and 1-year DK2 chassis warranty

Powered by
KOHLER®
Engines

