



3-POINT SPECIFICATIONS

BOOM POLES

	BP	HDBP
Lift Capacity	1000 lbs. (rear loop)/ 500 lbs. (front loop)	2000 lbs. (rear points)/ 1000 lbs. (front loop)
Hitch	Cat 1	Cat 1 & 2/ quick hitch compatible
Height	25-1/2"	24-1/2"
Width	32"	40"
Length	85-1/2"	95"
Weight	66 lbs.	150 lbs.
Features	multiple welded lifting loops	HD Category 1 and 2 hitch pins, Multiple welded lifting points

FINISH MOWER

	FM5	FM6
Horsepower	20-60 hp	20-60 hp
Hitch	Cat 1/ quick hitch compatible w/ floating top link	Cat 1/ quick hitch compatible w/ floating top link
Cutting Width	60"	72"
Height	34"	34"
Length	71"	73"
Weight	628 lbs.	670 lbs.
Gearbox	Cast Iron Housing w/ heat treated gears	Cast Iron Housing w/ heat treated gears
Blade Spindles	3 cast iron housings/ greasable bearings	3 cast iron housings/ greasable bearings
PTO Speed	540 rpm	540 rpm
Discharge	rear	rear
Cutting Height	.75-5.25" adjustable bushings	.75-5.25" adjustable bushings
Caster Wheel	10" diameter tires x 3.15" wide with nylon bushing	10" diameter tires x 3.15" wide with nylon bushing