

U1P-Drive - Full Synthetic Motor Oil

SAE 0W-20 API SP, ILSAC GF-6A

Auto – Light Truck | United States

Product Description

U1P-DRIVE SAE 0W-20 Full Synthetic Motor Oil, API SP, ILSAC GF-6A is a high performance full synthetic multigrade motor oil formulated for gasoline engines, combining 100% full synthetic base stocks with an Ultra-premium high performance additive package. This oil is designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines in both normal and extreme operating conditions.

U1P-DRIVE SAE 0W-20 Full Synthetic Motor Oil, API SP, ILSAC GF-6A exceeds the performance requirements of API SP, ILSAC GF-6A, and GM dexos1™ Gen 2 quality certifications. Delivers engine protection and cleanliness. Recommended for on-road and off-road use, light duty, and heavy duty. Creates a strong lubricant film in both cold and hot weather. Excellent for American, European, and Asian gasoline engines that require API SP quality motor oil and previous certifications. Substitutes older API (SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC, SB, SA).

Features and Benefits

- Longer engine life.
- Excellent overall lubrication and wear protection even at extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
QT	UFS020SPGF6AL	UL101	810050650120
1 US Gallon	UFS020SPGF6AG	UL101	810050650113
1 JUG (5 QTS)	UFS020SPGF6AJ	UL101	810050658249
5 Gallon Pail	UFS020SPGF6AP	UL101	810050650106
55 Gallon Drum	UFS020SPGF6AD	UL101	810050650090
265 Gallon Tote	UFS020SPGF6AT	UL101	810050650083



This product meets or exceeds the requirements of:

API SP, API SN Plus with Resource Conserving, API SN, API SM, API SL, API SJ

ILSAC GF-5

GM dexos1™ Gen 2

Chrysler MS6395

Ford WSS-M2C947-A (0W-20)



Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	44.55
Viscosity @ 100°C, cSt, ASTM D445	8.3
Viscosity index, ASTM D2270	165
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C
Pour point, °C, ASTM D97	-47
Flash point, °C, ASTM D92	210

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



Revised: 04/04/2025