

U1P-Drive Full Synthetic Motor Oil

5W-40 API SP

Auto – Light Truck | United States

Product Description

U1P-DRIVE SAE 5W-40 Full Synthetic Motor Oil, API SP is a high performance full synthetic multigrade motor oil formulated for gasoline engines, combining 100% full synthetic base stocks with an Ultra-premium high performance additive package. This oil is designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines in both normal and extreme operating conditions.

U1P-DRIVE SAE 5W-40 Full Synthetic Motor Oil, API SP exceeds the performance requirements of API SP quality certification. Delivers engine protection and cleanliness. Recommended for on-road and off-road use, light duty, and heavy duty. Creates a strong lubricant film in both cold and hot weather. Excellent for American, European, and Asian gasoline engines that require API SP quality motor oil and previous certifications. Substitutes older API (SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC, SB, SA).

Features and Benefits

- Longer Engine life.
- Excellent overall lubrication and wear protection even at extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
1.05 QT / 1 Liter	UFS0540SPL	UL105	810050650366
1 US Gallon	UFS0540SPG	UL105	810050650359
5 Gallon Pail	UFS0540SPP	UL105	810050650342
55 Gallon Drum	UFS0540SPD	UL105	810050650335
265 Gallon Tote	UFS0540SPT	UL105	810050650328



This product meets or exceeds the requirements of:

API SP, API SN, API SM, API SL, API SJ

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	86.8
Viscosity @ 100°C, cSt, ASTM D445	14.5
Viscosity index, ASTM D2270	175
CCS Apparent Viscosity, cP, ASTM D5293	5,200@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-35°C
Pour point, °C, ASTM D97	-42
Flash point, °C, ASTM D92	215



*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023