

## U1P-Bike - 4T Full Synthetic Motor Oil

# SAE 20W-50 API SN, JASO MA2

MotorCycle – ATV | United States

### Product Description

Ultra 100% synthetic 4-Stroke engine oil. Top performance formula that meets and exceeds the highest industry standard JASO MA2 API SN specifications. Top technology 100 % synthetic base-stock with precisely balanced Ultra high-performance additive package. Allow maximum power delivery by reducing internal friction for exceptional wear protection, Increasing engine life for on-road, off-road, street or motorsports. Proven at extreme temperature racing conditions, speed, and endurance.



### Features and Benefits

- For all 4-stroke motorcycles and ATVs with or without catalytic converters.
- For engines with or without integrated gear box, transmission. Wet or dry clutch.
- JASO MA2 API SN ensures optimum clutch performance at start-up, acceleration, and full speed.
- Exceptional wear protection extending engine, gear box and clutch life, leading to reduced maintenance cost.
- For liquid cooled or air-cooled engines. Improves thermal stability and fuel efficiency.
- Improved high temperature deposit protection for engine cleanliness and minimum sludge build up.
- Reduces oil thickening facilitating extended oil life, inside the manufacturer's oil change interval recommendation.
- Smoother shifting and enhanced clutch feeling and precision.



**Product Code**

Presentation	SKU	Manufacture ID	UPC
1 QT	UFS20504TSNMA2L	UL412	810050652582
5 Gallon Pail	UFS20504TSNMA2P	UL412	810050652568
55 Gallon Drum	UFS20504TSNMA2D	UL412	810050652551
265 Gallon Tote	UFS20504TSNMA2T	UL412	810050652544



**This product meets or exceeds the requirements of:**

API SN  
JASO MA  
JASO MA2

**Properties and Specifications\***

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	183.9
Viscosity @ 100°C, cSt, ASTM D445	21.5
Viscosity index, ASTM D2270	140
CCS Apparent Viscosity, cP, ASTM D5293	5,200@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	17,000@-20°C
Pour point, °C, ASTM D97	-30
Flash point, °C, ASTM D92	230

\*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 07/01/2025