

U1P-Bike - 4T Synthetic Blend Motor Oil

SAE 20W-50 API SL, JASO MA2

Motorcycle – ATV | United States

Product Description

Ultra synthetic blend 4-Stroke engine oil. High performance formula that meets and exceeds the highest industry standard JASO MA2 and API SL specification. A top technology blend of synthetic and mineral base-stocks with precisely balanced high performance additive package. Allow maximum power delivery by reducing internal friction for exceptional wear protection, increasing engine life for on-road and off-road. Proven at extreme temperature severe riding conditions, high speed, acceleration and endurance on the open road, countryside and in dense city traffic.



Features and Benefits

- For all 4-stroke motorcycles and ATVs with or without catalytic converters.
- For engines with or without integrated gear box, transmission. Wet or dry clutch.
- JASO MA2 API SL ensures optimum clutch performance at start-up, acceleration, and full speed.
- Exceptional wear protection extending engine, gear box and clutch life, leading to reduced maintenance cost.
- For liquid cooled or air-cooled engines. Improves thermal stability and fuel efficiency.
- Improved high temperature deposit protection for engine cleanliness and minimum sludge build up.
- Reduces oil thickening facilitating extended oil life, inside the manufacturer's oil change interval recommendation.
- Smoother shifting and enhanced clutch feeling and precision.



Product Code

Presentation	SKU	Manufacture ID	UPC
1.05 QT / 1 Liter	USB20504TSLMA2L	UL402	810050651981
5 Gallon Pail	USB20504TSLMA2P	UL402	810050651967
55 Gallon Drum	USB20504TSLMA2D	UL402	810050651950
265 Gallon Tote	USB20504TSLMA2T	UL402	810050651943



This product meets or exceeds the requirements of:

API SL
JASO MA
JASO MA2

Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	160.55
Viscosity @ 100°C, cSt, ASTM D445	18.5
Viscosity index, ASTM D2270	130
CCS Apparent Viscosity, cP, ASTM D5293	7,000@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-20°C
Pour point, °C, ASTM D97	-30
Flash point, °C, ASTM D92	220

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023