

## 4FT x 8FT SINGLE AXLE GALVANIZED FOLDING UTILITY TRAILER

38



### ITEM NUMBER

MFT4X8G

### UPC

827518009482

### DESCRIPTION

The trailer you've always needed has arrived with the DK2 MFT4X8G folding trailer kit. High-performing, durable and versatile, this trailer is ready for work. Built with a patented welded steel frame and deck for added strength and easy assembly, you'll spend less time reading manuals and more time on the road. The DK2 MFT4X8G is coated with high-performance hot-dipped galvanized steel, all while maintaining its complete folding functionality. When it comes to trailers – there's truly nothing like it.

### SPECIFICATION

<b>PAYLOAD CAPACITY</b>	1,450 lb (657.7 kg)
<b>GVWR</b>	1,787.3 lb (810.7 kg)
<b>WHEELS &amp; TIRES</b>	D.O.T. 5.30-12 6-ply tire, 80 PSI (5.5 Bar) cold
<b>MATERIAL</b>	Fully welded heavy-duty hot-dipped galvanized tubular steel
<b>RAILS</b>	Open design, tubular steel <b>(sold separately)</b>
<b>FLOORING</b>	Solid steel, anti-slip textured
<b>LIGHTING</b>	Pre-wired, Quick-connect D.O.T LED with flat 4-wire harness and connector
<b>BED DIMENSIONS</b>	96" (L) x 48" (W) 243.8 cm (L) x 121.9 cm (W)
<b>DIMENSIONS</b>	135" (L) x 62.3" (W) x 20" (H) 342.9 cm (L) x 158.2 cm (W) x 50.8 cm (H)
<b>WEIGHT</b>	337.3 lb (153 kg)
<b>SHIPPING DIMENSIONS</b>	48.4" (L) x 62.2" (W) x 7.9" (H) 122.9 cm (L) x 158 cm (W) x 20.1 cm (H)
<b>SHIPPING WEIGHT</b>	368.2 lb (167 kg)
<b>WARRANTY</b>	1-year limited



### FEATURES

- Folding design to fit into compact spaces vertically **1**
- Constructed with fully welded heavy-duty hot-dipped galvanized tubular steel
- Solid galvanized steel bed **2**
- 5.30-12 6-ply tires **3**
- Trolley wheels for easy stowaway transport while folded **4**
- Pre-wired quick-connect D.O.T. LED lighting with flat 4-wire harness and connector
- 2" (5.08 cm) coupler with safety chain and S-hook
- 8 stake holes for the MFT4X8RK fully welded tubular steel open rail kit **(sold separately)** **5**
- Includes all necessary paperwork for registration

### FOLDING DESIGN

