TECHNICAL DATA

VAR-79



VARATHANE[®] FURNITURE, WOOD FLOOR, AND WOOD LAMINATE MARKERS

DESCRIPTION AND USES

The Varathane[®] Furniture, Wood Floor, and Wood Laminate Markers quickly repair scratches to various stained wood tones and wood laminate surfaces. Varathane markers are ideal for hard to reach areas, repairing minor scratches and blemishes in furniture, cabinets, molding, floors, and more. Use the markers as a perfect complement to Varathane wood stains.

PRODUCTS

SKU	DESCRIPTION	
347840	Marker Set	
SIZE	E DESCRIPTION (Set Contents)	
0.13 Fl. Oz.	Maple Marker	
0.13 Fl. Oz.	Gray Marker	
0.13 Fl. Oz.	Cherry Marker	
0.13 Fl. Oz.	Walnut Marker	
0.13 Fl. Oz.	Mahogany Marker	
0.13 Fl. Oz.	Fl. Oz. Black Marker	
SKU	DESCRIPTION	
374189	Marker Set	
SIZE	DESCRIPTION (Set Contents)	
SIZE 0.13 Fl. Oz.	DESCRIPTION (Set Contents) White Marker	
-	• •	
0.13 Fl. Oz.	White Marker	
0.13 Fl. Oz. 0.13 Fl. Oz.	White Marker Boardwalk Marker	
0.13 Fl. Oz. 0.13 Fl. Oz. 0.13 Fl. Oz. 0.13 Fl. Oz.	White Marker Boardwalk Marker Carbon Gray Marker	

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants. Rinse with fresh water and allow to thoroughly dry.

APPLICATION

1. Prior to repairs, determine the Varathane Furniture, Wood Floor, and Wood Laminate Marker that best matches your wood project.

See each cap for color identification.

2. Test the Varathane Furniture, Wood Floor, and Wood Laminate Markers in an inconspicuous area to ensure color match. If the color matches, press marker to damaged area. Reapply to darken.

3. Carefully remove excess pigment with a soft, lint-free cloth and let dry.

4. Tightly cap each marker after use.

PHYSICAL PROPERTIES		
		FURNITURE, WOOD FLOOR, AND LAMINATE MARKERS
Resin		Rosin
Solvents		Ethyl Alcohol, Propylene Glycol
Solids By Weight		0.84%
VOC		488 g/l
Dry Times at 70°F (21°C) and 50% Relative Humidity	Touch	5 minutes
	Handle	10 minutes
	Fully Dry	15 minutes
Shelf Life		3 years
Flash Point		60°F
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061

Phone: 800-901-0411 www.rustoleum.com/varathane