

Description

WS 1805 Gel is an innovative ceramic protective coating for welding processes. With a single application it forms a film that effectively protects welding equipment for up to 8 hours.

No cleaning of the equipment is required, which reduces costs, improves productivity and is compatible with painting processes.

Thanks to its ceramic formula this product performs up to 8 times better than any Gel on the world market.

Features

- Regular use extends the life of nozzles in torches, reducing consumable costs by up to 70%.
- 90% cheaper than other gels on the market.
- Increases productivity by 11%.
- Exceptional lubrication and separating effect.
- Protects against corrosion.
- Stabilises the welding arc, ensuring the free flow of gas.
- Solvent-free.
- Silicone free.
- 100% active product, does not contain solvents or water.
- Non-flammable.
- Pack of 500 gr.

Applications

- MIG/MAG hand torches.

Instructions for use

- Dip the tip of the hot nozzle into the solid gel.
- A homogeneous film must be applied.
- It is recommended to use small quantities of product, excess is not recommended.
- Excess product can be removed by shaking the torch.

Demo
1805 Gel





Technical Data

Property	Specification/Method	Value
Reference	- - - - -	WS 1805 Gel
Aspect	- - - - -	Gel
Colour	- - - - -	White
Density	- - - - -	0.85 gr/cm3
Maximum temperature	Dry Film	1200°C



Whale Spray S.L.

P.I. Ametlla Park.
L'Ametlla del Vallès.
08480 - Barcelona, Spain.
T. : +34 93 882 77 12
whalespray@whalespray.com

All data contained in this document are based on experience and laboratory tests. The wide range of equipment and environmental conditions as well as unforeseen human factors may influence the application results to a greater or lesser extent. For this reason we advise you to check the compatibility of the product before use. This information is based on reliable experience, but is merely indicative.