

MAX TIGHT SQUARE KNOT HORSE FENCE

Designed for the serious horseman, the Max-Tight Suare Knot Horse Fence is manufactured using the Max-Tight Horse Safe Knot. This square knot provides extra vertical strength to withstand the impact of large animals. It also allows flexibility for installation on hilly terrain. Class I Galvanized Horse Fence resists corrosion, which results in a longer fence life. Continuous vertical and horizontal wires, wrapped in a horse-safe knot with a third wire, provide the strength and rigidity as well as the safety needed for



MAX TIGHT SQUARE KNOT SHEEP & GOAT FENCE

Need a field fence with smaller and consistent spacing throughout to contain your sheep & goats and strength of the stiff stay knot? OKBRAND manufactures Max Tight Square Knot Sheep & Goat Fence with 4" x 4" spacing from top to bottom to confine your most stubborn animals.

As with all OKBRAND Max Tight products our Horse Fence and Sheep & Goats products have the added benefit of our unique "Versi-Tail" feature. This feature allows for easier installation by adding a 8"tail at the beginning of each roll and a 8" tail at each end. This feature eliminates the need to remove cross-wire staples to allow enough wire for tying corners or splicing rolls.

What do the numbers in the product description mean? 1972-4-12.5									
<u>19</u>	<u>72″</u>	<u>4</u>	12.5						

MAX TIGHT SQUARE KNOT FIELD FENCE											
PRODUCT	NO HORIZ WIRES	FENCE HEIGHT	STAY OPENING	INSIDE WIRE GAUGE	TOP/BOTTOM GAUGE	ROLL LENTGH	APPROX WEIGHT	ROLLS/PALLET	COATING		
1036-2-12.5	10	36"	2"	12.5	10	100'	95	8	Class 1		
1348-2-12.5	13	48"	2"	12.5	10	100'	124	8	Class 1		
1660-2-12.5	16	60"	2"	12.5	10	100'	153	8	Class 1		
1972-2-12.5	19	72"	2"	12.5	10	100'	181	8	Class 1		
1348-2-12.5	13	48"	2"	12.5	10	200'	247	4	Class 1		
1660-2-12.5	16	60"	2"	12.5	10	200'	304	4	Class 1		
1348-2-12.5	13	48"	2"	12.5	10	300'	371	3	Class 1		
1660-2-12.5	16	60"	2"	12.5	10	300'	452	3	Class 1		
1348-4-12.5	13	48"	4"	12.5	10	330'	265	4	Class 1		
1660-4-12.5	16	60"	4"	12.5	10	330'	322	4	Class 1		
1972-4-12.5	19	72"	4"	12.5	10	330'		4	Class 1		



Oklahoma Steel & Wire 1042 South 1st Street Madill, Oklahoma 73446 800.654.4164



Iowa Steel & Wire 1500 West Van Buren Centerville, Iowa 52544 800.325.5118