



P-680 dog shock collar Specification

Part No.		Description	Remark	
Remote	Mode Setting	Dog 1/2		
	Shock Strength	1~16	Only Shock level adjustable	
	Vibration Strength	No		
	Voice Strength	No		
	Display	Display Module	Round Led White Module	
		Battery Sign	3 Levels	When Charging: Battery Volume Flow
		Dog 1/2	Yes	
		Level Display	1~16	Only Shock level adjustable
		Shock Sign	Yes	
		Vibration Sign	Yes	
		Tone Sign	Yes	
		LED Light		in Red when power off
	Battery	Battery Model	602030	
		Battery Capacity	300mAh	
		Charging Time	2H	
		Charging Port	Micro-USB	
		Standby Current	0.001mA≤I≤0.05mA	
		Power off Current	0.001mA≤I≤0.05mA	
		Working Current	0.8mA≤I≤1.5mA (Backlight off) 3mA≤I≤10mA (Backlight on)	
		Working Current	80mA≤I≤120mA (Sending Signal)	
Standby Time		180 Days	No Operation, No Interfere, No Shutdown	
Power off Standby Time		250 Days	Press Power off to shutdown	
Working Time		11 Days	One Function Operation 1min, 8 hours/day	
	Shock	Yes		

Receiver	Button	Vibration	Yes	When charging, Long press Tone and Vibration Button for 3 Seconds to enter Factory Settings
		Tone	Yes	
		Strength +	Yes	Sign"△"
		Strength-	Yes	Sign"▽"
		ON/OFF (Dog 1/2)	Yes	
		Dog 1/2 Switch	Yes	
	RF	Frequency	433.92MHz	
		Power	≤20dBmW	
		Transmitting Instruction	Tone: Indicator Light in Green Vibration: Indicator Light in Orange Shock: Indicator Light in Red	
	Mechanical	Waterproof	No	
		Color		
		LOGO		
		Silicon Case	Yes	
		Others		
	Display	Display Mode	LED Double Color: Red&Green	
		Low Battery Indicate	Red Light Blink each 4 Seconds	
		Standby Instruction	Green Light Blink each 4 Seconds	
		Tone Instruction	Red Light Keeps Bright (≈0.5s)	
Vibration Instruction		Red Light Keeps Bright (≈0.5s)		
Shock Instruction		Red Light Keeps Bright (≈0.5s)		
Pair Code		Green Light and Red Light Blinks by turn		
Power on Instruction		Green Light Blink One time		
Battery	Power off Instruction	Red Light Blink Four time		
	Battery Model	802025		
	Battery Capacity	300mAh		
	Charging Time	2H		
	Charging Port	Micro-USB		
	Standby Current	0.05mA≤I≤0.1mA		
	Power off Current	0.001mA≤I≤0.05mA		
	Working Current	0.5mA≤I≤1.5mA		
	Standby Time	180 Days	No Operation, No Interfere, No Shutdown	
	Power off Standby Time	250 Days	Press Power off to shutdown	
ON/OFF Button	Working Time	11 Days		
	Power Off	Long Press 3S		
	Power on	Short Press		

		Pair Code	Long press after power off to enter pairing mode	Red and Green light blink by turn to waiting for code pairing, around 30 seconds
	Working Mode	Tone Strength	SMT 9032 Toner	
		Vibration Strength		
		Shock Strength	25V±3V@500Ω	
		Vibration Button	NO	24 Hours no operation will enter deep sleep mode
		Waterproof	IPX7	
	Mechanical	Color		
		LOGO		
		Collar Length	0.75米	
		Collar Material		
Collar Tension Intensity		30KG		
Standard and Performance	FCC-ID	Yes		
	UL/CE	Yes		
	ROHS	Yes		
	DOE	Yes		
	California CEC			
	MSDS	Yes		
	UN38.3	Yes		
	Control Range	300 Meter		
Papet QA Internal Standard	Yes			
Package	Single Pack Size	160*160*42mm		
	Single Pack Weight	255g		
	Test Light	1		
	Adapter	No		
	Charging Cable	USB cable *1	1m	
	Short Contact Points	0		
	Long Silicone Cover	2		
	Metal Sheet	0		
	User Manual	1		
	Inside Support	Black Blister		
	Collar Strap	0.75m		
	Giftbox Material	Kraft Paper		
	Device per Carton	40		
	Carton Size	490*340*370MM		
	Carton Weight	11.6KG		



P-680 dog shock collar Specification

Remote Control	
N.W.	69g
Range	300M
Power	Lithium Battery
Battery Life	68 Days
Frequency (output)	433.92MHz
Antenna	Built in
Water and Dust Proof	IPX5
Communication, Encoding and Decoding	Single chip Control
Strength	Shock Level 1-16
Working Temperature	0°C - + 40 °C
Size	132.5X45X22mm
Receiver	
N.W.	44g (exclude the strap)
Power	Lithium Battery
Battery Life	11 Days
Communication Frequency	433.92MHz
Antenna	Built in
Water and Dust Proof	IPX7
Communication, Encoding and Decoding	Single chip Control
Working Temperature	0 °C - + 40 °C
Strap Length Range	22 - 49cm
Size	74.2x36.2x38mm
Shock Strength	
Max Action Time (s)	10
Lock Time(s)	5
Peak Current (mA)	≤ 80 (ECMA ≤ 150mA)
MONOPULSE energy(mJ)	≤ 0.5 (ECMA ≤ 5mJ)
Unit time output Energy(mJ/s)	≤ 300 (ECMA ≤ 500mJ/s)
Other information	
Certificate	CE;ROHS;EMC;FCC;IPX7
DETAILS:	300m remote control range. 16 levels stimulation can be adjustable individually. Remote wakes up receiver when entering sleep mode. Rechargeable for both remote and receiver collar. IPX7 waterproof for receiver collar. User-friendly big LED display. Battery indicator to check power supply anytime. Audible tone gently customized according to dog hearing system. Expandable to 2 dogs. According to ECMA.
Package Content:	1* Receiver & Adjustable Collar 1* Remote Transmitter 2* Silica column 1*Wrist Strap 1*Test Light 1*Charging Cable 1* User Manual
PACK STYLE:	Gift Box 16*16*4.2cm
QTY/CTN:	40PCS
NET Weight (kg):	11.6KGS
GROSS Weight (kg):	12KGS
CTN/SIZE (cm):	49*34*37cm