

1. Determine location of the Bike Tree-Dual. Allow sufficient room to fit bicycles.
2. Check to see if Bike Tree-Dual will be installed on a wall stud (go to step 3), or directly to the drywall (go to step 4).

3. Wall stud mounting:

Use top tube plate as a template to mark the screw locations. Make sure that the holes locations are vertical.

Drill pilot holes using an 1/8" drill bit.

4. Drywall mounting:

Use top tube as a template to mark the screw locations. Make sure that the hole locations are vertical

Install supplied self-drilling drywall anchors with a phillips screwdriver. Install until anchor head is flush with the wall. Do not overtighten.

5. To disassemble the HUB, slide the HUB off the tube, otherwise it will not disassemble. Once the HUB is off the tube it will then be able to separate into two pieces.

6. Hub assembly: (2x):

Determine hanger rod configuration (straight or angled) and insert to the hub front.

Close hub by installing hub rear.

7. Slide hub assembly to the top tube and secure location with the hub pin.

8. Slide the other hub assembly to the bottom tube and secure location with the hub pin.

9. Insert bottom tube to the top tube. Insert connector pin thru both tubes. Make sure that the pin goes all the way through.

10. Install entire unit to the wall by using the supplied screws and washers. A second person is recommended to assist in installing the screws.

If installing with the drywall anchors, you will hear a popping sound when you start installing the screws. This ensures that the anchor is firmly seated.

11. Hang bicycles (50 lbs maximum per hub assembly). Adjust hub locations if necessary.