

**DU-HOOKY****Assembly Instructions**

**1** Remove Du-Hooky from packaging and layout on a table or bench.



**2** Attach the end tube with the yellow tip to the bent tube by depressing the push button spring on the end tube and sliding it into the end of the bent tube and line up with the hole in the bent tube until the push spring button snaps into place. The end tube can be positioned in either direction so the yellow tip can be positioned in either direction.



**3** Next attach the bent tube to the re-tractable tube by depressing the push button spring on the re-tractable tube and sliding the bent tube onto the re-tractable tube, line up with hole in tube until the push spring button snaps into place. The bent tube can also be positioned in either direction, this is helpful when retrieving items and the re-tractable tube keeps loosening. You can turn the end tube the opposite direction so it stays tightened.



## DU-HOOKY

### Installation and Operation Instructions

#### Tools Required:

// 5/16" Socket // Drill or Impact Wrench

#### Installation Instructions:

- 4** Secure the mounting clip (*Item B*) to a convenient location in the bed of your pickup truck using a 5/16" socket to secure the hex head self drilling screws (*Item C*). We recommend installing over the wheel well as shown with the handle facing towards you or towards the front of the truck.

**Note:** You can also attach the mounting clip (*Item B*) to a wall in your shop or garage to keep the DU-HOOKY (*Item A*) within reach at all times. You can also use the Du-Hooky in SUV's and Van's or anywhere else you have hard to reach item's.

ITEM	QTY	DESCRIPTION
(A)	1	DU-HOOKY
(B)	1	Mounting Clip
(C)	2	Hex Head Self Drilling Screws



Shown in SUV

#### Operation Instructions:

- 5 Length Adjustment**  
Twist the DU-HOOKY (*Item A*) shaft 1/4 turn counterclockwise, then pull to extend the DU-HOOKY (*Item A*) (**DO NOT OVER-EXTEND**). Twist the DU-HOOKY (*Item A*) shaft 1/4 turn clockwise to tighten at desired length.
- 6 Tip**  
Slide tip under the item you're trying to retrieve, then turn the DU-HOOKY (*Item A*) all the way to the side, (so the front edge of the tip catches the lip of the bucket) then pull the DU-HOOKY (*Item A*) towards you, to retrieve items. This works great for getting underneath and hooking into cardboard boxes, the bottom of buckets, and anything else you can't get the hook around.
- 7 Set Screw**  
To re-position the tip, loosen the set screw using a screwdriver, then turn the tip to the desired position, and re-tighten the set screw. Do not over-tighten.  
**Note:** Tip turned sideways or in its original position works great for hanging plants and holiday decorations. Turned 180 degrees, it makes a good hook for retrieving duck decoys and lines.
- 8 Handle**  
Remove the end cap from the handle by twisting the end cap counterclockwise. This will reveal the threaded connector. The ice scraper accessory can be attached to the threaded connector. Many other standard items with a female connector, such as a paint roller, squeegee, or duster, can also be attached to the threaded connector.

